

Lift	Truck	Inspe	ection	Log
------	-------	-------	--------	-----

Month:	20
--------	----

Lift Truck ID# \_\_\_\_\_

CHECK LIST	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31
VISUAL INSPECTION																															
Propane: Relief Valve Up, Level																															
No Leaks Safety Straps																															
Rear Tire (Left)																															
Engine Compartment: Oil, Radiator																															
Air-Filter, And Fan Belt																															
Overhead Guard (Left)																															
Front Tire (Left)																															
Tilt Cylinder (Left)																															
Carriage (Left)																															
Fork Locking Pin (Left)																															
Fork (Left)																															
Mast																															
Lift Cylinder and Lift Chains																															
Carriage (Right)																															
Tilt Cylinder (Right)																															
Front Tire (Right)																															
Hydraulic Oil																															
Battery Connectors																															
Seat and Seat Belts																															
Overhead Guard (Right)																															
Rear Tire (Right)																															
Fork (Right)																															
Fork Locking Pin (Right)																															
OPERATIONAL INSPECTI	ON																														
Listen For Unusual Noise																															
Check Service and Park Brake																															
Lifting Control																															
Tilt Control																															
Forward: ACC: Steering, Braking																															
Rev: ACC: Steering, Braking																															
Lights																															
Horn																															
Gauges																															
Oil Spots on Floor																															
Operator's Initials																															

**Repairs Needed:**