# SAFETY DATA SHEET

### 1. Identification

**Product identifier** Lectra-Motive® Electric Parts Cleaner

Other means of identification

No. 05018 (Item# 1003634) **Product Code** Recommended use Energized electrical cleaner

**Recommended restrictions** None known.

Manufacturer/Importer/Supplier/Distributor information

Manufactured or sold by:

CRC Industries. Inc. Company name 885 Louis Dr. **Address** 

Warminster, PA 18974 US

Telephone

215-674-4300 **General Information Technical Assistance** 800-521-3168 **Customer Service** 800-272-4620 24-Hour Emergency 800-424-9300 (US)

(CHEMTREC) 703-527-3887 (International) Website www.crcindustries.com

# 2. Hazard(s) identification

Physical hazards Gases under pressure Compressed gas **Health hazards** Skin corrosion/irritation Category 2

Serious eye damage/eye irritation Category 2B Sensitization, skin Category 1B Carcinogenicity Category 1B

Specific target organ toxicity, single exposure Category 3 narcotic effects

Hazardous to the aquatic environment, acute **Environmental hazards** Category 2

hazard

Hazardous to the aquatic environment,

long-term hazard

Not classified.

Label elements

**OSHA** defined hazards



Signal word Danger

**Hazard statement** Contains gas under pressure; may explode if heated. Causes skin irritation. May cause an allergic

skin reaction. Causes eye irritation. May cause drowsiness or dizziness. May cause cancer. Toxic

Category 2

to aquatic life. Toxic to aquatic life with long lasting effects.

**Precautionary statement** Prevention

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not puncture or incinerate container. Do not expose to heat or store at temperatures above 49°C/120°F. Use with adequate ventilation. Open doors and windows or use other means to ensure a fresh air supply during use and while product is drying. If you experience any symptoms listed on this label, increase ventilation or leave the area. Avoid breathing mist or vapor. Wash thoroughly after handling. Contaminated work clothing must not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection. Avoid release to the environment.

Material name: Lectra-Motive® Electric Parts Cleaner

SDS US No. 05018 (Item# 1003634) Version #: 04 Revision date: 10-25-2017 Issue date: 12-20-2013

**Response** If on skin: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice/attention.

Take off contaminated clothing and wash before reuse. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you feel unwell. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. IF exposed or concerned:

Get medical advice/attention. Collect spillage.

Storage Store locked up. Protect from sunlight. Store in a well-ventilated place. Exposure to high

temperature may cause can to burst.

**Disposal** Dispose of contents/container in accordance with local/regional/national regulations.

Hazard(s) not otherwise classified (HNOC)

None known.

#### Supplemental information

When exposed to extreme heat or hot surfaces, vapors may decompose to harmful or fatal corrosive gases such as hydrogen chloride and possibly phosgene.

# 3. Composition/information on ingredients

#### **Mixtures**

Chemical name	Common name and synonyms	CAS number	%
tetrachloroethylene	perchloroethylene	127-18-4	90 - 100
carbon dioxide		124-38-9	1 - 5

Specific chemical identity and/or percentage of composition has been withheld as a trade secret.

#### 4. First-aid measures

Inhalation Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON

CENTER or doctor/physician if you feel unwell.

**Skin contact** Remove contaminated clothing immediately and wash skin with soap and water. In case of

eczema or other skin disorders: Seek medical attention and take along these instructions. If skin

irritation or rash occurs: Get medical advice/attention.

**Eye contact** Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if

present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

In the unlikely event of swallowing contact a physician or poison control center. Rinse mouth. Get

medical attention if symptoms occur.

Most important symptoms/effects, acute and

delayed

Ingestion

May cause drowsiness and dizziness. Headache. Nausea, vomiting. Irritation of eyes and mucous membranes. Exposed individuals may experience eye tearing, redness, and discomfort. Irritation of nose and throat. Skin irritation. May cause redness and pain. May cause an allergic skin reaction. Dermatitis. Rash.

Indication of immediate medical attention and special treatment needed

General information

Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

IF exposed or concerned: Get medical advice/attention. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.

# 5. Fire-fighting measures

Suitable extinguishing media Unsuitable extinguishing Water fog. Foam. Dry chemical powder. Dry chemical, CO2, or water spray.

media

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical

Contents under pressure. Pressurized container may rupture when exposed to heat or flame. During fire, gases hazardous to health may be formed. When exposed to extreme heat or hot surfaces, vapors may decompose to harmful or fatal corrosive gases such as hydrogen chloride and possibly phosgene.

Special protective equipment and precautions for firefighters

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

Fire-fighting equipment/instructions
General fire hazards

In case of fire: Stop leak if safe to do so. Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up.

Contents under pressure. Pressurized container may rupture when exposed to heat or flame.

#### 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Many gases are heavier than air and will spread along ground and collect in low or confined areas (sewers, basements, tanks). Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist or vapor. Emergency personnel need self-contained breathing equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Collect spillage. This material is classified as a water pollutant under the Clean Water Act and should be prevented from contaminating soil or from entering sewage and drainage systems which lead to waterways. Stop the flow of material, if this is without risk. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. Put material in suitable, covered, labeled containers. For waste disposal, see section 13 of the SDS.

**Environmental precautions** 

Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Do not contaminate water. Avoid discharge into drains, water courses or onto the ground.

# 7. Handling and storage

#### Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Pressurized container: Do not pierce or burn, even after use. Use with adequate ventilation. Open doors and windows or use other means to ensure a fresh air supply during use and while product is drying. If you experience any symptoms listed on this label, increase ventilation or leave the area. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. Use caution around energized equipment. The metal container will conduct electricity if it contacts a live source. This may result in injury to the user from electrical shock and/or flash fire. Avoid breathing mist or vapor. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Should be handled in closed systems, if possible. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Avoid release to the environment. Do not empty into drains. Observe good industrial hygiene practices. For product usage instructions, see the product label.

# Conditions for safe storage, including any incompatibilities

Level 1 Aerosol.

Contents under pressure. Do not handle or store near an open flame, heat or other sources of ignition. Do not puncture or incinerate container. Do not expose to heat or store at temperatures above 49 °C/120 °F. Protect from sunlight. Store in a well-ventilated place. Store in cool place. Exposure to high temperature may cause can to burst. Store away from incompatible materials (see Section 10 of the SDS).

Value

### 8. Exposure controls/personal protection

#### Occupational exposure limits

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

#### US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	туре	value	
carbon dioxide (CAS 124-38-9)	PEL	9000 mg/m3	
		5000 ppm	
US. OSHA Table Z-2 (29 CFR 1910.10	000)		
Components	Туре	Value	
tetrachloroethylene (CAS 127-18-4)	Ceiling	200 ppm	
•	TWA	100 ppm	
US. ACGIH Threshold Limit Values			
Components	Туре	Value	
carbon dioxide (CAS 124-38-9)	STEL	30000 ppm	
,	TWA	5000 ppm	

<b>US. ACGIH Threshold Limit Valu</b>	es		
Components	Туре	Value	
tetrachloroethylene (CAS 127-18-4)	STEL	100 ppm	
,	TWA	25 ppm	
US. NIOSH: Pocket Guide to Che	emical Hazards		
Components	Туре	Value	
carbon dioxide (CAS 124-38-9)	STEL	54000 mg/m3	
,		30000 ppm	
	TWA	9000 mg/m3	
		5000 ppm	

#### **Biological limit values**

ACGIH Biological Exposure Indices

Components	Value	Determinant	Specimen	Sampling Time
tetrachloroethylene (CAS 127-18-4)	0.5 mg/l	Tetrachloroethy lene	Blood	*
·	3 ppm	Tetrachloroethy lene	End-exhaled air	*

<sup>\* -</sup> For sampling details, please see the source document.

#### **Exposure guidelines**

#### US - Minnesota Haz Subs: Skin designation applies

tetrachloroethylene (CAS 127-18-4)

Skin designation applies.

Appropriate engineering

controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eve wash facilities and emergency shower should be available when handling this product. Provide eyewash station.

#### Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin protection

Wear protective gloves such as: Nitrile. Viton/butyl. Polyvinyl alcohol (PVA). Silver Shield® Hand protection

Other Wear appropriate chemical resistant clothing.

If engineering controls are not feasible or if exposure exceeds the applicable exposure limits, use a Respiratory protection

NIOSH-approved cartridge respirator with an organic vapor cartridge. Use a self-contained breathing apparatus in confined spaces and for emergencies. Air monitoring is needed to

determine actual employee exposure levels.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Observe any medical surveillance requirements. When using do not smoke, Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the workplace.

### 9. Physical and chemical properties

**Appearance** 

**Physical state** Liquid. **Form** Aerosol. Color Colorless. Odor Irritating. **Odor threshold** 50 ppm Not available.

Melting point/freezing point -8.1 °F (-22.3 °C) estimated Initial boiling point and boiling 250.3 °F (121.3 °C) estimated

range

Flash point

None (Tag Closed Cup)

**Evaporation rate** Very fast. Not available. Flammability (solid, gas) Upper/lower flammability or explosive limits

Flammability limit - lower

Not available.

(%)

Flammability limit - upper

(%)

Not available.

1230.2 hPa estimated Vapor pressure

Vapor density 5.76 (air = 1)

Relative density 1.62

0.02 % (77 °F (25 °C)) Solubility (water)

Partition coefficient (n-octanol/water)

Not available.

Not available. **Auto-ignition temperature Decomposition temperature** Not available. Not available. Viscosity (kinematic) 97.9 % estimated Percent volatile

Other information

**Partition coefficient** 

(oil/water)

2.88

# 10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

Material is stable under normal conditions. **Chemical stability** 

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoid Heat, flames and sparks. Contact with incompatible materials. When exposed to extreme heat or hot surfaces, vapors may decompose to harmful or fatal corrosive gases such as hydrogen

chloride and possibly phosgene.

Incompatible materials

Hazardous decomposition

products

Strong oxidizing agents. Strong acids. Strong bases.

Hydrogen chloride. Trace amounts of chlorine and phosgene. Carbon oxides. Halogenated

materials. Carbonyl halides.

### 11. Toxicological information

#### Information on likely routes of exposure

Prolonged inhalation may be harmful. May cause drowsiness and dizziness. Headache. Nausea, Inhalation

vomiting.

Skin contact Causes skin irritation. May cause an allergic skin reaction.

Eye contact Causes eye irritation.

Ingestion Ingestion of large amounts may produce gastrointestinal disturbances including irritation, nausea,

and diarrhea

Symptoms related to the physical, chemical and toxicological characteristics May cause drowsiness and dizziness. Headache. Nausea, vomiting. Irritation of eyes and mucous membranes. Exposed individuals may experience eye tearing, redness, and discomfort. Irritation of nose and throat. Skin irritation. May cause redness and pain. May cause an allergic skin

reaction. Dermatitis. Rash.

#### Information on toxicological effects

**Acute toxicity** None known.

Components **Species Test Results** 

tetrachloroethylene (CAS 127-18-4)

**Acute** Dermal

LD50 Rabbit > 3228 mg/kg

Material name: Lectra-Motive® Electric Parts Cleaner

SDS US No. 05018 (Item# 1003634) Version #: 04 Revision date: 10-25-2017 Issue date: 12-20-2013

**Species Test Results** Components

Oral

**LD50** Rat 2629 mg/kg

\* Estimates for product may be based on additional component data not shown.

Skin corrosion/irritation Causes skin irritation. Serious eye damage/eye Causes eve irritation.

irritation

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization May cause an allergic skin reaction.

No data available to indicate product or any components present at greater than 0.1% are Germ cell mutagenicity

mutagenic or genotoxic.

Carcinogenicity May cause cancer.

IARC Monographs. Overall Evaluation of Carcinogenicity

tetrachloroethylene (CAS 127-18-4) 2A Probably carcinogenic to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

US. National Toxicology Program (NTP) Report on Carcinogens

tetrachloroethylene (CAS 127-18-4) Reasonably Anticipated to be a Human Carcinogen.

This product is not expected to cause reproductive or developmental effects. Reproductive toxicity

Specific target organ toxicity -

single exposure

May cause drowsiness and dizziness.

Specific target organ toxicity -

repeated exposure

Not classified.

**Aspiration hazard** Not an aspiration hazard.

Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects. **Chronic effects** 

# 12. Ecological information

**Ecotoxicity** Toxic to aquatic life with long lasting effects. Accumulation in aquatic organisms is expected.

Components Species **Test Results** 

tetrachloroethylene (CAS 127-18-4)

Aquatic

Fish LC50 Rainbow trout, donaldson trout 4.73 - 5.27 mg/l, 96 hours

(Oncorhynchus mykiss)

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

tetrachloroethylene 2.88

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

### 13. Disposal considerations

Disposal of waste from residues / unused products This material and its container must be disposed of as hazardous waste. Consult authorities before disposal. Contents under pressure. Do not puncture, incinerate or crush. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical

or used container. Dispose in accordance with all applicable regulations.

D039: Waste Tetrachloroethylene Hazardous waste code

F001: Waste Halogenated Solvent - Spent Halogenated Solvent Used in Degreasing

F002: Waste Halogenated Solvent - Spent Halogenated Solvent

US RCRA Hazardous Waste U List: Reference

U210 tetrachloroethylene (CAS 127-18-4)

Material name: Lectra-Motive® Electric Parts Cleaner

<sup>\*</sup> Estimates for product may be based on additional component data not shown.

#### Contaminated packaging

Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

# 14. Transport information

DOT

UN number UN1950

**UN proper shipping name** Aerosols, poison, Limited Quantity

Transport hazard class(es)

Class 2.2
Subsidiary risk 6.1(PGIII)
Label(s) 2.2, 6.1
Packing group Not applicable.

Special precautions for user Forbidden from transportation by air.

Packaging exceptions 306
Packaging non bulk None
Packaging bulk None

IATA

UN number UN1950

**UN proper shipping name** Aerosols, non-flammable, containing substances in Division 6.1, Packing Group III

Transport hazard class(es)

Class 2.2 Subsidiary risk 6.1

Packing group Not applicable.

ERG Code 2P

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Other information

Passenger and cargo Allowed with restrictions.

aircraft

Cargo aircraft only Allowed with restrictions.

**IMDG** 

UN number UN1950 UN proper shipping name AEROSOLS

Transport hazard class(es)

Class 2 Subsidiary risk 6.1

Packing group Not applicable.

**Environmental hazards** 

Marine pollutant No.

EmS Not available.

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

#### 15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

US EPCRA (SARA Title III) Section 313 - Toxic Chemical: Listed substance

tetrachloroethylene (CAS 127-18-4)

**CERCLA Hazardous Substance List (40 CFR 302.4)** 

tetrachloroethylene (CAS 127-18-4) Listed.

**CERCLA Hazardous Substances: Reportable quantity** 

tetrachloroethylene (CAS 127-18-4) 100 LBS

Spills or releases resulting in the loss of any ingredient at or above its RQ require immediate notification to the National Response Center (800-424-8802) and to your Local Emergency Planning Committee.

Material name: Lectra-Motive® Electric Parts Cleaner

SDS US

#### Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

tetrachloroethylene (CAS 127-18-4)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

**Food and Drug** 

Not regulated.

Administration (FDA)

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Section 311/312 Immediate Hazard - Yes
Hazard categories Delayed Hazard - Yes
Fire Hazard - No
Pressure Hazard - Yes
Reactivity Hazard - No

SARA 302 Extremely No hazardous substance

#### **US** state regulations

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd.

(a))

tetrachloroethylene (CAS 127-18-4)

US. New Jersey Worker and Community Right-to-Know Act

carbon dioxide (CAS 124-38-9) tetrachloroethylene (CAS 127-18-4)

**US. Massachusetts RTK - Substance List** 

carbon dioxide (CAS 124-38-9) tetrachloroethylene (CAS 127-18-4)

US. Pennsylvania Worker and Community Right-to-Know Law

carbon dioxide (CAS 124-38-9) tetrachloroethylene (CAS 127-18-4)

**US. Rhode Island RTK** 

carbon dioxide (CAS 124-38-9) tetrachloroethylene (CAS 127-18-4)

**US. California Proposition 65** 

WARNING: This product contains a chemical known to the State of California to cause cancer.

US - California Proposition 65 - CRT: Listed date/Carcinogenic substance tetrachloroethylene (CAS 127-18-4)

Listed: April 1, 1988

Volatile organic compounds (VOC) regulations

**EPA** 

VOC content (40 CFR

51.100(s))

Consumer products (40 CFR 59, Subpt. C)

Not regulated

0 %

**State** 

Consumer products This product is regulated as an Energized Electrical Cleaner for the following states: California,

Connecticut, Delaware, District of Columbia, Illinois, Indiana, Maine, Maryland, Massachusetts, Michigan, New Jersey, New York, Ohio, Pennsylvania, Rhode Island and Virginia. It is for energized equipment use only. It is not to be used for motorized vehicle maintenance or their

parts. This product is compliant for use in all 50 states.

VOC content (CA) 0 % VOC content (OTC) 0 %

**International Inventories** 

Country(s) or regionInventory nameOn inventory (yes/no)\*AustraliaAustralian Inventory of Chemical Substances (AICS)YesCanadaDomestic Substances List (DSL)YesCanadaNon-Domestic Substances List (NDSL)NoChinaInventory of Existing Chemical Substances in China (IECSC)Yes

Material name: Lectra-Motive® Electric Parts Cleaner

SDS US

Country(s) or region Inventory name On inventory (yes/no)\*

Europe European Inventory of Existing Commercial Chemical

Substances (EINECS)

Europe European List of Notified Chemical Substances (ELINCS) No

JapanInventory of Existing and New Chemical Substances (ENCS)YesKoreaExisting Chemicals List (ECL)YesNew ZealandNew Zealand InventoryYes

Philippines Philippine Inventory of Chemicals and Chemical Substances Yes

(PICCS)

United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory

\*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

# 16. Other information, including date of preparation or last revision

Issue date12-20-2013Revision date10-25-2017Prepared byAllison Yoon

Version # 04

Further information CRC # 491G/1002481

HMIS® ratings Health: 2\*

Flammability: 0 Physical hazard: 0 Personal protection: B

NFPA ratings Health: 2

Flammability: 0 Instability: 0

NFPA ratings



**Disclaimer**The information contained in this document applies to this specific material as supplied. It may not

be valid for this material if it is used in combination with any other materials. This information is accurate to the best of CRC's knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label. For further clarification of any information contained on this (M)SDS consult your supervisor, a health & safety

professional, or CRC Industries, Inc..

**Revision Information** This document has undergone significant changes and should be reviewed in its entirety.

Material name: Lectra-Motive® Electric Parts Cleaner

SDS US

Yes