MATERIAL SAFETY DATA SHEET

Effective Date: March 1, 2007

SECTION I PRODUCT IDENTIFICATION & EMERGENCY INFORMATION

PRODUCT NAME(S) OR NUMBER(S) EMERGENCY PHONE NUMBERS

DAXCEL® FOAMASTIK® 161-D Adhesive Chemtrec® 800-424-9300 (Inside US)

703-527-3887 (Outside US)

Supplier 412-922-2536

MANUFACTURER/SUPPLIER/NAME/ADDRESS IMO & IATA HAZARD DESIGNATION

Dacar Products Company Inc.

1019 McCartney Street

PROPER NAME / CLASS / NUMBER / PKG GROUP / RQ
Adhesive, 3.3, UN 1133, III (containing less than 5% Naphtha, Petroleum)

CHEMICAL FAMILY FORMULA DOT DOMESTIC US GROUND TRANSPORT HAZARD DESIGNATION

Oil-based Adhesive See Section II Unregulated

HAZARD RATINGS

Health Department of the second of the secon

Reactivity 0 = Moderate N = None (see Section VIII)

Personal Protection N

SECTION II CHEMICAL COMPONENTS

CHEMICAL NAME	<u>TLV</u>	CAS NOS.	PCT.
Calcium Carbonate	N/A	471-34-1	60-70
Magnesium Carbonate	N/A	546-93-0	4-10
Linseed Oil	N/A	8001-26-1	4-10
Soybean Oil	N/A	68152-81-8	4-10
Petroleum Naphtha	500 ppm	8742-88-7 /	4-10
Mixture	σσο ρριτι	64742-47-8	1 10

(N/A = Not Available)

SECTION III PHYSICAL DATA

Boiling Point (°C / °F)	> 127 / 261	Solubility in Water	Negligible
Vapor Pressure (@ 20°C)	N/A	Specific Gravity	1.8
Vapor Density (air = 1)	N/A	Evaporation Rate	
Volatile Organic Content (g / I)	< 80	(Ethyl ether $= 1$)	N/A
ADDEADANCE	ODOR	MATERIAL IS A	

APPEARANCE ODOR MATERIAL IS A
Heavy Mastic, Light Gray Mild Odor Paste

SECTION IV FIRE AND EXPLOSION HAZARD DATA

FLASH POINT (Closed Cup) LEL UEL IGNITION TEMPERATURE EXTINGUISHING MEDIA

40°C / 104°F (Pensky Martin) 1.4* 8.1* 216°C / 421°F* Regular Foam or Carbon Dioxide

*Solvent Only

SPECIAL FIRE FIGHTING PROCEDURES UNUSUAL FIRE AND EXPLOSION HAZARDS

None

SECTION V PHYSIOLOGICAL EFFECTS

EFFECTS OF EXPOSURE

Eyes: May cause irritation

Skin: May cause irritation and contact dermatitis in sensitive persons

Inhalation: May cause lightheadedness

Swallowing: May cause irritation, nausea, vomiting or diarrhea

EMERGENCY AND FIRST AID PROCEDURES

Eyes: Flush with large amounts of water; get medical attention

Skin: Wash thoroughly with soap and water

Inhalation: Remove to fresh air

Swallowing: Drink two glasses of water and induce vomiting; get medical attention

SECTION VI REACTIVITY DATA

MATERIALS IS CONDITIONS TO AVOID MATERIALS TO AVOID DECOMPOSITION PRODUCTS

Stable Heat, flame and fire None Carbon dioxide/monoxide

HAZARDOUS POLYMERIZATION CONDITIONS TO AVOID

Will Not Occur Avoid open flame or sparks

SECTION VII SPILL OR LEAK PROCEDURES

SMALL SPILL

Absorb residue on floor absorbent or similar material; dispose of absorbent properly.

WASTE DISPOSAL METHOD

Dispose of in accordance with all Federal, State and Local laws and regulations.

LARGE SPILL

Material may be shoveled into proper containers. Residue may be absorbed by clay, sand, floor absorbent or similar materials and shoveled into containers.

SECTION VIII PROTECTIVE EQUIPMENT

ventilation: Generally none. For prolonged exposure in small, closed space, general ventilation.

Respiratory: None.

For Eyes: Generally none; product will not splash easily. If needed, use any type splash goggles.

For Skin: Generally none; for prolonged skin contact, wear natural rubber gloves.

SECTION IX SPECIAL PRECAUTIONS

Container may contain liquid or vapor residue. Do not cut container with torch. Obey all precautions until container disposed of. Do not reuse container. Dispose of container in accordance with Federal, State and Local regulations.

CHANGES since last version: None.