DOW CORNING™ 733 G&M Sealant-Clear



Version Revision Date: SDS Number: Date of last issue: 03/23/2017 5.0 10/17/2017 1291757-00010 Date of first issue: 02/12/2015

SECTION 1. IDENTIFICATION

Product name : DOW CORNING™ 733 G&M Sealant-Clear

Product code : 04069507

Manufacturer or supplier's details

Company Identification : THE DOW CHEMICAL COMPANY

2030 WILLARD H DOW CENTER

MIDLAND MI 48674-0000

UNITED STATES

Telephone : 800-258-2436

24-Hour Emergency Contact : Chemtrec +1 800-424-9300

Local Emergency Number : 800-424-9300

E-mail address : SDSQuestion@dow.com

Recommended use of the chemical and restrictions on use

Recommended use : Adhesive, binding agents

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with 29 CFR 1910.1200

Not a hazardous substance or mixture.

GHS label elements

Not a hazardous substance or mixture.

Precautionary Statements : Prevention:

P271 Use only outdoors or in a well-ventilated area.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Chemical nature : Silicone elastomer

Hazardous ingredients

Chemical name	CAS-No.	Concentration (% w/w)
Silicon dioxide	7631-86-9	>= 8 - <= 9
Titanium dioxide	13463-67-7	<=
		0.3197

DOW CORNING™ 733 G&M Sealant-Clear



Version Revision Date: SDS Number: Date of last issue: 03/23/2017 5.0 10/17/2017 1291757-00010 Date of first issue: 02/12/2015

SECTION 4. FIRST AID MEASURES

If inhaled : If inhaled, remove to fresh air.

Get medical attention if symptoms occur.

In case of skin contact : Wash with water and soap as a precaution.

Get medical attention if symptoms occur.

In case of eye contact : Flush eyes with water as a precaution.

Get medical attention if irritation develops and persists.

If swallowed, DO NOT induce vomiting.

Get medical attention if symptoms occur. Rinse mouth thoroughly with water.

Most important symptoms and effects, both acute and

delayed

None known.

Protection of first-aiders : No special precautions are necessary for first aid responders.

Notes to physician : Treat symptomatically and supportively.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media : Water spray

Alcohol-resistant foam Carbon dioxide (CO2)

Dry chemical

Unsuitable extinguishing

media

None known.

Carbon oxides

Silicon oxides Formaldehyde

Specific hazards during fire

fighting

Exposure to combustion products may be a hazard to health.

Hazardous combustion prod- :

ucts

Specific extinguishing meth-

ods

Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment. Use water spray to cool unopened containers.

Remove undamaged containers from fire area if it is safe to do

SO.

Evacuate area.

Special protective equipment:

for fire-fighters

Wear self-contained breathing apparatus for firefighting if

necessary.

Use personal protective equipment.

SECTION 6. ACCIDENTAL RELEASE MEASURES

DOW CORNING™ 733 G&M Sealant-Clear



Version Revision Date: SDS Number: Date of last issue: 03/23/2017 5.0 10/17/2017 1291757-00010 Date of first issue: 02/12/2015

Personal precautions, protective equipment and emergency procedures

Follow safe handling advice and personal protective

equipment recommendations.

Environmental precautions : Discharge into the environment must be avoided.

Prevent further leakage or spillage if safe to do so. Retain and dispose of contaminated wash water.

Local authorities should be advised if significant spillages

cannot be contained.

Methods and materials for containment and cleaning up

Soak up with inert absorbent material.

For large spills, provide diking or other appropriate

containment to keep material from spreading. If diked material can be pumped, store recovered material in appropriate

container.

Clean up remaining materials from spill with suitable

absorbent.

Local or national regulations may apply to releases and disposal of this material, as well as those materials and items

employed in the cleanup of releases. You will need to

determine which regulations are applicable.

Sections 13 and 15 of this SDS provide information regarding

certain local or national requirements.

SECTION 7. HANDLING AND STORAGE

Technical measures : See Engineering measures under EXPOSURE

CONTROLS/PERSONAL PROTECTION section.

Local/Total ventilation : Use only with adequate ventilation.

Advice on safe handling : Handle in accordance with good industrial hygiene and safety

practice.

Take care to prevent spills, waste and minimize release to the

environment.

Conditions for safe storage : Keep in properly labeled containers.

Store in accordance with the particular national regulations.

Materials to avoid : Do not store with the following product types:

Strong oxidizing agents

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Ingredients	CAS-No.	Value type	Control parame-	Basis
		(Form of	ters / Permissible	
		exposure)	concentration	
Silicon dioxide	7631-86-9	TWA (Dust)	20 Million OSHA Z-3 particles per cubic foot (Silica)	

DOW CORNING™ 733 G&M Sealant-Clear



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 03/23/2017

 5.0
 10/17/2017
 1291757-00010
 Date of first issue: 02/12/2015

		TWA (Dust)	80 mg/m3 / %SiO2 (Silica)	OSHA Z-3
		TWA	6 mg/m³ (Silica)	NIOSH REL
Titanium dioxide	13463-67-7	TWA (total dust)	15 mg/m³	OSHA Z-1
		TWA	10 mg/m³ (Titanium dioxide)	ACGIH

These substance(s) are inextricably bound in the product and therefore do not contribute to a dust inhalation hazard.

Silicon dioxide

Titanium dioxide

Engineering measures : Processing may form hazardous compounds (see section

10).

Ensure adequate ventilation, especially in confined areas.

Minimize workplace exposure concentrations.

Personal protective equipment

Respiratory protection : No personal respiratory protective equipment normally

required.

Hand protection

Remarks : Wash hands before breaks and at the end of workday.

Eye protection : Wear the following personal protective equipment:

Safety glasses

Skin and body protection : Skin should be washed after contact.

Hygiene measures : Ensure that eye flushing systems and safety showers are

located close to the working place. When using do not eat, drink or smoke. Wash contaminated clothing before re-use.

These precautions are for room temperature handling. Use at

elevated temperature or aerosol/spray applications may

require added precautions.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : paste

Color : colorless

Odor : Acetic acid

Odor Threshold : No data available

DOW CORNING™ 733 G&M Sealant-Clear



Version Revision Date: SDS Number: Date of last issue: 03/23/2017 5.0 10/17/2017 1291757-00010 Date of first issue: 02/12/2015

pH : Not applicable

Melting point/freezing point : No data available

Initial boiling point and boiling

range

Not applicable

Flash point : Not applicable

Evaporation rate : Not applicable

Flammability (solid, gas) : Not classified as a flammability hazard

Self-ignition : The substance or mixture is not classified as pyrophoric. The

substance or mixture is not classified as self heating.

Upper explosion limit / Upper

flammability limit

No data available

Lower explosion limit / Lower

flammability limit

No data available

Vapor pressure : Not applicable

Relative vapor density : No data available

Relative density : 1.04

Solubility(ies)

Water solubility : No data available

Partition coefficient: n-

octanol/water

No data available

Autoignition temperature : No data available

Decomposition temperature : No data available

Viscosity

Viscosity, dynamic : Not applicable

Explosive properties : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Molecular weight : No data available

Particle size : No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity : Not classified as a reactivity hazard.

Chemical stability : Stable under normal conditions.

DOW CORNING™ 733 G&M Sealant-Clear



Version Revision Date: SDS Number: Date of last issue: 03/23/2017 5.0 10/17/2017 1291757-00010 Date of first issue: 02/12/2015

Possibility of hazardous reac-

tions

Use at elevated temperatures may form highly hazardous

compounds.

Can react with strong oxidizing agents.

Acetic acid is formed upon contact with water or humid air. When heated to temperatures above 150 °C (300 °F) in the presence of air, trace quantities of formaldehyde may be

released.

Adequate ventilation is required.

See OSHA formaldehyde standard, 29 CFR 1910.1048 Hazardous decomposition products will be formed at elevated

temperatures.

Conditions to avoid : None known.

Incompatible materials : Oxidizing agents

Hazardous decomposition products

Thermal decomposition : Formaldehyde

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Skin contact Ingestion Eye contact

Acute toxicity

Not classified based on available information.

Ingredients:

Silicon dioxide:

Acute oral toxicity : LD50 (Rat): > 3,300 mg/kg

Assessment: The substance or mixture has no acute oral tox-

icity

Remarks: Information taken from reference works and the

literature.

Acute inhalation toxicity : LC50 (Rat): > 2.08 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Assessment: The substance or mixture has no acute inhala-

tion toxicity

Remarks: Information taken from reference works and the

literature.

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg

Assessment: The substance or mixture has no acute dermal

toxicity

Remarks: Information taken from reference works and the

literature.

DOW CORNING™ 733 G&M Sealant-Clear



Version Revision Date: SDS Number: Date of last issue: 03/23/2017 5.0 10/17/2017 1291757-00010 Date of first issue: 02/12/2015

Titanium dioxide:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 6.82 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Assessment: The substance or mixture has no acute inhala-

tion toxicity

Skin corrosion/irritation

Not classified based on available information.

Ingredients:

Silicon dioxide:

Result: No skin irritation

Remarks: Information taken from reference works and the literature.

Titanium dioxide:

Species: Rabbit

Result: No skin irritation

Serious eye damage/eye irritation

Not classified based on available information.

Ingredients:

Silicon dioxide:

Result: No eye irritation

Remarks: Information taken from reference works and the literature.

Titanium dioxide:

Species: Rabbit

Result: No eye irritation

Respiratory or skin sensitization

Skin sensitization

Not classified based on available information.

Respiratory sensitization

Not classified based on available information.

Ingredients:

Silicon dioxide:

Assessment: Does not cause skin sensitization.

Test Type: Skin: test type not specified

Species: Guinea pig Result: negative

Remarks: Information taken from reference works and the literature.

DOW CORNING™ 733 G&M Sealant-Clear



Version Revision Date: SDS Number: Date of last issue: 03/23/2017 5.0 10/17/2017 1291757-00010 Date of first issue: 02/12/2015

Titanium dioxide:

Test Type: Local lymph node assay (LLNA)

Routes of exposure: Skin contact

Species: Mouse Result: negative

Germ cell mutagenicity

Not classified based on available information.

Ingredients:

Silicon dioxide:

Genotoxicity in vitro : Result: negative

Remarks: Information taken from reference works and the

literature.

Genotoxicity in vivo : Application Route: Ingestion

Result: negative

Remarks: Information taken from reference works and the

literature.

Germ cell mutagenicity -

Assessment

: Animal testing did not show any mutagenic effects.

Titanium dioxide:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Result: negative

Genotoxicity in vivo : Test Type: In vivo micronucleus test

Species: Mouse Result: negative

Carcinogenicity

Not classified based on available information.

Ingredients:

Titanium dioxide:

Species: Rat

Application Route: inhalation (dust/mist/fume)

Exposure time: 24 Months

Method: OECD Test Guideline 453

Result: positive

ment

Remarks: The mechanism or mode of action may not be relevant in humans.

These substance(s) are inextricably bound in the product and therefore do not contribute to a

dust inhalation hazard.

Carcinogenicity - Assess-

: Limited evidence of carcinogenicity in inhalation studies with

animals.

IARC Group 2B: Possibly carcinogenic to humans

Titanium dioxide 13463-67-7

DOW CORNING™ 733 G&M Sealant-Clear



Version **Revision Date:** SDS Number: Date of last issue: 03/23/2017 1291757-00010 Date of first issue: 02/12/2015 5.0 10/17/2017

OSHA No component of this product present at levels greater than or

egual to 0.1% is on OSHA's list of regulated carcinogens.

NTP No ingredient of this product present at levels greater than or

equal to 0.1% is identified as a known or anticipated carcinogen

by NTP.

Reproductive toxicity

Not classified based on available information.

STOT-single exposure

Not classified based on available information.

STOT-repeated exposure

Not classified based on available information.

Repeated dose toxicity

Ingredients:

Titanium dioxide:

Species: Rat

NOAEL: 24,000 mg/kg Application Route: Ingestion Exposure time: 28 Days

Species: Rat NOAEL: 10 mg/m³

Application Route: inhalation (dust/mist/fume)

Exposure time: 2 y

Remarks: These substance(s) are inextricably bound in the product and therefore do not

contribute to a dust inhalation hazard.

Aspiration toxicity

Not classified based on available information.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Ingredients:

Titanium dioxide:

Toxicity to fish LC50 (Oncorhynchus mykiss (rainbow trout)): > 100 mg/l

Exposure time: 96 h

Method: OECD Test Guideline 203

aquatic invertebrates

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): > 100 mg/l

Exposure time: 48 h

Toxicity to algae : EC50 (Skeletonema costatum (marine diatom)): > 10,000 mg/l

Exposure time: 72 h

DOW CORNING™ 733 G&M Sealant-Clear



Version Revision Date: SDS Number: Date of last issue: 03/23/2017 5.0 10/17/2017 1291757-00010 Date of first issue: 02/12/2015

Toxicity to microorganisms : EC50: > 1,000 mg/l Exposure time: 3 h

Method: OECD Test Guideline 209

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Resource Conservation and

Recovery Act (RCRA)

This product has been evaluated for RCRA characteristics and does not meet the criteria of hazardous waste if discarded

in its purchased form.

Waste from residues : Dispose of in accordance with local regulations.

Contaminated packaging : Empty containers should be taken to an approved waste

handling site for recycling or disposal.

If not otherwise specified: Dispose of as unused product.

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

Not regulated as a dangerous good

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

49 CFR

Not regulated as a dangerous good

SECTION 15. REGULATORY INFORMATION

EPCRA - Emergency Planning and Community Right-to-Know

CERCLA Reportable Quantity

DOW CORNING™ 733 G&M Sealant-Clear



Version Revision Date: SDS Number: Date of last issue: 03/23/2017 5.0 10/17/2017 1291757-00010 Date of first issue: 02/12/2015

Ingredients	CAS-No.	Component RQ	Calculated product RQ
		(lbs)	(lbs)
Acetic acid	64-19-7	5000	*
Acetic anhydride	108-24-7	5000	*
Methanol	67-56-1	5000	*

^{*:} Calculated RQ exceeds reasonably attainable upper limit.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards : No SARA Hazards

SARA 313 : This material does not contain any chemical components with

known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

US State Regulations

Pennsylvania Right To Know

Dimethyl siloxane, hydroxy-terminated 70131-67-8
Silicon dioxide 7631-86-9
Aluminium 7429-90-5
Acetic acid 64-19-7
Acetic anhydride 108-24-7

California Prop. 65

WARNING: This product can expose you to chemicals including Methanol, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

California Permissible Exposure Limits for Chemical Contaminants

Silicon dioxide 7631-86-9

The ingredients of this product are reported in the following inventories:

TSCA : All chemical substances in this product are either listed on the

TSCA Inventory or are in compliance with a TSCA Inventory

exemption.

AICS : All ingredients listed or exempt.

IECSC : All ingredients listed or exempt.

DSL : All chemical substances in this product comply with the CEPA

1999 and NSNR and are on or exempt from listing on the

Canadian Domestic Substances List (DSL).

REACH : For purchases from Dow Chemical EU legal entities, all

ingredients are currently pre/registered or exempt under REACH. Please refer to section 1 for recommended uses. For purchases from non-EU Dow Chemical legal entities with the

intention to export into EEA please contact your DC

representative/local office.

DOW CORNING™ 733 G&M Sealant-Clear




Version Revision Date: SDS Number: Date of last issue: 03/23/2017 5.0 10/17/2017 1291757-00010 Date of first issue: 02/12/2015

П

SECTION 16. OTHER INFORMATION

Further information

NFPA:



Special hazard.

HMIS® IV:



HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)
NIOSH REL : USA. NIOSH Recommended Exposure Limits

OSHA Z-1 : USA. Occupational Exposure Limits (OSHA) - Table Z-1 Lim-

its for Air Contaminants

OSHA Z-3 : USA. Occupational Exposure Limits (OSHA) - Table Z-3 Min-

eral Dusts

ACGIH / TWA : 8-hour, time-weighted average

NIOSH REL / TWA : Time-weighted average concentration for up to a 10-hour

workday during a 40-hour workweek

OSHA Z-1 / TWA : 8-hour time weighted average OSHA Z-3 / TWA : 8-hour time weighted average

AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Conven-

DOW CORNING™ 733 G&M Sealant-Clear



Version Revision Date: SDS Number: Date of last issue: 03/23/2017 5.0 10/17/2017 1291757-00010 Date of first issue: 02/12/2015

tion for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Sources of key data used to compile the Material Safety

Data Sheet

Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agen-

cy, http://echa.europa.eu/

Revision Date : 10/17/2017

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

US / Z8