Safety Data Sheet OSHA Hazard Communication Standard 29 CFR 1910.1200. Prepared to GHS Rev 3.



Revision date: Initial version Date of issue: 04.24.2015

Page: 1/10

Trade name: Aqua Gel® IIP Pourable Wire Pulling Lubricant

SECTION 1: Identification

Product identifier: Aqua Gel® IIP Pourable Wire Pulling Lubricant.

Synonyms: None available.

Product Code Number: 31-421, 31-425, 31-435.

SDS number: ID002

Recommended use: Wire Pulling Lubricant.

Recommended restrictions: None known.

Manufacturer/Importer/Supplier/Distributor information:

Company Name: IDEAL INDUSTRIES, INC.

Company Address: Becker Place,

Sycamore, IL 60178

Company Telephone: Office hours (Mon – Fri)

7AM - 5 PM (CDT)

(815)895-5181

Company Contact Name: Darryl Docter.

Company Contact Email: IDEAL@IDEALINDUSTRIES.COM **Emergency phone number:** 24 HOUR EMERGENCY NUMBER:

(815)895-5181.

SECTION 2: Hazard(s) identification

Classification of the chemical in accordance with paragraph (d) of §1910.1200:

Physical hazards

Not classified as a physical hazard under GHS criteria

Health hazards

Skin corrosion/irritation, Category 2.

Serious eye damage/eye irritation, Category 2.

Environmental hazards

Not classified as a physical hazard under GHS criteria.

GHS Signal word: WARNING.

GHS Hazard statement(s): Causes skin irritation.

Causes serious eye irritation.

Revision Date: 6/1/2015 Page 1 of 10

GHS Hazard symbol(s):



GHS Precautionary statement(s):

Prevention: P264 - Wash skin thoroughly after handling.

P280 - Wear protective gloves/eye protection/face

protection.

Response: P302+P352 – If on skin: Wash with plenty of soap

and water.

P305 + P351 + P338 - If in eyes: Rinse cautiously

with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P332+P313 - If skin irritation occurs: Get medical

advice/attention.

P337+P313 - If eye irritation persists: Get medical

advice/ attention.

P362 - Take off contaminated clothing and wash before

reuse.

Storage: No storage precautionary statements.

Disposal: No disposal precautionary statements.

Hazard(s) not otherwise

Classified (HNOC): None known.

Percentage of ingredient(s) of unknown acute toxicity:

Not applicable.

SECTION 3: Composition/information on ingredients

Mixture:

Chemical name	CAS#	Concentration (weight %)
Potassium Hydroxide (20% solution)	1310-58-3	< 2%

Note: The balance of the ingredients are not classified as hazardous or below the threshold concentration, under the criteria of the Federal OSHA Hazard Communication Standard 29CFR 1910.1200.

Aqua Gel[®] IIP Pourable Wire Pulling Lubricant SDS#: ID002

SECTION 4: First-aid Measures

Description of necessary measures:

Inhalation: Obtain medical attention if there are signs of breathing difficulties.

Skin contact: Wash with plenty of soap and water. Remove contaminated clothing and thoroughly clean before reuse.

Eye contact: Flush eyes with water for at least 15 minutes, occasionally lifting eyelids. If pain or redness persists after flushing, obtain medical attention.

Ingestion: Do not induce vomiting. Consult physician or local poison control center.

Most important symptoms/effects, acute and delayed: Causes skin irritation. Causes serious eye irritation.

Indication of immediate medical attention and special treatment needed: If any symptoms are observed, contact a physician and give them this SDS sheet. If exposed or concerned: Get medical advice/attention.

SECTION 5: Fire-fighting measures

Suitable extinguishing media: Not flammable. Use extinguishing media suitable for surrounding materials.

Unsuitable extinguishing media: No data available.

Specific hazards arising from the chemical: Extreme temperatures of combustion or burning and contact with nitrites could result in the formation of nitrosamines which are potential carcinogens.

Combustion products - Carbon monoxide, Carbon dioxide. Nitrogen based products.

Special protective equipment and precautions for fire-fighters: For fire involving this material, do not enter any enclosed or confined fire space without proper protective equipment. This may include self-contained breathing apparatus to protect against the hazardous effects of combustion products and oxygen deficiencies.

SECTION 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures: Stay upwind and away from spill/release. For large spillages, notify persons downwind of the spill/release, isolate immediate hazard area and keep unauthorized personnel out. Wear appropriate protective equipment, including respiratory protection, as conditions warrant (see Section 8). See Sections 2 and 7 for additional information on hazards and precautionary measures.

Revision Date: June 1, 2015 Page 3 of 10

Aqua Gel[®] IIP Pourable Wire Pulling Lubricant SDS#: ID002

Methods and material for containment and cleaning up:

Persons not wearing protective equipment should be excluded from area of spill until cleanup has been completed. Stop spill at source, wipe up, shovel or vacuum spilled material. Clean up spills immediately as they can be dangerously slippery. Prevent run-off to sewers, streams or other bodies of water. If run-off occurs, notify proper authorities as required.

SECTION 7: Handling and Storage

Precautions for safe handling: Wash thoroughly after handling. Wear protective gloves/clothing and eye/face protection. Use good personal hygiene practices and wear appropriate personal protective equipment (see section 8).

Conditions for safe storage, including any incompatibles: Store at temperatures between 40 - 180°F. Avoid freezing. Keep away from children, infants and pets. Keep container(s) tightly closed and properly labeled. Store only in approved containers. Keep away from any incompatible material (see Section 10). Protect container(s) against physical damage.

"Empty" containers retain residue and may be dangerous. "Empty" drums should be completely drained, properly bunged, and promptly shipped to the supplier or a drum reconditioner. All containers should be disposed of in an environmentally safe manner and in accordance with governmental regulations.

SECTION 8: Exposure controls/personal protection

Control Parameters:

Occupational exposure limits:

US OSHA HAZARDOUS COMPONENTS (29 CFR 1910.1200):		
Permissible Exposure Limits		
Substance	PEL-TWA (8 hour)	PEL-STEL (15 min)
	(o nour)	(15 11111)
Potassium Hydroxide	No data available	No data available

US ACGIH Threshold Limit Values		
Substance	TLV-TWA (8 hour)	TLV-STEL (15 min)
Potassium Hydroxide	2 mg/m ³ Ceiling	No data available

NIOSH Exposure Limits		
Substance	TWA	STEL
Potassium Hydroxide	2 mg/m ³ Ceiling	No data available

Appropriate engineering controls: General (mechanical) room ventilation is expected to be adequate. Special local ventilation is suggested at points where vapors can be expected to escape to the workplace air or in enclosed areas.

Revision Date: June 1, 2015 Page 4 of 10

Agua Gel[®] IIP Pourable Wire Pulling Lubricant SDS#: ID002

Individual protection measures, such as personal protective equipment:

Eye/face protection: None normally required, but the use of OSHA compliant safely glasses or splash goggles recommended.

Skin and Hand protection: None normally needed -Neoprene if necessary. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

Respiratory protection: None normally required.

Other: Eye wash / eye bath in the work area is recommended but not necessary.

Thermal hazards: No data available.

SECTION 9: Physical and chemical properties

Appearance

Physical state: Liquid

Form: Clear pourable gel.

Color: Blue. Odor: Mild odor.

Odor threshold: No data available $6.4 - 8.0 @ 150^{\circ}F$ pH:

 $6.5 - 8.0 @ 77^{\circ}F$

Melting point/freezing point: No data available **Initial boiling point and** 100°C (212°F)

boiling range:

Flash point: None

Evaporation rate: No data available Flammability (solid, gas): Not applicable

Upper/lower flammability or explosive limits

Flammability limit – lower %): No data available Flammability limit – upper (%): No data available Explosive limit – lower (%): No data available **Explosive limit – upper (%):** No data available Vapor pressure: No data available Vapor density: No data available **Relative Density:** 0.9930-1.0330 **Solubility(ies):** Infinite.

Partition coefficient (n-octanol/water): No data available **Auto-ignition temperature:** No data available No data available **Decomposition temperature:**

Viscosity: 4000 - 6000 cps @ 5 rpm 150°F

7500 – 14000 cps @ 5 rpm 212°F

Other information:

Revision Date: June 1, 2015 Page 5 of 10 Aqua Gel[®] IIP Pourable Wire Pulling Lubricant

SDS#: ID002

% Volatile by volume: ~ 90% Percent solids by weight: ~ 10%

SECTION 10: Stability and Reactivity

Reactivity: Not chemically reactive.

Chemical stability: Stable under normal ambient and anticipated

conditions of use.

Possibility of hazardous reactions: Hazardous reactions not anticipated.

Conditions to avoid: Avoid prolonged storage at temperatures exceeding

190°F.

Extreme temperatures of combustion or burning and contact with nitrites could result in the formation of nitrosamines which are potential carcinogens. This

condition is unlikely to occur.

Incompatible materials: Avoid contact with strong oxidizers and nitrites. **Hazardous decomposition Products:** In the unlikely event of combustion of dried residue,

oxides and nitrogen may be released.

SECTION 11: Toxicological information

Information on likely routes of exposure:

Inhalation:Not an expected route of entry.Ingestion:Not an expected route of entry.Skin:May produce skin irritation.Eyes:Not an expected route of entry.

Symptoms related to the physical, chemical, and toxicological characteristics:

Upon prolonged contact, may cause temporary eye discomfort.

Delayed and immediate effects and chronic effects from short or long-term exposure:

Detailed below.

Numerical measures of toxicity:

Ingredient Information:

Substance	Test Type (species)	Value
Potassium hydroxide	LD ₅₀ Oral (Rat)	273 mg/kg
	LD ₅₀ Dermal (Rabbit)	No data available
	LC ₅₀ Inhalation (Rat)	No data available

Product Acute Toxicity Estimates:

Acute Oral Toxicity – no data available Acute Dermal Toxicity - no data available Acute Inhalation Toxicity - no data available Aqua $\operatorname{Gel}^{\circledR}$ IIP Pourable Wire Pulling Lubricant

SDS#: ID002

Skin corrosion/irritation: This material may cause skin irritation.

Serious eye damage/eye irritation: Upon prolonged contact, may cause temporary eye

discomfort.

Respiratory sensitization: No information available on the mixture, however

none of the components have been classified as a respiratory sensitizer (or are below the concentration

threshold for classification).

Skin sensitization: No information available on the mixture, however

none of the components have been classified as a skin sensitizer (or are below the concentration threshold

for classification).

Germ cell mutagenicity: No information available on the mixture, however

none of the components have been classified for

germ cell mutagenicity (or are below the concentration threshold for classification).

Carcinogenicity: No information available on the mixture, however

none of the components are listed in the National Toxicology Program (NTP) Report on Carcinogens (latest edition) or has been found to be a potential carcinogen in the International Agency for Research on Cancer (IARC) Monographs (latest edition), or by

OSHA.

Reproductive toxicity: No information available on the mixture, however

none of the components have been classified for reproductive toxicity (or are below the concentration

threshold for classification).

Specific target organ toxicity-

Single exposure: No information available on the mixture, however

none of the components have been classified for STOT SE (or are below the concentration threshold

for classification).

Specific target organ toxicity-

Repeat exposure: No information available on the mixture, however

none of the components have been classified for STOT RE (or are below the concentration threshold

for classification).

Aspiration hazard: No information available on the mixture, however

none of the components have been classified for

Aqua Gel[®] IIP Pourable Wire Pulling Lubricant

SDS#: ID002

aspiration hazard (or are below the concentration

threshold for classification).

Further information: No data available.

SECTION 12: Ecological information

Ecotoxicity:

Product data: No data available

Ingredient Information:

Substance	Test	Species	Value
	Type		
	LC ₅₀	Fish - Gambusia affinis (Mosquito fish)	85 mg/l (24h)
Potassium hydroxide	LC ₅₀	Aquatic crustacea	No data available
	EC ₅₀	Algae	No data available

Persistence and Degradability: No data available **Bioaccumulative Potential:** No data available.

Mobility in Soil: No data available.

Other adverse effects: No data available.

SECTION 13: Disposal considerations

Disposal instructions:

The generator of a waste is always responsible for making proper hazardous waste determinations and needs to consider state and local requirements in addition to federal regulations.

See Sections 7 and 8 for information on handling, storage and personal protection and Section 9 for physical/chemical properties. It is possible that the material as produced contains constituents which are not required to be listed in the SDS but could affect the hazardous waste determination. Additionally, use which results in chemical or physical change of this material could subject it to regulation as a hazardous waste.

SECTION 14: Transport Information

DOT: This material is not classified as dangerous under DOT regulations.

IATA: This material is not classified as dangerous under IATA regulations.

IMDG: This material is not classified as dangerous under IMDG regulations.

Revision Date: June 1, 2015 Page 8 of 10

SECTION 15: Regulatory Information

Safety, health and environmental regulations specific for the product.

USA:

United States Federal Regulations: This SDS complies with the OSHA, 29 CFR 1910.1200. The product is hazardous under OSHA.

Toxic Substances Control Act (TSCA) – All substances in this product are listed, as required, on the TSCA inventory.

SARA Superfund and Reauthorization Act of 1986 Title III sections 302, 311,312 and 313:

Section 302 – No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

CERCLA Hazardous Substance List, 40 CFR 302.4:

Component	Reportable Quantity
Potassium Hydroxide	1000 lbs

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130): None listed.

Clean Water Act Section 311 Hazardous Substances (40 CFR 117.3): None listed.

SARA Title III

Section 302 Extremely Hazardous Substance (40 CFR 355, Appendix A): None listed.

Section 311/312 (40 CFR 370):

Acute Health Hazard: Yes Chronic Health Hazard: No.

Fire Hazard: No Pressure Hazard: No Reactivity Hazard: No

Section 313 Toxic Release Inventory (40 CFR 372):

None

STATE REGULATIONS:

This SDS contains specific health and safety data is applicable for state requirements. For details on your regulatory requirements you should contact the appropriate agency in your state.

Aqua Gel[®] IIP Pourable Wire Pulling Lubricant SDS#: ID002

California Proposition 65 (California Safe Drinking Water and Toxic Enforcement Act of 1986: No components are listed on Prop 65.

Massachusetts Right to Know: Potassium hydroxide is listed on the Massachusetts Right to Know List.

Minnesota Hazardous Substance List: None of the components are listed on the Minnesota Hazardous Substance List.

New Jersey Right to Know: Potassium hydroxide is listed on the New Jersey Right to Know list.

Pennsylvania Right to Know: Potassium hydroxide is listed on the Pennsylvania Right to Know List.

Canada WHMIS Hazard Class: D2B - Toxic Material

SECTION 16: Other information, including date of preparation or last revision.

Revision Date: April 24, 2015

To the best of our knowledge, the information contained herein is accurate. However IDEAL INDUSTRIES INC. does not assume any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist.

Revision Date: June 1, 2015 Page 10 of 10