

## Klean Strip Aircraft Decal &amp; Adhesive Remover

Printed: 04/17/2015

Revision: 04/17/2015

Supersedes Revision: 03/20/2015

## 1. PRODUCT AND COMPANY IDENTIFICATION

<b>Product Name:</b>	Klean Strip Aircraft Decal & Adhesive Remover	
<b>Company Name:</b>	W. M. Barr 2105 Channel Avenue Memphis, TN 38113	<b>Phone Number:</b> (901)775-0100
<b>Web site address:</b>	www.wmbarr.com	
<b>Emergency Contact:</b>	3E 24 Hour Emergency Contact	(800)451-8346
<b>Information:</b>	W.M. Barr Customer Service	(800)398-3892
<b>Intended Use:</b>	Lifts decals and adhesive residue from automotive finishes, glass, chrome or metal bumpers.	
<b>Synonyms:</b>	EAD908	
<b>Additional Information</b>	This product is regulated by the United States Consumer Product Safety Commission and is subject to certain labeling requirements under the Federal Hazardous Substances Act. These requirements differ from the classification criteria and hazard information required for safety data sheets (SDS). The product label also includes other important information, including directions for use, and should always be read in its entirety prior to using the product.	

## 2. HAZARDS IDENTIFICATION

**Flammable Aerosols, Category 1**  
**Gas Under Pressure, Liquefied gas**  
**Acute Toxicity: Oral, Category 4**  
**Acute Toxicity: Skin, Category 4**  
**Acute Toxicity: Inhalation, Category 4**  
**Serious Eye Damage/Eye Irritation, Category 2A**  
**Germ Cell Mutagenicity, Category 1B**  
**Carcinogenicity, Category 2**  
**Specific Target Organ Toxicity (single exposure), Category 1**  
**Aspiration Toxicity, Category 1**  
**Simple Asphyxiant**



**GHS Signal Word:** Danger

**GHS Hazard Phrases:**

- H223: Flammable aerosol.
- H280: Containers gas under pressure; may explode if heated.
- H302: Harmful if swallowed.
- H304: May be fatal if swallowed and enters airways.
- H312: Harmful in contact with skin.
- H319: Causes serious eye irritation.
- H332: Harmful if inhaled.
- H340: May cause genetic defects.
- H351: Suspected of causing cancer.
- H370: Causes damage to organs.

**GHS Precaution Phrases:**

- P201: Obtain special instructions before use.
- P202: Do not handle until all safety precautions have been read and understood.
- P210: Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
- P211: Do not spray on an open flame or any other ignition source.
- P251: Pressurized container: Do not pierce or burn, even after use.
- P260: Do not breathe gas/mist/vapors/spray.

## Klean Strip Aircraft Decal &amp; Adhesive Remover

Printed: 04/17/2015

Revision: 04/17/2015

Supersedes Revision: 03/20/2015

**GHS Response Phrases:**


P264: Wash hands thoroughly after handling.  
 P270: Do not eat, drink or smoke when using this product.  
 P271: Use only outdoors or in a well-ventilated area.  
 P280: Wear protective gloves/protective clothing/eye protection/face protection.  
 P281: Use personal protective equipment as required.  
 P301+310: IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.  
 P312: Call a POISON CENTER or doctor/physician if you feel unwell.  
 P302+352: IF ON SKIN: Wash with plenty of soap and water.  
 P304+340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.  
 P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
 P307+311: IF exposed: Call a POISON CENTER or doctor/physician.  
 P308+313: IF exposed or concerned: Get medical attention/advice.  
 P330: Rinse mouth.  
 P331: Do NOT induce vomiting.  
 P337+313: If eye irritation persists, get medical advice/attention.  
 P363: Wash contaminated clothing before reuse.

**GHS Storage and Disposal Phrases:**

P405: Store locked up.  
 P410+403: Protect from sunlight and store in well-ventilated place.  
 P412: Do not expose to temperatures exceeding 50 °C/122 °F.  
 P501: Dispose of contents/container according to local, state and federal regulations.

**Hazard Rating System:**

<b>HEALTH</b>	*	2
<b>FLAMMABILITY</b>		4
<b>PHYSICAL</b>		1
<b>PPE</b>		X

**HMIS:****OSHA Regulatory Status:**

This material is classified as hazardous under OSHA regulations.

**Potential Health Effects (Acute and Chronic):**

This product has not been tested as a whole to determine health effects. The health effects listed below are associated with the individual ingredients listed in Section 3.

**EYES:** Causes eye irritation. May cause pain, a burning sensation, watering, redness, change in vision, and eye damage.

**SKIN:** Causes skin irritation. May cause redness, itching, and drying and cracking of the skin. Prolonged or repeated skin contact may cause drying and cracking of the skin and possible skin burns. May be absorbed through the skin with possible systemic effects.

**INHALATION:** May cause irritation to the nose, throat, and respiratory tract. Concentrations above the TLV may cause headache, dizziness, nausea, shortness of breath, and vomiting. Higher concentrations may cause central nervous system depression and unconsciousness, nasal discharge, hoarseness, coughing, chest pain, and breathing difficulty.

Reports have associated repeated and prolonged overexposure to solvents with neurological and other physiological damage. Intentional misuse by deliberately concentrating and inhaling solvents may be harmful or fatal.

Methanol has caused birth defects in laboratory animals, but only when inhaled at extremely high vapor concentrations. The relevance of this finding to humans is uncertain.

## Klean Strip Aircraft Decal &amp; Adhesive Remover

Printed: 04/17/2015

Revision: 04/17/2015

Supersedes Revision: 03/20/2015

INGESTION: May cause nausea, vomiting, loss of appetite, gastrointestinal irritation, diarrhea, central nervous system depression, and headache. Aspiration into lungs can cause severe lung damage, which can be fatal. May cause leg pain, pain in the abdomen and lower back, visual impairment, including blindness, coma, and death.

TARGET ORGANS: eyes, central nervous system, skin, respiratory tract, gastrointestinal system

PRIMARY ROUTES OF ENTRY: skin, eyes, inhalation, ingestion

**Medical Conditions Generally** Diseases of the skin, eyes, and respiratory system.

**Aggravated By Exposure:**

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

CAS #	Hazardous Components (Chemical Name)	Concentration	RTECS #
78-93-3	Methyl ethyl ketone {MEK; 2-Butanone}	55.0 -65.0 %	EL6475000
67-56-1	Methanol {Methyl alcohol; Carbinol; Wood alcohol}	15.0 -20.0 %	PC1400000
68476-86-8	Liquified petroleum gas, sweetened {propane, isobutane, n-butane}	<20.0 %	NA
95-63-6	1,2,4-Trimethylbenzene {Pseudocumene}	2.0 -7.0 %	DC3325000
620-14-4	Benzene, 1-Ethyl-3-methyl- {3-Ethyltoluene}	2.0 -4.0 %	NA
108-67-8	Mesitylene {1,3,5-Trimethylbenzene}	1.0 -2.0 %	OX6825000
611-14-3	Benzene, 1-Ethyl-2-methyl- {2-Ethyltoluene}	0.6 -1.8 %	XT2500000
622-96-8	Benzene, 1-Ethyl-4-methyl- {4-Ethyltoluene}	0.6 -1.8 %	XT2550000
526-73-8	1,2,3-Trimethylbenzene	0.6 -1.4 %	DC3300000
103-65-1	Benzene, Propyl- {N-Propylbenzene}	0.6 -1.4 %	DA8750000
95-47-6	o-Xylene {Benzene, o-Dimethyl-}	0.4 -1.2 %	ZE2450000
98-82-8	Cumene {Benzene, 1-Methylethyl-; Isopropylbenzene}	0.04 -0.2 %	GR8575000

**Additional Chemical Information** Specific percentage of composition is being withheld as a trade secret.

### 4. FIRST AID MEASURES

**Emergency and First Aid Procedures:**

**Skin:**

Immediately begin washing the skin thoroughly with large amounts of water and mild soap, if available, while removing contaminated clothing. Seek medical attention if irritation develops or persists.

**Eyes:**

Immediately begin to flush eyes with water, remove any contact lens. Continue to flush the eyes for at least 15 minutes. Seek medical attention.

**Inhalation:**

Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get immediate medical attention.

**Ingestion:**

If swallowed, do NOT induce vomiting. Seek immediate medical attention. Call a

**Klean Strip Aircraft Decal & Adhesive Remover**

Printed: 04/17/2015

Revision: 04/17/2015

Supersedes Revision: 03/20/2015

<b>Signs and Symptoms Of Exposure:</b>	physician, hospital emergency room, or poison control center immediately. Never give anything by mouth to an unconscious person.
<b>Note to Physician:</b>	See Potential Health Effects.  This product contains methanol which can cause intoxication and central nervous system depression. Methanol is metabolized to formic acid and formaldehyde. These metabolites can cause metabolic acidosis, visual disturbances and blindness. Since metabolism is required for these toxic symptoms, their onset may be delayed from 6 to 30 hours following ingestion. Ethanol competes for the same metabolic pathway and has been used to prevent methanol metabolism. Ethanol administration is indicated in symptomatic patients or at blood methanol concentrations above 20 ug/dl. Methanol is effectively removed by hemodialysis.

**5. FIRE FIGHTING MEASURES**

<b>Flash Pt:</b>	Level 3 Aerosol No data.
<b>Explosive Limits:</b>	LEL: No data. UEL: No data.
<b>Autoignition Pt:</b>	No data.
<b>Suitable Extinguishing Media:</b>	Use carbon dioxide, dry powder, or foam.
<b>Unsuitable Extinguishing Media:</b>	None known.
<b>Fire Fighting Instructions:</b>	Self-contained respiratory protection should be provided for fire fighters fighting fires in buildings or confined areas. Storage containers exposed to fire should be kept cool with water spray to prevent pressure build-up. Stay away from containers that have been exposed to intense heat or flame.
<b>Flammable Properties and Hazards:</b>	Danger! Flammable! Keep away from heat, sparks, flame, and all other sources of ignition. Do not smoke. Extinguish all flames and pilot lights, and turn off stoves, heaters, electric motors and all other sources of ignition during use and until all vapors are gone. Beware of static electricity that may be generated by synthetic clothing and other sources. Contents under pressure. Do not puncture, incinerate or store above 120 degrees F. Exposure to heat or prolonged exposure to sun may cause bursting.  FLASHPOINT OF LIQUID CONCENTRATE: 20 degrees Fahrenheit  FLASHPOINT OF PROPELLANT: -142 degrees Fahrenheit

**6. ACCIDENTAL RELEASE MEASURES**

<b>Steps To Be Taken In Case Material Is Released Or Spilled:</b>	Vapors may cause flash fire or ignite explosively.  Clean up: Keep unnecessary people away; isolate hazard area and deny entry. Stay upwind, out of low areas, and ventilate closed spaces before entering. Shut off ignition sources; keep flares, smoking or flames out of hazard area. Use non-sparking tools. Use proper bonding and grounding methods for all equipment and processes. Keep out of waterways and bodies of water. Be cautious of vapors collecting in small enclosed spaces, sewers, low lying areas, confined spaces, etc.  Small spills: Take up with sand, earth or other noncombustible absorbent material and place in a plastic container where applicable.  Large spills: Dike far ahead of spill for later disposal.
---	---

## Klean Strip Aircraft Decal &amp; Adhesive Remover

Printed: 04/17/2015

Revision: 04/17/2015

Supersedes Revision: 03/20/2015

Waste Disposal: Dispose in accordance with applicable local, state and federal regulations.

## 7. HANDLING AND STORAGE

### Precautions To Be Taken in Handling:

Read carefully all cautions and directions on product label before use. Since empty container retains residue, follow all label warnings even after container is empty. Dispose of empty container according to all regulations. Do not reuse this container.

Do not use this product near any source of heat or open flame, furnace areas, pilot lights, stoves, etc.

Do not use in small enclosed spaces, such as basements and bathrooms. Vapors can accumulate and explode if ignited.

A source of clean water should be available in the work area for flushing eyes and skin.

### Precautions To Be Taken in Storing:

#### STORAGE

Store as a Level 3 Aerosol (NFPA 30B)

Replace overcap on container after each use. Store in a cool, dry place. Do not store near flames or at elevated temperatures. Do not expose to temperatures above 120 degrees Fahrenheit. Exposure to heat or prolonged exposure to sun can cause bursting.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

CAS #	Partial Chemical Name	OSHA TWA	ACGIH TWA	Other Limits
78-93-3	Methyl ethyl ketone {MEK; 2-Butanone}	PEL: 200 ppm	TLV: 200 ppm STEL: 300 ppm	No data.
67-56-1	Methanol {Methyl alcohol; Carbinol; Wood alcohol}	PEL: 200 ppm	TLV: 200 ppm STEL: 250 ppm	No data.
68476-86-8	Liquified petroleum gas, sweetened {propane, isobutane, n-butane}	No data.	No data.	No data.
95-63-6	1,2,4-Trimethylbenzene {Pseudocumene}	No data.	No data.	No data.
620-14-4	Benzene, 1-Ethyl-3-methyl- {3-Ethyltoluene}	No data.	No data.	No data.
108-67-8	Mesitylene {1,3,5-Trimethylbenzene}	No data.	No data.	No data.
611-14-3	Benzene, 1-Ethyl-2-methyl- {2-Ethyltoluene}	No data.	No data.	No data.
622-96-8	Benzene, 1-Ethyl-4-methyl- {4-Ethyltoluene}	No data.	No data.	No data.
526-73-8	1,2,3-Trimethylbenzene	No data.	No data.	No data.
103-65-1	Benzene, Propyl- {N-Propylbenzene}	No data.	No data.	No data.
95-47-6	o-Xylene {Benzene, o-Dimethyl-}	PEL: 100 ppm	TLV: 100 ppm STEL: 150 ppm	No data.
98-82-8	Cumene {Benzene, 1-Methylethyl-; Isopropylbenzene}	PEL: 50 ppm	TLV: 50 ppm	No data.

## Klean Strip Aircraft Decal &amp; Adhesive Remover

Printed: 04/17/2015

Revision: 04/17/2015

Supersedes Revision: 03/20/2015

<b>Respiratory Equipment (Specify Type):</b>	For use in areas with inadequate ventilation or fresh air, wear a properly maintained and properly fitted NIOSH approved respirator for organic solvent vapors.  For OSHA controlled work places and other regular users - Use only with adequate ventilation under engineered air control systems designed to prevent exceeding the appropriate TLV.  A dust mask does not provide protection against vapors.
<b>Eye Protection:</b>	Chemical splash goggles, or face shields are recommended to safeguard against potential eye contact, irritation, or injury. Chemical goggles or face shields are recommended when splashing or spraying of chemical is possible. A faceshield provides more protection to help reduce chemical contact to the face and eyes.
<b>Protective Gloves:</b>	Wear gloves with as much resistance to the chemical ingredients as possible. Glove materials such as nitrile and natural rubber provide protection. Glove selection should be based on chemicals being used and conditions of use. Consult your glove supplier for additional information. Gloves contaminated with product should be discarded and not reused.
<b>Other Protective Clothing:</b>	Various application methods can dictate the use of additional protective safety equipment, such as impermeable aprons to minimize exposure.
<b>Engineering Controls (Ventilation etc.):</b>	Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits.  Use only with adequate ventilation to prevent buildup of vapors. Do not use in areas where vapors can accumulate and concentrate, such as basements, bathrooms or small enclosed areas. Whenever possible, use outdoors in an open air area. If using indoors open all windows and doors and maintain a cross ventilation of moving fresh air across the work area. If strong odor is noticed or you experience slight dizziness, headache, nausea or eye-watering -- STOP -- ventilation is inadequate. Leave area immediately and move to fresh air.
<b>Work/Hygienic/Maintenance Practices:</b>	Wash hands thoroughly after use and before eating, drinking, or smoking.  Do not eat, drink, or smoke in the work area.  Discard any clothing or other protective equipment that cannot be decontaminated.  Facilities storing or handling this material should be equipped with an emergency eyewash and safety shower.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

<b>Physical States:</b>	[ X ] Gas    [ X ] Liquid    [ ] Solid	
<b>Appearance and Odor:</b>	No data available.	
<b>Melting Point:</b>	No data.	
<b>Boiling Point:</b>	148.00 F - 482.00 F	
<b>Autoignition Pt:</b>	No data.	
<b>Flash Pt:</b>	No data.	
<b>Explosive Limits:</b>	LEL: No data.	UEL: No data.
<b>Specific Gravity (Water = 1):</b>	0.82	
<b>Density:</b>	6.79 LB/GL at 75.0 F	

## Klean Strip Aircraft Decal &amp; Adhesive Remover

Printed: 04/17/2015

Revision: 04/17/2015

Supersedes Revision: 03/20/2015

<b>Vapor Pressure (vs. Air or mm Hg):</b>	No data.
<b>Vapor Density (vs. Air = 1):</b>	> 1
<b>Evaporation Rate:</b>	< 1
<b>Solubility in Water:</b>	No data.
<b>Percent Volatile:</b>	>= 98.0 % by weight.
<b>VOC / Volume:</b>	98.9000 % WT

## 10. STABILITY AND REACTIVITY

<b>Stability:</b>	Unstable [ ]    Stable [ X ]
<b>Conditions To Avoid - Instability:</b>	No data available.
<b>Incompatibility - Materials To Avoid:</b>	Oxidizing materials, caustics, amines, ammonia, strong bases, chloroform, chlorosulfonic acid, oleum, hydrogen peroxide, nitric acid, sulfuric acid, strong inorganic acids, and reactive metals.
<b>Hazardous Decomposition Or Byproducts:</b>	Thermal Decomposition may produce carbon monoxide, carbon dioxide, and unidentified organic compounds in black smoke.
<b>Possibility of Hazardous Reactions:</b>	Will occur [ ]    Will not occur [ X ]
<b>Conditions To Avoid - Hazardous Reactions:</b>	No data available.

## 11. TOXICOLOGICAL INFORMATION

<b>Toxicological Information:</b>	This product has not been tested as a whole. Refer to section 2 for acute and chronic effects.
<b>Carcinogenicity/Other Information:</b>	CAS# 78-93-3: Standard Draize Test, Eyes, Human, 350.0 PPM. Result: Behavioral: Anticonvulsant. - Journal of Industrial Hygiene and Toxicology, Vol/p/yr: 25,282, 1943 IARC 2B - Possibly Carcinogenic to Humans

CAS #	Hazardous Components (Chemical Name)	NTP	IARC	ACGIH	OSHA
78-93-3	Methyl ethyl ketone {MEK; 2-Butanone}	n.a.	n.a.	n.a.	n.a.
67-56-1	Methanol {Methyl alcohol; Carbinol; Wood alcohol}	n.a.	n.a.	n.a.	n.a.
68476-86-8	Liquified petroleum gas, sweetened {propane, isobutane, n-butane}	n.a.	n.a.	n.a.	n.a.
95-63-6	1,2,4-Trimethylbenzene {Pseudocumene}	n.a.	n.a.	n.a.	n.a.
620-14-4	Benzene, 1-Ethyl-3-methyl- {3-Ethyltoluene}	n.a.	n.a.	n.a.	n.a.
108-67-8	Mesitylene {1,3,5-Trimethylbenzene}	n.a.	n.a.	n.a.	n.a.
611-14-3	Benzene, 1-Ethyl-2-methyl- {2-Ethyltoluene}	n.a.	n.a.	n.a.	n.a.
622-96-8	Benzene, 1-Ethyl-4-methyl- {4-Ethyltoluene}	n.a.	n.a.	n.a.	n.a.
526-73-8	1,2,3-Trimethylbenzene	n.a.	n.a.	n.a.	n.a.
103-65-1	Benzene, Propyl- {N-Propylbenzene}	n.a.	n.a.	n.a.	n.a.
95-47-6	o-Xylene {Benzene, o-Dimethyl-}	n.a.	n.a.	A4	n.a.
98-82-8	Cumene {Benzene, 1-Methylethyl-; Isopropylbenzene}	n.a.	2B	n.a.	n.a.



## 12. ECOLOGICAL INFORMATION

**General Ecological Information:** This product has not been tested as a whole.

## 13. DISPOSAL CONSIDERATIONS

**Waste Disposal Method:** Dispose in accordance with applicable local, state and federal regulations.

## 14. TRANSPORT INFORMATION

**LAND TRANSPORT (US DOT):**

**DOT Proper Shipping Name:** Aerosols, flammable  
**DOT Hazard Class:** 2.1 FLAMMABLE GAS  
**UN/NA Number:** UN1950



**Additional Transport Information:** The shipper/supplier may apply one of the following exceptions: Combustible Liquid, Consumer Commodity, Limited Quantity, Viscous Liquid, Does Not Sustain Combustion, or others, as allowed under 49CFR Hazmat Regulations. Please consult 49CFR Subchapter C to ensure that subsequent shipments comply with these exceptions.

## 15. REGULATORY INFORMATION

**EPA SARA (Superfund Amendments and Reauthorization Act of 1986) Lists**

CAS #	Hazardous Components (Chemical Name)	S. 302 (EHS)	S. 304 RQ	S. 313 (TRI)
78-93-3	Methyl ethyl ketone {MEK; 2-Butanone}	No	Yes 5000 LB	No
67-56-1	Methanol {Methyl alcohol; Carbinol; Wood alcohol}	No	Yes 5000 LB	Yes
68476-86-8	Liquified petroleum gas, sweetened {propane, isobutane, n-butane}	No	No	No
95-63-6	1,2,4-Trimethylbenzene {Pseudocumene}	No	No	Yes
620-14-4	Benzene, 1-Ethyl-3-methyl- {3-Ethyltoluene}	No	No	No
108-67-8	Mesitylene {1,3,5-Trimethylbenzene}	No	No	No
611-14-3	Benzene, 1-Ethyl-2-methyl- {2-Ethyltoluene}	No	No	No
622-96-8	Benzene, 1-Ethyl-4-methyl- {4-Ethyltoluene}	No	No	No
526-73-8	1,2,3-Trimethylbenzene	No	No	No
103-65-1	Benzene, Propyl- {N-Propylbenzene}	No	No	No
95-47-6	o-Xylene {Benzene, o-Dimethyl-}	No	Yes 1000 LB	Yes
98-82-8	Cumene {Benzene, 1-Methylethyl-; Isopropylbenzene}	No	Yes 5000 LB	Yes

**This material meets the EPA 'Hazard Categories' defined for SARA Title III Sections 311/312 as indicated:**

<input checked="" type="checkbox"/> Yes	<input type="checkbox"/> No	Acute (immediate) Health Hazard
<input checked="" type="checkbox"/> Yes	<input type="checkbox"/> No	Chronic (delayed) Health Hazard
<input checked="" type="checkbox"/> Yes	<input type="checkbox"/> No	Fire Hazard
<input checked="" type="checkbox"/> Yes	<input type="checkbox"/> No	Sudden Release of Pressure Hazard
<input type="checkbox"/> Yes	<input checked="" type="checkbox"/> No	Reactive Hazard



# SAFETY DATA SHEET

## Klean Strip Aircraft Decal & Adhesive Remover

Page: 9  
Printed: 04/17/2015  
Revision: 04/17/2015  
Supersedes Revision: 03/20/2015

CAS #	Hazardous Components (Chemical Name)	Other US EPA or State Lists
78-93-3	Methyl ethyl ketone {MEK; 2-Butanone}	CAA HAP,ODC: No; CWA NPDES: No; TSCA: Yes - Inventory; CA PROP.65: No
67-56-1	Methanol {Methyl alcohol; Carbinol; Wood alcohol}	CAA HAP,ODC: HAP; CWA NPDES: No; TSCA: Yes - Inventory; CA PROP.65: Yes
68476-86-8	Liquified petroleum gas, sweetened {propane, isobutane, n-butane}	CAA HAP,ODC: No; CWA NPDES: No; TSCA: Yes - Inventory; CA PROP.65: No
95-63-6	1,2,4-Trimethylbenzene {Pseudocumene}	CAA HAP,ODC: No; CWA NPDES: No; TSCA: Yes - Inventory; CA PROP.65: No
620-14-4	Benzene, 1-Ethyl-3-methyl- {3-Ethyltoluene}	CAA HAP,ODC: No; CWA NPDES: No; TSCA: No; CA PROP.65: No
108-67-8	Mesitylene {1,3,5-Trimethylbenzene}	CAA HAP,ODC: No; CWA NPDES: No; TSCA: Yes - Inventory, 4 Test; CA PROP.65: No
611-14-3	Benzene, 1-Ethyl-2-methyl- {2-Ethyltoluene}	CAA HAP,ODC: No; CWA NPDES: No; TSCA: Yes - Inventory; CA PROP.65: No
622-96-8	Benzene, 1-Ethyl-4-methyl- {4-Ethyltoluene}	CAA HAP,ODC: No; CWA NPDES: No; TSCA: Yes - Inventory; CA PROP.65: No
526-73-8	1,2,3-Trimethylbenzene	CAA HAP,ODC: No; CWA NPDES: No; TSCA: Yes - Inventory, 8D TERM; CA PROP.65: No
103-65-1	Benzene, Propyl- {N-Propylbenzene}	CAA HAP,ODC: No; CWA NPDES: No; TSCA: Yes - Inventory, 12(b); CA PROP.65: No
95-47-6	o-Xylene {Benzene, o-Dimethyl-}	CAA HAP,ODC: HAP; CWA NPDES: No; TSCA: Yes - Inventory; CA PROP.65: No
98-82-8	Cumene {Benzene, 1-Methylethyl-; Isopropylbenzene}	CAA HAP,ODC: HAP; CWA NPDES: No; TSCA: Yes - Inventory, 4 Test; CA PROP.65: Yes

### 16. OTHER INFORMATION

**Revision Date:** 04/17/2015  
**Preparer Name:** W.M. Barr EHS Dept (901)775-0100

**Additional Information About This Product:** No data available.

**This Product:**

**Company Policy or Disclaimer:** The information contained herein is presented in good faith and believed to be accurate as of the effective date shown above. This information is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determination of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. Any use of this data and information must be determined by the user to be in accordance with applicable federal, state and local laws and regulations.