Safety Data Sheet

Revised On 03/15/2017

Page 1/4

Trade name: SAFETY BLUE Product code: 0000160129 Product category PC38 Paints and coatings. Manufacturer/Supplier: Seymour of Sycamore 917 Crosby Avenue Sycamore, IL 60178 phone: S15-895-9101 www.seymourpaint.com Basification of the substance or mixture Flam. Aerosol 1 H:22 Extremely flammable aerosol. Press. Gas Press. Gas H280 Contains gas under pressure; may explode if heated. Eye Irrit. 2A H319 Causes serious eye irritation. STOT RE 2 H373 May cause dowsiness or dizziness. STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure GHS02 GHS04 GHS07 GHS08 Danger Extremely flammable aerosol. Contains gas under pressure; may explode if heated. Causes serious eye irritation. May cause damage to organs through prolonged or repeated exposure GHS02 GHS04 GHS07 GHS08 Danger Extremely flammable aerosol. Contains gas under pressure; may explode if heated. Causes serious eye irritation. May cause damage to organs through prolonged or repeated exposus damage to organs through prolonged or repeated exposus eye or the set sparks/port surfacton. Precautionary statements Danger <th>epeated exposure. s. No smoking. e. cion/face protection. omfortable for breathing.</th>	epeated exposure. s. No smoking. e. cion/face protection. omfortable for breathing.
Emergency telephone number: CHEMTEL 1-800-255-3924, or 813-248-0585. 2 Hazard(s) identification Classification of the substance or mixture Flam. Aerosol 1 H222 Extremely flammable aerosol. Press. Gas Press. Gas H280 Contains gas under pressure; may explode if heated. Eye Irrit. 2A H319 Causes serious eye irritation. STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure GHS02 GHS04 GHS07 GHS08 Signal word Hazard statements Precautionary statements Precautionary statements Precautionary statements Quest Protective gloves/protective clothing/eye protect Do not preate dust/me/gas/mist/vapors/spray. IF INHALED: Remove person to fresh air and keep core of burn, even after use. Wash hands thoroughy with water for several n and easy to do. Continue rinsing. Call a POISON CENTER/doctor if you feel unwell. If eye irritation persists: Get medical advice/attention. Store in a well-ventilated place. Keep container in accordance v regulations. Store in a well-ventilated place. Keep container in accordance v regulations. Signal word Hazard statements Precautionary statements Call a POISON CENTERIZ/doctor in a well-ventilated area.	epeated exposure. s. No smoking. e. cion/face protection. omfortable for breathing.
Classification of the substance or mixture Flam. Aerosol 1 H222 Extremely flammable aerosol. Press. Gas H280 Contains gas under pressure; may explode if heated. Eye Irrit. 2A H319 Causes serious eye irritation. STOT SE 3 H336 May cause drowsiness or dizziness. STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure GHS Hazard pictograms Image: the substance or organs through prolonged or repeated exposure Signal word Danger Hazard statements Extremely flammable aerosol. Contains gas under pressure; may explode if heated. Causes serious eye irritation. May cause drowsiness or dizziness. May cause damage to organs through prolonged or repeated exposure Precautionary statements May cause damage to organs through prolonged or repeated exposure Precautionary statements Wash hands thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protective gloves/protective clothing/eye protective ob continue rinsign. Call a POISON CENTER/doctor if you feel unwell. If eye irritation persists: Get medical advice/attention. Store in a well-ventilated place. Keep container tight? Dispose of contents/container in accordance veregulations. Store in a well-ve	epeated exposure. s. No smoking. e. cion/face protection. omfortable for breathing.
Flam. Aerosol 1 H222 Extremely flammable aerosol. Press. Gas H280 Contains gas under pressure; may explode if heated. Eye Irrit. 2A H319 Causes serious eye irritation. STOT SE 3 H336 May cause damage to organs through prolonged or repeated exposur GHS Hazard pictograms Image: Contains gas under pressure; may explode if heated. Signal word Image: Contains gas under pressure; may explode if heated. Hazard statements Danger Precautionary statements Danger Precautionary statements Danger or the edit of the end of	epeated exposure. s. No smoking. e. cion/face protection. omfortable for breathing.
Signal word Hazard statements Danger Extremely flammable aerosol. Contains gas under pressure; may explode if heated. Causes serious eye irritation. May cause drowsiness or dizziness. May cause damage to organs through prolonged or r Keep away from head/sparks/open flames/hot surface Do not spray on an open flame or other ignition source Do not pierce or burn, even after use. Wash hands thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protect Do not breathe dust/fume/gas/mist/vapors/spray. IF INHALED: Remove person to fresh air and keep c If in eyes: Rinse cautiously with water for several n and easy to do. Continue rinsing. Call a POISON CENTER/doctor if you feel unwell. If eye irritation persists: Get medical advice/attention. Store locked up. Protect from sunlight. Do not expose to temperatures Protect from sunlight. Store in a well-ventilated place Store in a well-ventilated place. Keep container tight Dispose of contents/container in accordance v regulations. 3 Composition/information on ingredients Chemical Characterization: Mixtures Chemical Description: This product is a mixture of the substances listed bely Dangerous components: This product is a mixture of the substances listed bely	s. No smoking. e. rion/face protection. omfortable for breathing.
Precautionary statements Keep away from heat/sparks/open flames/hot surface Do not spray on an open flame or other ignition source Do not pierce or burn, even after use. Wash hands thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protect Do not breathe dust/fume/gas/mist/vapors/spray. IF INHALED: Remove person to fresh air and keep c If in eyes: Rinse cautiously with water for several n and easy to do. Continue rinsing. Call a POISON CENTER/doctor if you feel unwell. If eye irritation persists: Get medical advice/attention. Store locked up. Protect from sunlight. Do not expose to temperatures Protect from sunlight. Store in a well-ventilated place Store in a well-ventilated place. Keep container tighth Dispose of contents/container in accordance w regulations. This product is a mixture of the substances listed bell Dangerous components: This product is a mixture of the substances listed bell	s. No smoking. e. rion/face protection. omfortable for breathing.
Chemical characterization: Mixtures Chemical Description: This product is a mixture of the substances listed below Dangerous components: This product is a mixture of the substances listed below	closed.
Chemical characterization: Mixtures Chemical Description: This product is a mixture of the substances listed below Dangerous components: This product is a mixture of the substances listed below	
Dangerous components:	w with nonhazardous additions.
67-64-1 Acetone	
	39.3
74-98-6 propane 110-19-0 Isobutyl Acetate	15.75
106-97-8 n-butane	9.25
108-10-1 methyl isobutyl ketone	2.20
107-87-9 Methyl Propyl Ketone	1.92
2807-30-9 Glycol Ether EP	1.61
13463-67-7 titanium dioxide	1.29
4 First-aid measures	
After inhalation:Supply fresh air; consult doctor in case of complaintsAfter skin contact:Remove contaminated clothing. Wash exposed areaAfter eye contact:Rinse opened eye for several minutes under runn doctor.	with soap and water. ng water. If symptoms persist, consu
After swallowing: Rinse out mouth and then drink plenty of water. Rinse mouth with water. Do not induce vomiting.	
Most important symptoms and effects: Dizziness	
Indication of any immediate medical attention needed: No further relevant information available.	
E Fire fighting measures	
5 Fire-fighting measures Extinguishing agents: CO2, extinguishing powder or water spray. Fight larg	
Special hazards: CO2, extinguishing powder or water spray. Fight large	r fires with water spray

Safety Data Sheet

Page 2/4

Printing date 03/17/2017		Revised On 03/15/2017
Trade name: SAFETY BLUE		
Protective equipment for firefighters:	A respiratory protective device may be necessary.	(Contd. of page 1)
6 Accidental release measures		
Personal precautions, protective equipment and emergency procedures:	Wear protective equipment. Keep unprotected persons away. Use respiratory protective device against the effects of fumes/dust/aerosol.	
Methods and material for containment and cleaning up:	Ensure adequate ventilation.	
7 Handling and storage Precautions for safe handling Storage requirements:	Use only in well ventilated areas. Keep away from sources of heat and direct sunlight. Do not wareh conditions. Store locked up.	ouse in subfreezing
8 Exposure controls/personal prot		
Components with limit values that r 67-64-1 Acetone	equire monitoring at the workplace:	
PEL (USA) Long-term value: 2400 mg REL (USA) Long-term value: 590 mg/ TLV (USA) Short-term value: 1187 mg	m ³ , 250 ppm a/m ³ . 500 ppm	
Long-term value: 594 mg/ BEI 74-98-6 propane	τι», 2ου μρm	
PEL (USA) Long-term value: 1800 mg	//m³, 1000 ppm	
REL (USA) Long-term value: 1800 mg/m³, 1000 ppm TLV (USA) refer to Appendix F inTLVs&BEIs book; NIC-EX		
PEL (USA) Long-term value: 700 mg/	I 10-19-0 Isobutyl Acetate PEL (USA) Long-term value: 700 mg/m ³ , 150 ppm	
REL (USA) Long-term value: 700 mg/	m³, 150 ppm	
TLV (USA) Short-term value: 172 mg/m³, 150 ppm Long-term value: 238 mg/m³, 50 ppm 106-97-8 n-butane		
REL (USA) Long-term value: 1900 mg TLV (USA) Short-term value: (2370) r NIC-EX		
108-10-1 methyl isobutyl ketone		
PEL (USA) Long-term value: 410 mg/ REL (USA) Short-term value: 300 mg/ Long-term value: 205 mg/	m ³ , 75 ppm	
TLV (USA) Short-term value: 307 mg/ Long-term value: 82 mg/m BEI	m³, 75 ppm ³, 20 ppm	
107-87-9 Methyl Propyl Ketone		
PEL (USA) Long-term value: 700 mg/ REL (USA) Long-term value: 530 mg/		
TLV (USA) Short-term value: 529 mg/		
Ingredients with biological limit values:		
67-64-1 Acetone		
BEI (USA) 50 mg/L Medium: urine Time: end of shift Parameter: Acetone (nons	pecific)	
108-10-1 methyl isobutyl ketone		
BEI (USA) 1 mg/L Medium: urine Time: end of shift Parameter: MIBK		
Hygienic protection:	Keep away from foodstuffs and animal feed. Wash hands after use. Immediately remove all soiled and contaminated clothing.	
Breathing equipment:	Wash hands after use. Avoid contact with the eyes and skin. Do not eat or drink while working. A respirator is generally not necessary when using this product outdoors of In cases where short and/or long term overexposure exists, a charcoal filte worn. If you suspect overexposure conditions exist, please consult and bygeine	er respirator should be
Hand protection:	hygeine. Nitrile gloves. Protective gloves. The glove material must be impermeable and resistant t	to the substance.
Eye protection:	Tightly sealed goggles	

Printing date 03/17/2017

Trade name: SAFETY BLUE

Appearance: Odor: Odor threshold:

9 Physical and chemical properties

pH-value: Melting point/Melting range Boiling point:

Aerosol. Aromatic Not determined.		
Not determined. Undetermined. -110 °C (-166 °F)		
-19 °C (-2 °F) Extremely flammable.		

• •	
Flash point: Flammability (solid, gas):	-19 °C (-2 °F) Extremely flammable.
Decomposition temperature:	Not determined.
Auto igniting:	Product is not self-igniting.
Danger of explosion: Lower Explosion Limit: Upper Explosion Limit:	In use, may form flammable/explosive vapour-air mixture. 1.7 Vol % 10.9 Vol %
Vapor pressure: Relative Density: Vapor density Evaporation rate Partition coefficient: n-octonal/water:	Not determined. Between 0.77 and 0.85 (Water equals 1.00) Not determined. Not applicable. Not determined.
Solubility: Viscosity: VOC content (less exempt solvents):	Not determined. Not determined. 45.0 %
Solids content:	15.5 %

10 Stability and reactivity	
Reactivity: Conditions to avoid:	Stable at normal temperatures. Do not allow can to exceed 120 degrees Fahrenheit. Do not warehouse in subfreezing temperatures.
Chemical stability: Possibility of hazardous reactions: Incompatible materials: Hazardous decomposition:	Not fully evaluated. No dangerous reactions known. No further relevant information available. No dangerous decomposition products known.

11 Toxicological information

TT TOXICOlOgical	mormation	
LD/LC50 value	s that are relevant for	classification:
110-19-0 Isobu		
Oral LD50	4763 mg/kg (rbt)	
106-97-8 n-butane		
Inhalative LC50)/4 h 658 mg/l (rat)	
108-10-1 methyl isobutyl ketone		
Oral LD50) 2100 mg/kg (rat)	
Dermal LD50) 16000 mg/kg (rat	
Inhalative LC50/4 h 8.3-16.6 mg/l (ra)
13463-67-7 titanium dioxide		
Oral LD50) >20000 mg/kg (ra	at)
Dermal LD50) >10000 mg/kg (rt	ot)
Inhalative LC50)/4 h >6.82 mg/l (rat)	
Information on Skin effects: Eye effects: Sensitization:	toxicological effects:	No data available. No irritant effect. Irritating effect. No sensitizing effects known.
12 Ecological int	formation	
Aquatic toxicit Persistence an Bioaccumulati Mobility in soil Other adverse	d degradability: ve potential: :	Hazardous for water, do not empty into drains. The product is degradable after prolonged exposure to natural weathering processes. No further relevant information available. No further relevant information available. No further relevant information available.
13 Disposal cons Dispose of in ac be disposed of Recommendat	ccordance with local, s responsibly. Do not hea	tate, and federal regulations. Do not puncture, incinerate, or compact. Partially empty cans must at or cut empty containers with electric or gas torches. Completely empty cans should be recycled.
14 Transport info	ormation	
UN-Number		UN1950

Page 3/4

(Contd. of page 2)

Revised On 03/15/2017

Printing date 03/17/2017

Safety Data Sheet

Revised On 03/15/2017

Page 4/4

nting date 03/17/2017	Revised On 03/15/201
ade name: SAFETY BLUE	
DOT	(Contd. of page 3
	UN1950
DOT	Consumer Commodity ORM-D
ADR	Aerosols, flammable 1950 Aerosols
Transport hazard class(es):	1950 Aerosols
Class	2.1
Marine pollutant:	No
Special precautions for user: EMS Number:	Warning: Gases
Packaging Group:	F-D,S-U
UN "Model Regulation":	UN1950, Aerosols, 2.1
5 Regulatory information	
SARA Section 355 (extremely haza	rdous substances):
None of the ingredients in this produc	
SARA Section 313 (Specific toxic c	
108-10-1 methyl isobutyl ketone	nemica iistiigs).
Toxic Substances Control Act	
(TSCA):	All ingredients for this product are found on the inventory list of substances.
Consumer Product Safety	
Comission (CPSC):	This product complies with 16 CFR 1303 and does not contain more than 90 ppm of lead.
California Proposition 65 chemical	s known to cause cancer:
108-10-1 methyl isobutyl ketone	
13463-67-7 titanium dioxide	
100-41-4 ethyl benzene	
	s known to cause birth defects or reproductive harm:
108-10-1 methyl isobutyl ketone	
CANADIAN ENVIRONMENTAL PROTECTION ACT:	All benerdeus ingradients far this product oppose on the Consedier Demostics Cubatance List
WHMIS Symbols for Canada:	All hazardous ingredients for this product appear on the Canadian Domestice Substance List. A - Compressed gas
	D2 <u>B</u> - Toxic material causing other toxic effects
EPA:	
67-64-1 Acetone	
110-19-0 Isobutyl Acetate	
108-10-1 methyl isobutyl ketone	
6 Other information	
	De sud-teme Affeire
Contact: Date of preparation / last revision	Regulatory Affairs