# SAFETY DATA SHEET


### 1. Identification

Product number	1000014885
Product identifier	1.4OZ AAS STATIC GUARD 80755310 LT 12PK
Company information	Assured Packaging Inc 6080 Vipond Drive Mississauga, ON L5T 2V4 Canada
Company phone	General Assistance 1-905-565-1410
Emergency telephone US	1-866-836-8855
Emergency telephone outside US	1-952-852-4646
Version #	01
Recommended use	Coating
Recommended restrictions	None known.

# 2. Hazard(s) identification

# Physical hazards Health hazards **OSHA** defined hazards

#### Label elements



Category 1



Signal word	Danger
Hazard statement	Extremely flammable aerosol.
Precautionary statement	
Prevention	Keep away from heat/sparks/open flames/hot surfaces No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use.
Response	Wash hands after handling.
Storage	Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
Disposal	Dispose of waste and residues in accordance with local authority requirements.
Hazard(s) not otherwise classified (HNOC)	None known.
Supplemental information	None.

## 3. Composition/information on ingredients

#### **Mixtures**

Chemical name	Common name and synonyms	CAS number	%
Ethyl Alcohol		64-17-5	60 - 80
1,1-Difluoroethane		75-37-6	10 - 20
Isobutane		75-28-5	2.5 - 10
Propane		74-98-6	1 - 2.5
Quaternary Ammonium Compounds, Bis(hydrogenated Tallow Alkyl)dimethyl, Chlorides		61789-80-8	1 - 2.5
Other components below reportable	elevels		0.1 - 1

\*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

## 4. First-aid measures

Inhalation	If symptoms develop move victim to fresh air. Get medical attention if symptoms persist.
Skin contact	Wash off with soap and water. Get medical attention if irritation develops and persists.
Eye contact	Rinse with water. Get medical attention if irritation develops and persists.
Ingestion	Rinse mouth. Get medical attention if symptoms occur.
Most important symptoms/effects, acute and delayed	Headache. Coughing.
Indication of immediate medical attention and special treatment needed	Treat symptomatically.
General information	Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

# 5. Fire-fighting measures

Suitable extinguishing media	Alcohol resistant foam. Powder. Carbon dioxide (CO2).
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	Contents under pressure. Pressurized container may explode when exposed to heat or flame. During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.
Fire fighting equipment/instructions	Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk. Use water spray to cool unopened containers. In the event of fire and/or explosion do not breathe fumes.
General fire hazards	Extremely flammable aerosol.

# 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	Refer to attached safety data sheets and/or instructions for use. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Isolate area until gas has dispersed. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. For waste disposal, see section 13 of the SDS.
Environmental precautions	Avoid discharge into drains, water courses or onto the ground.
7. Handling and storage	
Precautions for safe handling	Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.
Conditions for safe storage,	Level 2 Aerosol.
including any incompatibilities	Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store away from incompatible materials (see Section 10 of the SDS).

# 8. Exposure controls/personal protection

### Occupational exposure limits

Components	Туре	000) Value
Ethyl Alcohol (CAS 64-17-5)	PEL	1900 mg/m3
		1000 ppm
Propane (CAS 74-98-6)	PEL	1800 mg/m3
		1000 ppm
US. ACGIH Threshold Limit	Values	
Components	Туре	Value
Ethyl Alcohol (CAS 64-17-5)	STEL	1000 ppm
Isobutane (CAS 75-28-5)	STEL	1000 ppm
US. NIOSH: Pocket Guide t	o Chemical Hazards	
Components	Туре	Value
Ethyl Alcohol (CAS 64-17-5)	TWA	1900 mg/m3
		1000 ppm
Isobutane (CAS 75-28-5)	TWA	1900 mg/m3
		800 ppm
Propane (CAS 74-98-6)	TWA	1800 mg/m3
		1000 ppm
	ntal Exposure Level (WEEL) Guides	
Components	Туре	Value
1,1-Difluoroethane (CAS 75-37-6)	TWA	2700 mg/m3
		1000 ppm
logical limit values	No biological exposure limits noted for	
propriate engineering htrols	Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.	
inois		
		ished, maintain airborne levels to an acceptable level.
	exposure limits have not been establ	ished, maintain airborne levels to an acceptable level. nent
ividual protection measures	exposure limits have not been establ , such as personal protective equipm	ished, maintain airborne levels to an acceptable level. nent
ividual protection measures Eye/face protection	exposure limits have not been establ , such as personal protective equipm Wear safety glasses with side shields	ished, maintain airborne levels to an acceptable level. nent s (or goggles).
ividual protection measures Eye/face protection Skin protection	exposure limits have not been establ , such as personal protective equipm Wear safety glasses with side shields Wear appropriate chemical resistant	ished, maintain airborne levels to an acceptable level. nent
ividual protection measures Eye/face protection Skin protection Hand protection	exposure limits have not been establ <b>such as personal protective equipm</b> Wear safety glasses with side shields Wear appropriate chemical resistant supplier. Wear suitable protective clothing.	ished, maintain airborne levels to an acceptable level. nent s (or goggles).
ividual protection measures Eye/face protection Skin protection Hand protection Other	exposure limits have not been estable <b>such as personal protective equipm</b> Wear safety glasses with side shields Wear appropriate chemical resistant supplier. Wear suitable protective clothing. If permissible levels are exceeded us	ished, maintain airborne levels to an acceptable level. <b>nent</b> s (or goggles). gloves. Suitable gloves can be recommended by the glov se NIOSH mechanical filter / organic vapor cartridge or an

#### 9. Physical and chemical properties

Appearance	
Physical state	Gas.
Form	Aerosol.
Color	Not available.
Odor	Not available.
Odor threshold	Not available.
рН	Not available.
Melting point/freezing point	Not available.
Initial boiling point and boiling range	Not available.

Flash point	-156.0 °F (-104.4 °C) Propellant estimated		
Evaporation rate	Not available.		
Flammability (solid, gas)	Not available.		
Upper/lower flammability or explosive limits			
Flammability limit - lower (%)	3.5 % estimated		
Flammability limit - upper (%)	18.4 % estimated		
Explosive limit - lower (%)	Not available.		
Explosive limit - upper (%)	Not available.		
Vapor pressure	Not available.		
Vapor density	Not available.		
Relative density	Not available.		
Solubility(ies)			
Solubility (water)	Not available.		
Partition coefficient (n-octanol/water)	Not available.		
Auto-ignition temperature	807.97 °F (431.1 °C) estimated		
Decomposition temperature	Not available.		
Viscosity	Not available.		
Other information			
Explosive properties	Not explosive.		
Oxidizing properties	Not oxidizing.		
Specific gravity	0.232 estimated		
10. Stability and reactivity	,		

#### 10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	Hazardous polymerization does not occur.
Conditions to avoid	Avoid temperatures exceeding the flash point. Contact with incompatible materials.
Incompatible materials	Strong oxidizing agents. Nitrates. Fluorine. Chlorine.
Hazardous decomposition products	No hazardous decomposition products are known.

# 11. Toxicological information

# Information on likely routes of exposure

Inhalation	No adverse effects due to inhalation are expected.
Skin contact	No adverse effects due to skin contact are expected.
Eye contact	Direct contact with eyes may cause temporary irritation.
Ingestion	Expected to be a low ingestion hazard.
Symptoms related to the physical, chemical and toxicological characteristics	Headache. Coughing.

### Information on toxicological effects

Species	Test Results
Cat	85.41 mg/l, 4.5 Hours
	43.68 mg/l, 6 Hours
	•

omponents	Species	Test Results
	Mouse	> 60000 ppm
		79.43 mg/l, 134 Minutes
	Rat	> 115.9 mg/l, 4 Hours
		51.3 mg/l, 6 Hours
Oral	Mankov	6000 malka
LD50	Monkey	6000 mg/kg
	Mouse	10500 ml/kg
	Pig	> 5000 mg/kg
	Rat	10470 mg/kg
		7800 ml/kg
obutane (CAS 75-28-5)		
<u>Acute</u>		
Inhalation LC50	Mouse	1237 mg/l, 120 Minutes
2000	WOUSE	52 %, 120 Minutes
	Pat	
	Rat	1355 mg/l
ropane (CAS 74-98-6) <u>Acute</u>		
Inhalation		
LC50	Mouse	1237 mg/l, 120 Minutes
		52 %, 120 Minutes
		1355 mg/l
	Rat	
	Rat	658 mg/l/4h
uaternary Ammonium Compou <u>Acute</u> Dermal	Rat Inds, Bis(hydrogenated Tallow Alkyl)dimethy	658 mg/l/4h
Acute		658 mg/l/4h
<u>Acute</u> Dermal	inds, Bis(hydrogenated Tallow Alkyl)dimethy	658 mg/l/4h I, Chlorides (CAS 61789-80-8)
Acute Dermal LD50	inds, Bis(hydrogenated Tallow Alkyl)dimethy	658 mg/l/4h I, Chlorides (CAS 61789-80-8)
Acute Dermal LD50 Inhalation	unds, Bis(hydrogenated Tallow Alkyl)dimethy Rat	658 mg/l/4h I, Chlorides (CAS 61789-80-8) > 2000 mg/kg, 24 Hours > 180 mg/l, 60 Minutes
Acute Dermal LD50 Inhalation LC50	unds, Bis(hydrogenated Tallow Alkyl)dimethy Rat	658 mg/l/4h I, Chlorides (CAS 61789-80-8) > 2000 mg/kg, 24 Hours
Acute Dermal LD50 Inhalation LC50 Oral LD50	unds, Bis(hydrogenated Tallow Alkyl)dimethy Rat Rat Rat v be based on additional component data not	658 mg/l/4h I, Chlorides (CAS 61789-80-8) > 2000 mg/kg, 24 Hours > 180 mg/l, 60 Minutes > 2000 mg/kg shown.
Acute Dermal LD50 Inhalation LC50 Oral LD50	unds, Bis(hydrogenated Tallow Alkyl)dimethy Rat Rat Rat	658 mg/l/4h I, Chlorides (CAS 61789-80-8) > 2000 mg/kg, 24 Hours > 180 mg/l, 60 Minutes > 2000 mg/kg shown.
Acute Dermal LD50 Inhalation LC50 Oral LD50 * Estimates for product may	unds, Bis(hydrogenated Tallow Alkyl)dimethy Rat Rat Rat v be based on additional component data not	658 mg/l/4h I, Chlorides (CAS 61789-80-8) > 2000 mg/kg, 24 Hours > 180 mg/l, 60 Minutes > 2000 mg/kg shown. orary irritation.
Acute Dermal LD50 Inhalation LC50 Oral LD50 * Estimates for product may kin corrosion/irritation erious eye damage/eye	unds, Bis(hydrogenated Tallow Alkyl)dimethy Rat Rat Rat be based on additional component data not Prolonged skin contact may cause temp Direct contact with eyes may cause temp	658 mg/l/4h I, Chlorides (CAS 61789-80-8) > 2000 mg/kg, 24 Hours > 180 mg/l, 60 Minutes > 2000 mg/kg shown. orary irritation.
Acute Dermal LD50 Inhalation LC50 Oral LD50 * Estimates for product may kin corrosion/irritation erious eye damage/eye ritation	unds, Bis(hydrogenated Tallow Alkyl)dimethy Rat Rat Rat be based on additional component data not Prolonged skin contact may cause temp Direct contact with eyes may cause temp	658 mg/l/4h I, Chlorides (CAS 61789-80-8) > 2000 mg/kg, 24 Hours > 180 mg/l, 60 Minutes > 2000 mg/kg shown. orary irritation.
Acute Dermal LD50 Inhalation LC50 Oral LD50 * Estimates for product may kin corrosion/irritation erious eye damage/eye ritation espiratory or skin sensitizati	unds, Bis(hydrogenated Tallow Alkyl)dimethy Rat Rat Rat be based on additional component data not Prolonged skin contact may cause temp Direct contact with eyes may cause temp	658 mg/l/4h I, Chlorides (CAS 61789-80-8) > 2000 mg/kg, 24 Hours > 180 mg/l, 60 Minutes > 2000 mg/kg shown. orary irritation. porary irritation.
Acute Dermal LD50 Inhalation LC50 Oral LD50 * Estimates for product may kin corrosion/irritation erious eye damage/eye ritation espiratory or skin sensitizati Respiratory sensitization	ands, Bis(hydrogenated Tallow Alkyl)dimethy Rat Rat Rat be based on additional component data not Prolonged skin contact may cause temp Direct contact with eyes may cause temp <b>on</b> Not a respiratory sensitizer. This product is not expected to cause sk	658 mg/l/4h I, Chlorides (CAS 61789-80-8) > 2000 mg/kg, 24 Hours > 180 mg/l, 60 Minutes > 2000 mg/kg shown. orary irritation. porary irritation.
Acute Dermal LD50 Inhalation LC50 Oral LD50 * Estimates for product may kin corrosion/irritation erious eye damage/eye ritation espiratory or skin sensitizati Respiratory sensitization Skin sensitization	Inds, Bis(hydrogenated Tallow Alkyl)dimethy Rat Rat Rat Tobe based on additional component data not Prolonged skin contact may cause temp Direct contact with eyes may cause temp Direct contact with eyes may cause temp Not a respiratory sensitizer. This product is not expected to cause sk No data available to indicate product or a mutagenic or genotoxic.	658 mg/l/4h I, Chlorides (CAS 61789-80-8) > 2000 mg/kg, 24 Hours > 180 mg/l, 60 Minutes > 2000 mg/kg shown. orary irritation. porary irritation.
Acute Dermal LD50 Inhalation LC50 Oral LD50 * Estimates for product may kin corrosion/irritation erious eye damage/eye ritation espiratory or skin sensitizati Respiratory sensitization Skin sensitization erm cell mutagenicity arcinogenicity IARC Monographs. Overal	Inds, Bis(hydrogenated Tallow Alkyl)dimethy Rat Rat Rat Tobe based on additional component data not Prolonged skin contact may cause temp Direct contact with eyes may cause temp Direct contact with eyes may cause temp Not a respiratory sensitizer. This product is not expected to cause sk No data available to indicate product or a mutagenic or genotoxic.	658 mg/l/4h I, Chlorides (CAS 61789-80-8) > 2000 mg/kg, 24 Hours > 180 mg/l, 60 Minutes > 2000 mg/kg shown. orary irritation. porary irritation. porary irritation.
Acute Dermal LD50 Inhalation LC50 Oral LD50 * Estimates for product may kin corrosion/irritation erious eye damage/eye ritation espiratory or skin sensitizati Respiratory sensitization Skin sensitization erm cell mutagenicity arcinogenicity IARC Monographs. Overal Not listed. OSHA Specifically Regula	Rat Rat Rat Rat Not a respiratory sensitizer. This product is not considered to be a ca	658 mg/l/4h I, Chlorides (CAS 61789-80-8) > 2000 mg/kg, 24 Hours > 180 mg/l, 60 Minutes > 2000 mg/kg shown. orary irritation. porary irritation. in sensitization. any components present at greater than 0.1% are arcinogen by IARC, ACGIH, NTP, or OSHA.
Acute Dermal LD50 Inhalation LC50 Oral LD50 * Estimates for product may kin corrosion/irritation erious eye damage/eye ritation espiratory or skin sensitizati Respiratory sensitization skin sensitization skin sensitization erm cell mutagenicity arcinogenicity IARC Monographs. Overal Not listed. OSHA Specifically Regula Not regulated.	Inds, Bis(hydrogenated Tallow Alkyl)dimethy Rat Rat Rat be based on additional component data not Prolonged skin contact may cause temp Direct contact with eyes may cause temp Direct contact with eyes may cause temp on Not a respiratory sensitizer. This product is not expected to cause sk No data available to indicate product or a mutagenic or genotoxic. This product is not considered to be a ca Il Evaluation of Carcinogenicity	658 mg/l/4h I, Chlorides (CAS 61789-80-8) > 2000 mg/kg, 24 Hours > 180 mg/l, 60 Minutes > 2000 mg/kg shown. orary irritation. porary irritation. porary irritation.

Specific target organ toxicity - single exposure	Not classified.
Specific target organ toxicity - repeated exposure	Not classified.
Aspiration hazard	Not likely, due to the form of the product.

### 12. Ecological information

Ecotoxicity

The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

	pooolonity	possibility that large of nequent opine can have a narmar of damaging check of the christiannent.		
Components		Species	Test Results	
Ethyl Alcohol (CAS 64-	Ethyl Alcohol (CAS 64-17-5)			
Aquatic				
Crustacea	EC50	Water flea (Daphnia magna)	7700 - 11200 mg/l, 48 hours	
Fish	LC50	Fathead minnow (Pimephales prom	nelas) >100.1 mg/l, 96 hours	

\* Estimates for product may be based on additional component data not shown.

Persistence and degradability No data is available on the degradability of this product.

### **Bioaccumulative potential**

Partition coefficient n-octanol / water (log Kow)		
1,1-Difluoroethane	0.75	
Ethyl Alcohol	-0.31	
Isobutane	2.76	
Propane	2.36	
Mobility in soil	No data available.	
Other adverse effects	No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.	

## 13. Disposal considerations

Disposal instructions	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Dispose of contents/container in accordance with local/regional/national/international regulations.
Local disposal regulations	Dispose in accordance with all applicable regulations.
Hazardous waste code	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Waste from residues / unused products	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers.

# 14. Transport information

DOT	
UN number	UN1950
UN proper shipping name	Aerosols, flammable, (each not exceeding 1 L capacity)
Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Label(s)	2.1
Packing group	Not applicable.
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Special provisions	N82
Packaging exceptions	306
Packaging non bulk	None
Packaging bulk	None
This product mosts the event	an requirements of agotion 172,206 as a limited quantity and may be obinned as a limited quan

This product meets the exception requirements of section 173.306 as a limited quantity and may be shipped as a limited quantity. Until 12/31/2020, the "Consumer Commodity - ORM-D" marking may still be used in place of the new limited quantity diamond mark for packages of UN 1950 Aerosols. Limited quantities require the limited quantity diamond mark on cartons after 12/31/20 and may be used now in place of the "Consumer Commodity ORM-D" marking.

ΙΑΤΑ	
UN number	UN1950
UN proper shipping name Transport hazard class(es)	Aerosols, flammable
Class	2.1
Subsidiary risk	-
Label(s)	2.1
Packing group	Not applicable.
Environmental hazards	No.
ERG Code	10L
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling. Read safety instructions, SDS and emergency procedures before handling.
Other information	
Passenger and cargo aircraft	Allowed with restrictions.
Cargo aircraft only	Allowed with restrictions.
Packaging Exceptions	LTD QTY
IMDG	
UN number	UN1950
UN proper shipping name	AEROSOLS
Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Label(s)	None
Packing group	Not applicable.
Environmental hazards	
Marine pollutant	No.
EmS	F-D, S-U
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling. Read safety instructions, SDS and emergency procedures before handling.
Packaging Exceptions	LTD QTY
Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	Not applicable.

DOT



# 15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D) Not regulated. CERCLA Hazardous Substance List (40 CFR 302.4) Not listed. SARA 304 Emergency release notification Not regulated. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050) Not regulated. Superfund Amendments and Reauthorization Act of 1986 (SARA) **Hazard categories** Immediate Hazard - No Delayed Hazard - No Fire Hazard - Yes Pressure Hazard - No Reactivity Hazard - No SARA 302 Extremely hazardous substance Not listed. SARA 311/312 Hazardous No chemical SARA 313 (TRI reporting) Not regulated. Other federal regulations Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List Not regulated. Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130) 1.1-Difluoroethane (CAS 75-37-6) Isobutane (CAS 75-28-5) Propane (CAS 74-98-6) Safe Drinking Water Act Not regulated. (SDWA) US state regulations US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100) Not listed. US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a)) Isobutane (CAS 75-28-5) **US. Massachusetts RTK - Substance List** 1.1-Difluoroethane (CAS 75-37-6) Ethyl Alcohol (CAS 64-17-5) Isobutane (CAS 75-28-5) Propane (CAS 74-98-6) US. New Jersey Worker and Community Right-to-Know Act 1,1-Difluoroethane (CAS 75-37-6) Ethyl Alcohol (CAS 64-17-5) Isobutane (CAS 75-28-5) Propane (CAS 74-98-6) US. Pennsylvania Worker and Community Right-to-Know Law Ethyl Alcohol (CAS 64-17-5) Isobutane (CAS 75-28-5) Propane (CAS 74-98-6) **US. Rhode Island RTK** 1.1-Difluoroethane (CAS 75-37-6) Isobutane (CAS 75-28-5) Propane (CAS 74-98-6) US. California Proposition 65 California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

#### International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

\*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

# 16. Other information, including date of preparation or last revision

Issue date	10-27-2017
Version #	01
Disclaimer	The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.