# **CR**@

# SAFETY DATA SHEET

## 1. Identification

Product identifier Industrial Adhesive Remover

Other means of identification

**Product Code** No. 03250 (Item# 1003473)

Recommended use Adhesive remover
Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Manufactured or sold by:

Company name CRC Industries, Inc.

Address 885 Louis Dr.

Warminster, PA 18974 US

Telephone

 General Information
 215-674-4300

 Technical Assistance
 800-521-3168

 Customer Service
 800-272-4620

 24-Hour Emergency
 800-424-9300 (US)

(CHEMTREC) 703-527-3887 (International)
Website www.crcindustries.com

# 2. Hazard(s) identification

Physical hazards Flammable aerosols Category 1

Aspiration hazard

Gases under pressure Compressed gas Serious eye damage/eye irritation Category 2A

Environmental hazards Not classified.

OSHA defined hazards Not classified.

Label elements

**Health hazards** 



Signal word Danger

Hazard statement Extremely flammable aerosol. Contains gas under pressure; may explode if heated. May be fatal if

swallowed and enters airways. Causes serious eye irritation.

**Precautionary statement** 

**Prevention** Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open

flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Do not apply while equipment is energized. Extinguish all flames, pilot lights, and heaters. Vapors will accumulate readily and may ignite. Use only with adequate ventilation; maintain ventilation during use and until all vapors are gone. Open doors and windows or use other means to ensure a fresh air supply during use and while product is drying. If you experience any symptoms listed on this label, increase ventilation or leave the area. Wash thoroughly after handling. Wear eye

Category 1

protection/face protection.

Response If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting. If in eyes: Rinse

cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing. If eye irritation persists: Get medical advice/attention.

Storage Store in a well-ventilated place. Store locked up. Protect from sunlight. Do not expose to

temperatures exceeding 50°C/122°F. Exposure to high temperature may cause can to burst.

**Disposal** Dispose of contents/container in accordance with local/regional/national regulations.

Material name: Industrial Adhesive Remover
No. 03250 (Item# 1003473) Version #: 02 Revision date: 02-15-2018 Issue date: 10-15-2014

None known.

Supplemental information

None.

# 3. Composition/information on ingredients

#### **Mixtures**

Ingestion

Chemical name	Common name and synonyms	CAS number	<u></u>
distillates (petroleum), hydrotreate light	d	64742-47-8	50 - 60
dipropylene glycol monopropyl ether (dpmp)		29911-27-1	20 - 30
carbon dioxide		124-38-9	3 - 5

Specific chemical identity and/or percentage of composition has been withheld as a trade secret.

#### 4. First-aid measures

**Inhalation** Move to fresh air. Call a physician if symptoms develop or persist.

**Skin contact** Wash off with soap and water. Get medical attention if irritation develops and persists.

**Eye contact** Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If

Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred

can a physician of poison control center immediately. Kinse mount, by not induce voin

vomiting occurs, keep head low so that stomach content doesn't get into the lungs.

Most important symptoms/effects, acute and

delayed

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

Aspiration may cause pulmonary edema and pneumonitis. Headache. Nausea, vomiting. Diarrhea.

**General information**Ensure that medical personnel are aware of the material(s) involved, and take precautions to

protect themselves.

vision.

# 5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing media

Specific hazards arising from

the chemical

Special protective equipment and precautions for firefighters

Fire fighting

equipment/instructions

General fire hazards

Water fog. Alcohol resistant foam. Dry chemical powder. Dry chemicals. Carbon dioxide (CO2).

Do not use water jet as an extinguisher, as this will spread the fire.

Contents under pressure. Pressurized container may rupture when exposed to heat or flame. During fire, gases hazardous to health may be formed.

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

In case of fire: Stop leak if safe to do so. Move containers from fire area if you can do so without risk. Cool containers exposed to heat with water spray and remove container, if no risk is involved. Containers should be cooled with water to prevent vapor pressure build up.

Extremely flammable aerosol. Contents under pressure. Pressurized container may rupture when exposed to heat or flame.

#### 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Many gases are heavier than air and will spread along ground and collect in low or confined areas (sewers, basements, tanks). Wear appropriate protective equipment and clothing during clean-up. Emergency personnel need self-contained breathing equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. This product is miscible in water. This material is classified as a water pollutant under the Clean Water Act and should be prevented from contaminating soil or from entering sewage and drainage systems which lead to waterways. Stop the flow of material, if this is without risk. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the SDS.

Material name: Industrial Adhesive Remover

ndustrial Adhesive Remover

#### **Environmental precautions**

Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

## 7. Handling and storage

#### Precautions for safe handling

Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. Use caution around energized equipment. The metal container will conduct electricity if it contacts a live source. This may result in injury to the user from electrical shock and/or flash fire. Avoid contact with eyes. Avoid prolonged or repeated contact with skin. Avoid prolonged exposure. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Observe good industrial hygiene practices. For product usage instructions, see the product label.

## Conditions for safe storage, including any incompatibilities

Level 2 Aerosol.

Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store in a well-ventilated place. Stored containers should be periodically checked for general condition and leakage. Store away from incompatible materials (see Section 10 of the SDS).

# 8. Exposure controls/personal protection

#### Occupational exposure limits

US. OSHA	Table 7-1	l imite fo	r Air Contar	ninante /29	CFR 1910	1000\

Components	Type	Value	
carbon dioxide (CAS 124-38-9)	PEL	9000 mg/m3	
·		5000 ppm	
distillates (petroleum), hydrotreated light (CAS 64742-47-8)	PEL	400 mg/m3	
,		100 ppm	
US. ACGIH Threshold Limit Valu	ies		
Components	Туре	Value	
carbon dioxide (CAS 124-38-9)	STEL	30000 ppm	
,	TWA	5000 ppm	
US. NIOSH: Pocket Guide to Che	emical Hazards		
_	Turne	Value	
Components	Туре	Value	

# 64742-47-8) **Biological limit values**

distillates (petroleum),

hydrotreated light (CAS

No biological exposure limits noted for the ingredient(s).

**TWA** 

**TWA** 

# Appropriate engineering

controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash facilities and emergency shower should be available when handling this product.

30000 ppm

9000 mg/m3 5000 ppm

100 mg/m3

#### Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin protection

Hand protection Wear protective gloves such as: Nitrile. Neoprene.

Other Wear appropriate chemical resistant clothing.

Material name: Industrial Adhesive Remover

SDS US

**Respiratory protection** If engineering controls are not feasible or if exposure exceeds the applicable exposure limits, use a

NIOSH-approved cartridge respirator with an organic vapor cartridge. Use a self-contained breathing apparatus in confined spaces and for emergencies. Air monitoring is needed to

determine actual employee exposure levels.

**Thermal hazards** Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work

clothing and protective equipment to remove contaminants.

# 9. Physical and chemical properties

**Appearance** 

Physical state Liquid.

Form Aerosol.

Color Water-white.

Odor Slight. Hydrocarbon-like.

Odor threshold Not available.
pH Not available.

Melting point/freezing point -121 °F (-85 °C) estimated Initial boiling point and boiling 392 °F (200 °C) estimated

range

Flash point 185 °F (85 °C) Setaflash

**Evaporation rate** Slow.

Flammability (solid, gas) Not available.

Upper/lower flammability or explosive limits

Flammability limit - lower

0.6 % estimated

(%)

Flammability limit - upper

8.3 % estimated

(%)

Vapor pressure 2265.4 hPa estimated

Vapor density > 1 (air = 1)

Relative density 0.87 estimated

Solubility(ies)

Solubility (water) Slightly soluble.

Partition coefficient Not available.

(n-octanol/water)

Auto-ignition temperature 401 °F (205 °C) estimated

**Decomposition temperature**Not available. **Percent volatile**96 % estimated

#### 10. Stability and reactivity

**Reactivity**The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoid Heat, flames and sparks. Avoid temperatures exceeding the flash point. Contact with incompatible

materials.

Incompatible materials Strong oxidizing agents.

**Hazardous decomposition** Carbon oxides. Aldehydes. Ketones. Organic acids.

products

#### 11. Toxicological information

# Information on likely routes of exposure

**Inhalation** Prolonged inhalation may be harmful.

**Skin contact** No adverse effects due to skin contact are expected.

**Eye contact** Causes serious eye irritation.

Material name: Industrial Adhesive Remover

SDS US

No. 03250 (Item# 1003473) Version #: 02 Revision date: 02-15-2018 Issue date: 10-15-2014

Ingestion Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious

chemical pneumonia.

Symptoms related to the physical, chemical and toxicological characteristics Aspiration may cause pulmonary edema and pneumonitis. Headache. Nausea, vomiting. Diarrhea. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and

1475 mg/kg

Information on toxicological effects

May be fatal if swallowed and enters airways. **Acute toxicity** 

Components **Test Results Species** 

dipropylene glycol monopropyl ether (dpmp) (CAS 29911-27-1)

Acute Dermal

LD50 Rabbit > 2000 mg/kg 5340 mg/kg

Oral

LD50 Rat > 2000 mg/kg

distillates (petroleum), hydrotreated light (CAS 64742-47-8)

Acute

Dermal

LD50 Rabbit > 2000 mg/kg

Inhalation

Rat LC50 > 20 mg/l, 4 hours

Oral

LD50 Rat > 5000 mg/kg

Skin corrosion/irritation Prolonged skin contact may cause temporary irritation.

Serious eye damage/eye

irritation

Causes serious eye irritation.

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization This product is not expected to cause skin sensitization.

Germ cell mutagenicity No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Not classifiable as to carcinogenicity to humans. Carcinogenicity

IARC Monographs. Overall Evaluation of Carcinogenicity

Not listed.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

Not regulated.

US. National Toxicology Program (NTP) Report on Carcinogens

Not listed.

Reproductive toxicity This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

Not classified.

May be fatal if swallowed and enters airways. If aspirated into lungs during swallowing or vomiting, **Aspiration hazard** 

may cause chemical pneumonia, pulmonary injury or death.

**Chronic effects** Prolonged inhalation may be harmful.

# 12. Ecological information

The product is not classified as environmentally hazardous. However, this does not exclude the **Ecotoxicity** 

possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Material name: Industrial Adhesive Remover

Components Species Test Results

dipropylene glycol monopropyl ether (dpmp) (CAS 29911-27-1)

Aquatic

Acute

Crustacea EC50 Water flea (Daphnia magna) > 100 mg/l, 48 hours
Fish LC50 Rainbow trout,donaldson trout > 100 mg/l, 96 hours

(Oncorhynchus mykiss)

distillates (petroleum), hydrotreated light (CAS 64742-47-8)

Aquatic

Crustacea EC50 Water flea (Daphnia pulex) 2.7 - 5.1 mg/l, 48 hours

**Persistence and degradability** No data is available on the degradability of any ingredients in the mixture.

**Bioaccumulative potential** 

Partition coefficient n-octanol / water (log Kow)

dipropylene glycol monopropyl ether (dpmp) 0.87 OECD 107 0.88 OECD 107

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Hazardous waste code Not regulated.

**Contaminated packaging** Empty containers should be taken to an approved waste handling site for recycling or disposal.

Since emptied containers may retain product residue, follow label warnings even after container is

emptied.

**Disposal instructions**The dispensed liquid product is not a RCRA hazardous waste (See 40 CFR Part 261.20 - 261.33).

Empty container can be recycled. Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches

with chemical or used container. Dispose in accordance with all applicable regulations.

14. Transport information

DOT

UN number UN1950

UN proper shipping name

Transport hazard class(es)

Aerosols, flammable, Limited Quantity

Class 2.1 Subsidiary risk -Label(s) 2.1

Packing group Not applicable.

**Special precautions for user** Read safety instructions, SDS and emergency procedures before handling.

Special provisionsN82Packaging exceptions306Packaging non bulk304Packaging bulkNone

IATA

UN number UN1950

**UN proper shipping name** Aerosols, flammable, Limited Quantity

Transport hazard class(es)

Class 2.1 Subsidiary risk -

Packing group Not applicable.

ERG Code 10L

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Other information

Passenger and cargo

aircraft

Allowed with restrictions.

Cargo aircraft only

Allowed with restrictions.

**IMDG** 

UN number UN1950

**UN** proper shipping name AEROSOLS, Limited Quantity

Transport hazard class(es)

2 Class Subsidiary risk

Packing group Not applicable.

**Environmental hazards** 

Marine pollutant No. F-D, S-U **EmS** 

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

#### 15. Regulatory information

**US federal regulations** This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

Not regulated.

US EPCRA (SARA Title III) Section 313 - Toxic Chemical: Listed substance

Not regulated.

**CERCLA Hazardous Substance List (40 CFR 302.4)** 

**CERCLA Hazardous Substances: Reportable quantity** 

Not listed.

Spills or releases resulting in the loss of any ingredient at or above its RQ require immediate notification to the National Response Center (800-424-8802) and to your Local Emergency Planning Committee.

#### Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

Not regulated. Food and Drug

Administration (FDA)

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Flammable (gases, aerosols, liquids, or solids) Classified hazard

Gas under pressure categories

Acute toxicity (any route of exposure) Serious eye damage or eye irritation

Aspiration hazard

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous Yes

chemical

SARA 313 (TRI reporting)

Not regulated.

#### US state regulations

US. New Jersey Worker and Community Right-to-Know Act

carbon dioxide (CAS 124-38-9)

**US. Massachusetts RTK - Substance List** 

carbon dioxide (CAS 124-38-9)

US. Pennsylvania Worker and Community Right-to-Know Law

carbon dioxide (CAS 124-38-9)

distillates (petroleum), hydrotreated light (CAS 64742-47-8)

No. 03250 (Item# 1003473) Version #: 02 Revision date: 02-15-2018 Issue date: 10-15-2014

Material name: Industrial Adhesive Remover

#### US. Rhode Island RTK

carbon dioxide (CAS 124-38-9)

#### **California Proposition 65**

California Safe Drinking Water and Toxic Enforcement Act of 2016 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins. For more information go to www.P65Warnings.ca.gov.

# US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

distillates (petroleum), hydrotreated light (CAS 64742-47-8)

#### Volatile organic compounds (VOC) regulations

**EPA** 

VOC content (40 CFR

. (--

96 %

Consumer products

51.100(s))

(40 CFR 59, Subpt. C)

Not regulated

State

Consumer products This product is regulated as a General Purpose Adhesive Remover. This product is compliant for

use in all 50 states.

VOC content (CA) 0 % VOC content (OTC) 0 %

#### **International Inventories**

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No

EuropeEuropean List of Notified Chemical Substances (ELINCS)YesJapanInventory of Existing and New Chemical Substances (ENCS)NoKoreaExisting Chemicals List (ECL)YesNew ZealandNew Zealand InventoryYesPhilippinesPhilippine Inventory of Chemicals and Chemical SubstancesYes

(PICCS)

TaiwanTaiwan Toxic Chemical Substances (TCS)YesUnited States & Puerto RicoToxic Substances Control Act (TSCA) InventoryYes

#### 16. Other information, including date of preparation or last revision

Issue date10-15-2014Revision date02-15-2018Prepared byAllison Yoon

Version # 02

Further information CRC # 490C/1002479

**Disclaimer** The information contained in this document applies to this specific material as supplied. It may not

be valid for this material if it is used in combination with any other materials. This information is accurate to the best of CRC's knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label. For further clarification of any information contained on this (M)SDS consult your supervisor, a health & safety

professional, or CRC Industries, Inc..

**Revision information**This document has undergone significant changes and should be reviewed in its entirety.

No. 03250 (Item# 1003473) Version #: 02 Revision date: 02-15-2018 Issue date: 10-15-2014

<sup>\*</sup>A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).