SAFETY DATA SHEET



1. Identification

Product identifier OCAL Spray Patch- Gray

Other means of identification

SDS number SDS-00024
Product code SPRAY-G

Recommended use Vinyl Resin Coating.

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Company name Thomas & Betts Corporation
Address 8155 T & B Boulevard

Memphis, TN 38125

USA

Telephone 901-252-5000 ext.8324

E-mail Not available.

Emergency phone number For Hazardous Materials [or Dangerous Goods] Incident

Spill, Leak, Fire, Exposure, or Accident Call CHEMTREC Day or Night +1 703-741-5970

2. Hazard(s) identification

Physical hazardsFlammable aerosolsCategory 1Health hazardsAcute toxicity, inhalationCategory 4

Acute toxicity, inhalation

Category 4

Skin corrosion/irritation

Category 2

Serious eye damage/eye irritation

Category 2A

Carcinogenicity

Category 1A

Reproductive toxicity

Category 2

Specific target organ toxicity, single exposure Category 3 respiratory tract irritation

Specific target organ toxicity, single exposure Category 3 narcotic effects

Specific target organ toxicity, repeated Category 2 (central nervous system,

exposure respiratory system)

OSHA defined hazards Not classified.

Label elements



Signal word Danger

Hazard statement Extremely flammable aerosol. Causes skin irritation. Causes serious eye irritation. Harmful if

inhaled. May cause respiratory irritation. May cause drowsiness or dizziness. May cause cancer. Suspected of damaging the unborn child. May cause damage to organs (central nervous system,

respiratory system) through prolonged or repeated exposure.

Precautionary statement

Prevention Obtain special instructions before use. Do not handle until all safety precautions have been read

and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Do not breathe mist or vapor. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face

protection.

OCAL Spray Patch- Gray SDS US

Response If exposed or concerned: Get medical advice/attention. If inhaled: Remove person to fresh air and

keep comfortable for breathing. Call a poison center/doctor if you feel unwell. If on skin: Wash with plenty of water/. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash before reuse. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get

medical advice/attention.

Storage Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect from

sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise classified (HNOC)

None known.

Supplemental information None.

3. Composition/information on ingredients

Mixtures

Chemical name	CAS number	%	
4-Methylpentan-2-one	108-10-1	30-40	
Toluene	108-88-3	30-40	
Vinyl chloride	75-01-4	5-10	
Carbon black	1333-86-4	1-5	
Titanium Dioxide	13463-67-7	1-5	
Vinyl acetate	108-05-4	1-5	

Composition comments

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

Inhalation

Remove victim to fresh air and keep at rest in a position comfortable for breathing. Oxygen or artificial respiration if needed. Call a POISON CENTER or doctor/physician if you feel unwell.

Skin contact

Take off immediately all contaminated clothing. Wash off with soap and water. Get medical

attention if irritation develops and persists.

Eye contact

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Ingestion In the unlikely event of swallowing contact a physician or poison control center. Rinse mouth.

Most important

symptoms/effects, acute and

delayed

May cause drowsiness and dizziness. Narcosis. Headache. Nausea, vomiting. Behavioral changes. Decrease in motor functions. Skin irritation. May cause redness and pain. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. May cause respiratory irritation. Prolonged exposure may cause chronic effects.

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Keep victim warm. Keep victim under observation. Symptoms may be delayed.

General information

IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance.

5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing

media

Foam. Powder. Carbon dioxide (CO2).

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical

Contents under pressure. Pressurized container may explode when exposed to heat or flame. During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

Fire fighting equipment/instructions

Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.

OCAL Spray Patch- Gray SDS US

Use standard firefighting procedures and consider the hazards of other involved materials. Move

containers from fire area if you can do so without risk.

General fire hazards

Extremely flammable aerosol.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area).

Large Spills: Dike the spilled material, where this is possible. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

For waste disposal, see section 13 of the SDS.

Environmental precautions

Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not breathe mist or vapor. Avoid contact with eyes. Avoid prolonged exposure. Pregnant or breastfeeding women must not handle this product. Should be handled in closed systems, if possible. Use only outdoors or in a well-ventilated area. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Keep away from heat, sparks and open flame. This material can accumulate static charge which may cause spark and become an ignition source. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in original tightly closed container. Store in a well-ventilated place. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Components	Туре	Value		
Vinyl chloride (CAS 75-01-4)	STEL	5 ppm		
·	TWA	1 ppm		
US. OSHA Table Z-1 Limits for Air	Contaminants (29 CFR 1910.	1000)		
Components	Туре	Value	Form	
4-Methylpentan-2-one (CAS	PEL	410 mg/m3		

Components	Туре	Value	Form
4-Methylpentan-2-one (CAS 108-10-1)	PEL	410 mg/m3	
,		100 ppm	
Carbon black (CAS 1333-86-4)	PEL	3.5 mg/m3	
Titanium Dioxide (CAS 13463-67-7)	PEL 4000	15 mg/m3	Total dust.
US. OSHA Table Z-2 (29 CFR 1910	.1000)		

Components	Туре	Value
Toluene (CAS 108-88-3)	Ceiling	300 ppm
	TWA	200 ppm

OCAL Spray Patch- Gray SDS US

US. ACGIH Threshold Limit Values

Components	Туре	Value	Form
4-Methylpentan-2-one (CAS 108-10-1)	STEL	75 ppm	
ŕ	TWA	20 ppm	
Carbon black (CAS 1333-86-4)	TWA	3.5 mg/m3	Inhalable fraction.
Titanium Dioxide (CAS 13463-67-7)	TWA	10 mg/m3	
Toluene (CAS 108-88-3)	TWA	20 ppm	
Vinyl acetate (CAS 108-05-4)	STEL	15 ppm	
,	TWA	10 ppm	
Vinyl chloride (CAS 75-01-4)	TWA	1 ppm	

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Туре	Value	
4-Methylpentan-2-one (CAS 108-10-1)	STEL	300 mg/m3	
·		75 ppm	
	TWA	205 mg/m3	
		50 ppm	
Carbon black (CAS 1333-86-4)	TWA	3.5 mg/m3	
Toluene (CAS 108-88-3)	STEL	560 mg/m3	
		150 ppm	
	TWA	375 mg/m3	
		100 ppm	
Vinyl acetate (CAS 108-05-4)	Ceiling	15 mg/m3	
•		4 ppm	

Biological limit values

ACGIH Biological Exposure Indices

Components	Value	Determinant	Specimen	Sampling Time
4-Methylpentan-2-one (CA 108-10-1)	AS1 mg/l	Methyl isobutyl ketone	Urine	*
Toluene (CAS 108-88-3)	0.3 mg/g	o-Cresol, with hydrolysis	Creatinine in urine	*
	0.03 mg/l	Toluene	Urine	*
	0.02 mg/l	Toluene	Blood	*

^{* -} For sampling details, please see the source document.

Exposure guidelines

US - California OELs: Skin designation

Toluene (CAS 108-88-3)

Vinyl chloride (CAS 75-01-4)

Can be absorbed through the skin.

Can be absorbed through the skin.

US - Minnesota Haz Subs: Skin designation applies

Toluene (CAS 108-88-3) Skin designation applies.

Appropriate engineering controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station.

Individual protection measures, such as personal protective equipment

Eye/face protection Chemical respirator with organic vapor cartridge and full facepiece.

Skin protection

Hand protection Wear appropriate chemical resistant gloves. Suitable gloves can be recommended by the glove

supplier.

OCAL Spray Patch- Gray SDS US

Skin protection

Other Wear suitable protective clothing. Use of an impervious apron is recommended.

Respiratory protection Chemical respirator with organic vapor cartridge and full facepiece.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Observe any medical surveillance requirements. When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Physical state Liquid.
Form Aerosol.
Color Gray.
Odor Solvent.
Odor threshold 86.2

pH Not available.
 Melting point/freezing point Not available.
 Initial boiling point and boiling 57.2 °F (14 °C)

range

Flash point -0.4 °F (-18.0 °C) Evaporation rate 2.1 (BUAC=1)

Flammability (solid, gas) Extremely flammable aerosol.

6

Upper/lower flammability or explosive limits

Flammability limit - lower

(%)

Flammability limit - upper

(%)

Explosive limit - lower (%) Not available.

Explosive limit - upper (%) Not available.

Vapor pressure 1486.4 mm Hg

Vapor density 2.3 Relative density 0.926

Solubility(ies)

Solubility (water) Negligible.

Partition coefficient Not available.

(n-octanol/water)

Auto-ignition temperatureNot available.Decomposition temperatureNot available.Viscosity< 50 SUS</th>

Other information

Explosive properties Not explosive.

Oxidizing properties Not oxidizing.

VOC (Weight %) 4.69 lb/gal

10. Stability and reactivity

ReactivityThe product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoidAvoid temperatures exceeding the flash point. Contact with incompatible materials.

Incompatible materials Strong oxidizing agents. Aluminum. Peroxides.

OCAL Spray Patch- Gray SDS US

Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapors.

11. Toxicological information

Information on likely routes of exposure

Inhalation Harmful if inhaled. May cause damage to organs through prolonged or repeated exposure by

inhalation. May cause drowsiness and dizziness. Headache. Nausea, vomiting.

Skin contact Causes skin irritation.

Eye contact Causes serious eye irritation.

Ingestion Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics

May cause drowsiness and dizziness. Narcosis. Headache. Nausea, vomiting. Behavioral changes. Decrease in motor functions. Skin irritation. May cause redness and pain. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. May

cause respiratory irritation.

Information on toxicological effects

Acute toxicity Harmful if inhaled. Narcotic effects. May cause respiratory irritation.

Components Species Test Results

4-Methylpentan-2-one (CAS 108-10-1)

Acute

Inhalation

LC50 Rat 2000 - 4000 ppm, 4 Hours

Toluene (CAS 108-88-3)

Acute

Dermal

LD50 Rabbit 14.1 ml/kg

Inhalation

LC50 Rat 49000 mg/m³, 4 Hours

Oral

LD50 Rat 5580 mg/kg

Vinyl acetate (CAS 108-05-4)

Acute

Oral

LD50 Rat 2920 mg/kg

Skin corrosion/irritation Causes skin irritation.

Serious eye damage/eye

irritation

Causes serious eye irritation.

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization This product is not expected to cause skin sensitization.

Germ cell mutagenicityNo data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity May cause cancer.

IARC Monographs. Overall Evaluation of Carcinogenicity

4-Methylpentan-2-one (CAS 108-10-1)

Carbon black (CAS 1333-86-4)

Titanium Dioxide (CAS 13463-67-7)

2B Possibly carcinogenic to humans.

2B Possibly carcinogenic to humans.

2B Possibly carcinogenic to humans.

Toluene (CAS 108-88-3) 3 Not classifiable as to carcinogenicity to humans.

Vinyl acetate (CAS 108-05-4) 2B Possibly carcinogenic to humans.

Vinyl chloride (CAS 75-01-4) 1 Carcinogenic to humans.

NTP Report on Carcinogens

Reproductive toxicity

Vinyl chloride (CAS 75-01-4) Known To Be Human Carcinogen.

Suspected of damaging the unborn child.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Vinyl chloride (CAS 75-01-4) Cancer

OCAL Spray Patch- Gray SDS US

Specific target organ toxicity -

single exposure

May cause respiratory irritation. May cause drowsiness and dizziness.

Specific target organ toxicity -

repeated exposure

May cause damage to organs (central nervous system, respiratory system) through prolonged or

repeated exposure.

Aspiration hazard

Not an aspiration hazard.

Chronic effects

May cause damage to organs through prolonged or repeated exposure. Prolonged inhalation may

be harmful. Prolonged exposure may cause chronic effects.

12. Ecological information

Ecotoxicity

The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Species Test Results Components

Toluene (CAS 108-88-3)

Aquatic

Crustacea EC50 Water flea (Daphnia magna) 5.46 - 9.83 mg/l, 48 hours Fish LC50 Pink salmon (Oncorhynchus gorbuscha) 6.86 - 8.48 mg/l, 96 hours

Persistence and degradability

No data is available on the degradability of this product.

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

4-Methylpentan-2-one (CAS 108-10-1) 1.31 Toluene (CAS 108-88-3) 2.73 Vinyl acetate (CAS 108-05-4) 0.73

Mobility in soil No data available.

Other adverse effects The product contains volatile organic compounds which have a photochemical ozone creation

potential.

13. Disposal considerations

Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents **Disposal instructions**

under pressure. Do not puncture, incinerate or crush. Dispose of contents/container in accordance

with local/regional/national/international regulations.

Local disposal regulations

Dispose in accordance with all applicable regulations.

Hazardous waste code

The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal. Do not re-use empty containers.

14. Transport information

DOT

UN1950 **UN** number **UN proper shipping name** Aerosols (No)

Transport hazard class(es)

Class 2 Subsidiary risk Label(s) 2.1

Packing group Not applicable.

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Packaging exceptions 306 Packaging non bulk None Packaging bulk None

IATA

UN1950 **UN** number **UN proper shipping name** Aerosols

Transport hazard class(es) Class

OCAL Spray Patch- Gray

931414 Revision: 2 Revision date: 12-May-2016 Issue date: 08-December-2015

2

Subsidiary risk -Label(s) 2.1

Packing group Not applicable.

Environmental hazards No ERG Code 10L

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

IMDG

UN number UN1950 **UN proper shipping name** AEROSOLS

Transport hazard class(es)

Class 2 Subsidiary risk -Label(s) 2.1

Packing group Not applicable.

Environmental hazards

Marine pollutant No

EmS Not available.

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Transport in bulk according to Annex II of MARPOL 73/78 and

the IBC Code

15. Regulatory information

US federal regulationsThis product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Vinyl chloride (CAS 75-01-4) Cancer

Not established.

Central nervous system

Liver Blood Flammability

CERCLA Hazardous Substance List (40 CFR 302.4)

4-Methylpentan-2-one (CAS 108-10-1) LISTED
Toluene (CAS 108-88-3) LISTED
Vinyl acetate (CAS 108-05-4) LISTED
Vinyl chloride (CAS 75-01-4) LISTED

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - Yes

Delayed Hazard - Yes Fire Hazard - Yes Pressure Hazard - Yes Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Chemical name CAS number Reportable **Threshold** Threshold **Threshold** quantity planning quantity planning quantity, planning quantity, (pounds) (pounds) lower value upper value (pounds) (pounds)

Vinyl acetate 108-05-4 5000 1000

SARA 311/312 Hazardous No

chemical

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.	
4-Methylpentan-2-one	108-10-1	30-40	
Toluene	108-88-3	30-40	
Vinyl chloride	75-01-4	5-10	
Vinyl acetate	108-05-4	1-5	

OCAL Spray Patch- Gray SDS US

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

4-Methylpentan-2-one (CAS 108-10-1)

Toluene (CAS 108-88-3)

Vinyl acetate (CAS 108-05-4)

Vinyl chloride (CAS 75-01-4)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Vinyl acetate (CAS 108-05-4) Vinyl chloride (CAS 75-01-4)

Safe Drinking Water Act

Not regulated.

(SDWA)

Drug Enforcement Administration (DEA). List 2, Essential Chemicals (21 CFR 1310.02(b) and 1310.04(f)(2) and Chemical Code Number

4-Methylpentan-2-one (CAS 108-10-1) 6715 Toluene (CAS 108-88-3) 6594

Drug Enforcement Administration (DEA). List 1 & 2 Exempt Chemical Mixtures (21 CFR 1310.12(c))

4-Methylpentan-2-one (CAS 108-10-1) 35 %WV Toluene (CAS 108-88-3) 35 %WV

DEA Exempt Chemical Mixtures Code Number

4-Methylpentan-2-one (CAS 108-10-1) 6715 Toluene (CAS 108-88-3) 594

US state regulations

US. Massachusetts RTK - Substance List

4-Methylpentan-2-one (CAS 108-10-1)

Carbon black (CAS 1333-86-4)

Titanium Dioxide (CAS 13463-67-7)

Toluene (CAS 108-88-3)

Vinyl acetate (CAS 108-05-4)

Vinyl chloride (CAS 75-01-4)

US. New Jersey Worker and Community Right-to-Know Act

4-Methylpentan-2-one (CAS 108-10-1)

Carbon black (CAS 1333-86-4)

Titanium Dioxide (CAS 13463-67-7)

Toluene (CAS 108-88-3)

Vinyl acetate (CAS 108-05-4)

Vinyl chloride (CAS 75-01-4)

US. Pennsylvania Worker and Community Right-to-Know Law

4-Methylpentan-2-one (CAS 108-10-1)

Carbon black (CAS 1333-86-4)

Titanium Dioxide (CAS 13463-67-7)

Toluene (CAS 108-88-3)

Vinyl acetate (CAS 108-05-4)

Vinyl chloride (CAS 75-01-4)

US. Rhode Island RTK

4-Methylpentan-2-one (CAS 108-10-1)

Toluene (CAS 108-88-3)

Vinyl acetate (CAS 108-05-4)

Vinyl chloride (CAS 75-01-4)

US. California Proposition 65

WARNING: This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm.

US - California Proposition 65 - Carcinogens & Reproductive Toxicity (CRT): Listed substance

4-Methylpentan-2-one (CAS 108-10-1)

Carbon black (CAS 1333-86-4)

Titanium Dioxide (CAS 13463-67-7)

Toluene (CAS 108-88-3)

Vinyl chloride (CAS 75-01-4)

International Inventories

Country(s) or regionInventory nameOn inventory (yes/no)*AustraliaAustralian Inventory of Chemical Substances (AICS)Yes

OCAL Spray Patch- Gray SDS US
931414 Revision: 2 Revision date: 12-May-2016 Issue date: 08-December-2015 9 / 10

Canada Non-Domestic Substances List (NDSL) No China Inventory of Existing Chemical Substances in China (IECSC) Yes Europe European Inventory of Existing Commercial Chemical Yes Substances (EINECS) Europe European List of Notified Chemical Substances (ELINCS) No Inventory of Existing and New Chemical Substances (ENCS) Japan Yes Korea Existing Chemicals List (ECL) Yes New Zealand New Zealand Inventory Yes **Philippines** Philippine Inventory of Chemicals and Chemical Substances Yes

(PICCS)

United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory

Inventory name

Domestic Substances List (DSL)

Yes

On inventory (yes/no)*

16. Other information, including date of preparation or last revision

08-December-2015 Issue date **Revision date** 12-May-2016

Revision # 2

Country(s) or region

Canada

Health: 2* **HMIS®** ratings

Flammability: 4 Physical hazard: 0

NFPA ratings



Disclaimer

Thomas & Betts Corporation cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available.

OCAL Spray Patch- Gray SDS US

^{*}A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s). A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).