## 1 Identification of the substance and manufacturer Trade name: SAFETY RED Product code: 0000200671 Recommended use: Paint and coatings application. Uses advised against: Any that differs from the recommended use. Manufacturer/Supplier: Seymour of Sycamore Seymour of Sycamore 3041 Dougall Avenue, Suite 503 Windsor, ONT N9E 1S3 CANADA phone: 800-435-4482 917 Crosby Avenue Sycamore, IL 60178 USA phone: 815-895-9101 www.seymourpaint.com www.seymourpaint.com 1-800-255-3924 Emergency telephone number: 2 Hazard(s) identification Classification of the substance or mixture Flam. Aerosol 1 H222 Extremely flammable aerosol. Press. Gas H280 Contains gas under pressure; may explode if heated. STOT SE 3 H335 May cause respiratory irritation. STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure. **GHS Hazard pictograms** GHS02 GHS04 GHS07 GHS08 Danger Signal word Hazard statements Extremely flammable aerosol. Contains gas under pressure; may explode if heated. May cause respiratory irritation. May cause damage to organs through prolonged or repeated exposure. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. **Precautionary statements** Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Do not breathe dust/fume/gas/mist/vapors/spray. Use only outdoors or in a well-ventilated area. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you feel unwell. Store in a well-ventilated place. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Dispose of contents/container in accordance with local/regional/national/international regulations. **3 Composition/information on ingredients**

## Chemical characterization: Mixtures

Chemical D	escription:	This product is a mixture of the substances listed below with nonhazardous additions.	
	components:		
64742-89-8	VM&P Naphtha		15-25%
	propane		15-25%
1317-65-3	Calcium Carbonate		10-15%
106-97-8	n-butane		5-10%
64742-47-8	Mineral Spirits		1-5%

After inhalation:Supply fresh air; consult doctor in case of complaints.After skin contact:Remove contaminated clothing. Wash exposed area with soap and water.After eye contact:Rinse opened eye for several minutes under running water. Then consult a doctor.After swallowing:Rinse out mouth and then drink plenty of water.Most important symptoms and effects:DizzinessIndication of any immediate medical attention needed:DizzinessNo further relevant information available.5 Fire-fighting measuresCO2, extinguishing powder or water spray. Fight larger fires with water spray.Special hazards: Protective equipment for firefighters:CO2, extinguishing powder or water spray.A respiratory protective device may be necessary.A respiratory protective device may be necessary.	4 First-aid measures	
attention needed:       No further relevant information available.         5 Fire-fighting measures       Extinguishing agents:         Special hazards:       CO2, extinguishing powder or water spray. Fight larger fires with water spray. Can form explosive gas-air mixtures.         Protective equipment for       CO2, extinguishing powder or water spray. Fight larger fires with water spray.	After skin contact: After eye contact: After swallowing: Most important symptoms and effects:	Remove contaminated clothing. Wash exposed area with soap and water. Rinse opened eye for several minutes under running water. Then consult a doctor. Rinse out mouth and then drink plenty of water. Rinse mouth with water. Do not induce vomiting. Dizziness
Extinguishing agents:       CO2, extinguishing powder or water spray. Fight larger fires with water spray.         Special hazards:       Can form explosive gas-air mixtures.         Protective equipment for       Can form explosive gas-air mixtures.	attention needed:	No further relevant information available.
Extinguishing agents:       CO2, extinguishing powder or water spray. Fight larger fires with water spray.         Special hazards:       Can form explosive gas-air mixtures.         Protective equipment for       Can form explosive gas-air mixtures.		
Special hazards: Can form explosive gas-air mixtures.	5 Fire-fighting measures	
	Special hazards:	CO2, extinguishing powder or water spray. Fight larger fires with water spray. Can form explosive gas-air mixtures.
		A respiratory protective device may be necessary.

Revised On 01/06/2020

	(Contd. of page
Accidental release measures	
Personal precautions, protective	
equipment and emergency	
procedures:	Wear protective equipment. Keep unprotected persons away. Use respiratory protective device against the effects of fumes/dust/aerosol.
Methods and material for	
containment and cleaning up:	Ensure adequate ventilation.
Handling and storage Precautions for safe handling	Use only in well ventilated areas.
Storage requirements:	Keep away from sources of heat and direct sunlight. Do not warehouse in subfreezing condition Store locked up.
Exposure controls/personal pro	otection
Components with limit values that	require monitoring at the workplace:
74-98-6 propane	
PEL (USA) Long-term value: 1800 n	
REL (USA) Long-term value: 1800 n	
TLV (USA) refer to Appendix F inTL 106-97-8 n-butane	
REL (USA) Long-term value: 1900 n	ng/m³, 800 ppm
TLV (USA) Short-term value: 2370 r	
(EX)	
Hygienic protection:	Keep away from foodstuffs and animal feed. Wash hands after use. Wash hands after use.
	Do not eat or drink while working.
Breathing equipment:	A respirator is generally not necessary when using this product outdoors or in large open areas.
	cases where short and/or long term overexposure exists, a charcoal filter respirator should be wor If you suspect overexposure conditions exist, please consult an authority on chemical hygeine.
Hand protection:	Nitrile gloves.
-	The glove material must be impermeable and resistant to the substance.
Eye protection:	Tightly sealed goggles
Physical and chemical properti	
Appearance:	Aerosol.
Odor:	Aromatic
Odor threshold:	Not determined.
pH-value:	Not determined. Undetermined.
Melting point/Melting range Boiling point:	-44 °C (-111.2 °F)
Flash point:	-19 °C (-66.2 °F)
Flammability (solid, gas):	Extremely flammable.
Decomposition temperature:	Not determined.
Auto igniting:	Product is not self-igniting.
Danger of explosion:	In use, may form flammable/explosive vapour-air mixture.
Lower Explosion Limit:	1.7 Vol %
Upper Explosion Limit:	10.9 Vol %
Vapor pressure:	Not determined.
Relative Density: Vapor density	Between 0.77 and 0.85 (Water equals 1.00) Not determined.
Evaporation rate	Not applicable.
Partition coefficient: n-octonal/wat	er: Not determined.
Solubility:	Not determined.
Viscosity: VOC content (less exempt solvents	Not determined.
Water:	33.5 %
Stability and reactivity	
Reactivity:	Stable at normal temperatures.
Conditions to avoid:	Do not allow can to exceed 120 degrees Fahrenheit. Do not warehouse in subfreezir temperatures.
Chemical stability:	Not fully evaluated.
Possibility of hazardous reactions	No dangerous reactions known.
Incompatible materials:	No further relevant information available. (Contd. on page

Safety Data Sheet

Printing date 01/10/2020 Trade name: SAFETY RED Hazardous decomposition:  11 Toxicological information LD/LC50 values that are relevant for 106-97-8 n-butane Inhalative LC50/4 h 658 mg/l (rat) Information on toxicological effect Skin effects: Eye effects: Eye effects: Sensitization:	
Hazardous decomposition: 11 Toxicological information LD/LC50 values that are relevant for 106-97-8 n-butane Inhalative LC50/4 h 658 mg/l (rat) Information on toxicological effect Skin effects: Eye effects:	No dangerous decomposition products known.
11 Toxicological information         LD/LC50 values that are relevant for         106-97-8 n-butane         Inhalative       LC50/4 h         658 mg/l (rat)         Information on toxicological effect         Skin effects:         Eye effects:	No dangerous decomposition products known.
11 Toxicological information         LD/LC50 values that are relevant for         106-97-8 n-butane         Inhalative       LC50/4 h         658 mg/l (rat)         Information on toxicological effect         Skin effects:         Eye effects:	No dangerous decomposition products known.
11 Toxicological information         LD/LC50 values that are relevant for         106-97-8 n-butane         Inhalative       LC50/4 h         658 mg/l (rat)         Information on toxicological effect         Skin effects:         Eye effects:	or classification: s: No data available.
LD/LC50 values that are relevant for 106-97-8 n-butane Inhalative LC50/4 h 658 mg/l (rat) Information on toxicological effect Skin effects: Eve effects:	s: No data available.
LD/LC50 values that are relevant for 106-97-8 n-butane Inhalative LC50/4 h 658 mg/l (rat) Information on toxicological effect Skin effects: Eve effects:	s: No data available.
106-97-8 n-butane Inhalative LC50/4 h 658 mg/l (rat) Information on toxicological effect Skin effects: Eye effects:	s: No data available.
Inhalative LC50/4 h 658 mg/l (rat) Information on toxicological effect Skin effects: Eye effects:	s: No data available.
Information on toxicological effect Skin effects: Eve effects:	s: No data available.
Skin effects: Eve effects:	No lata available.
Eve effects:	
Sensitization:	No irritating effect.
	No sensitizing effects known.
12 Ecological information	
Aquatic toxicity:	Hazardous for water, do not empty into drains.
Persistence and degradability: Other information:	The product is degradable after prolonged exposure to natural weathering processes. This product does not contain any chlorofluorocarbons (CFC's), hydrochlorofluorocarbons
Other Information.	(HCFC's), perfluorocarbons (PFC's), heavy metals (chromium, lead, cadmium), or chlorinated
	solvents.
Bioaccumulative potential:	No further relevant information available.
Mobility in soil: Other adverse effects:	No further relevant information available. No further relevant information available.
13 Disposal considerations	
	state, and federal regulations. Do not puncture, incinerate, or compact. Partially empty cans must be
disposed of responsibly. Do not heat	or cut empty containers with electric or gas torches.
Recommendation:	Completely empty cans should be recycled.
14 Transport information	
UN-Number	UN1950
DOT	N/A
DOT	UN1950 Consumer Commodity ORM-D
201	Aerosols, flammable
ADR	1950 Aerosols
Transport hazard class(es): Class	2.1
Marine pollutant:	No
Special precautions for user:	Warning: Gases
EMS Number:	F-D,S-U
Packaging Group: UN "Model Regulation":	 UN1950, Aerosols, 2.1
15 Regulatory information	
SARA Section 355 (extremely haza	rdous substances):
None of the ingredients in this produce	
SARA Section 313 (Specific toxic of	
None of the ingredients is listed.	nemicai nətiliyə).
Toxic Substances Control Act	
(TSCA):	All hazardous ingredients are found on the inventory list of substances.
Canadían Domestic Substances Lis	st
(DSL): Consumer Broduct Sofety	All ingredients are listed or exempted.
Consumer Product Safety Comission (CPSC):	This product complies with 16 CFR 1303 and does not contain more than 90 ppm of lead.
California Proposition 65 chemical	
100-41-4 ethyl benzene	
-	birth defects or reproductive harm:
None of the ingredients is listed.	
EPA:	
None of the ingredients is listed.	
16 Other information	
Contact:	Regulatory Affairs