



Safety Data Sheet

Copyright,2020, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document Group:	32-6230-0	Version Number:	3.00
Issue Date:	28/11/2020	Supersedes Date:	07/04/2020

This Safety Data Sheet has been prepared in accordance with the Malaysia Occupational Safety and Health (Chemical Classification, Labelling and Safety Data Sheets) Regulations 2013.

SECTION 1: Identification

1.1. Product identifier

3M™ Perfect-It™ Rubbing Compound PN 06085, 06086, 06087, 39060, 6070

Product Identification Numbers

60-4550-7365-4 60-4551-0167-9 UU-0036-5276-3

1.2. Recommended use and restrictions on use

Recommended use

Automotive

1.3. Supplier's details

ADDRESS: 3M Malaysia Sdn. Bhd., Level 8, Block F, Oasis Square, No.2, Jalan PJU 1A/7A, Ara Damansara 47301
Petaling, Jaya, Selangor
Telephone: 03-7884 2888
E Mail: 3mmyehsr@mmm.com
Website: www.3M.com.my

1.4. Emergency telephone number

+60 03-7884 2888

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

Chronic Aquatic Toxicity: Category 3.

2.2. Label elements

Signal word

Not applicable.

Symbols

Not applicable.

Pictograms

Not applicable

3M™ Perfect-It™ Rubbing Compound PN 06085, 06086, 06087, 39060, 6070**Hazard Statements**

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements**Prevention:**

P280E Wear protective gloves.

Disposal:

P501 Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

2.3. Other hazards

Repeated exposure may cause skin dryness or cracking.

SECTION 3: Composition/information on ingredients

This material is a mixture.

Ingredient	C.A.S. No.	% by Wt
Water	7732-18-5	40 - 70
HYDRODESULFURIZED KEROSENE (PETROLEUM)	64742-81-0	10 - 30
Aluminum Oxide (non-fibrous)	1344-28-1	< 16
Castor oil	8001-79-4	1 - 5
Ethylbenzene	100-41-4	< 0.5
Naphthalene	91-20-3	< 0.5

Any remaining components do not contribute to the hazards of this material.

SECTION 4: First aid measures**4.1. Description of first aid measures****Inhalation:**

Remove person to fresh air. If you feel unwell, get medical attention.

Skin Contact:

Wash with soap and water. If signs/symptoms develop, get medical attention.

Eye Contact:

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1. Information on toxicological effects.

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

Material will not burn.

5.2. Special hazards arising from the substance or mixture

None inherent in this product.

Hazardous Decomposition or By-Products

Substance

Carbon monoxide
Carbon dioxide
Oxides of Nitrogen

Condition

During Combustion
During Combustion
During Combustion

5.3. Special protective actions for fire-fighters

No special protective actions for fire-fighters are anticipated.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water.

6.3. Methods and material for containment and cleaning up

Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with detergent and water. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Keep out of reach of children. Do not handle until all safety precautions have been read and understood. Avoid breathing dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid release to the environment. Use personal protective equipment (gloves, respirators, etc.) as required.

7.2. Conditions for safe storage including any incompatibilities

Store away from areas where product may come into contact with food or pharmaceuticals.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments
------------	------------	--------	------------	---------------------

3M™ Perfect-It™ Rubbing Compound PN 06085, 06086, 06087, 39060, 6070

Ethylbenzene	100-41-4	ACGIH	TWA:20 ppm	A3: Confirmed animal carcin.
Ethylbenzene	100-41-4	Malaysia OELs	TWA(8 hours):434 mg/m ³ (100 ppm)	
Aluminum Oxide (non-fibrous)	1344-28-1	Malaysia OELs	TWA (proposed)(8 hours):10 mg/m ³	
Aluminum, insoluble compounds	1344-28-1	ACGIH	TWA(respirable fraction):1 mg/m ³	A4: Not class. as human carcin
HYDRODESULFURIZED KEROSENE (PETROLEUM)	64742-81-0	ACGIH	TWA(as total hydrocarbon vapor, non-aerosol):200 mg/m ³	A3: Confirmed animal carcin., SKIN
Naphthalene	91-20-3	ACGIH	TWA:10 ppm	A3: Confirmed animal carcin., Danger of cutaneous absorption
Naphthalene	91-20-3	Malaysia OELs	TWA(8 hours):52 mg/m ³ (10 ppm)	

ACGIH : American Conference of Governmental Industrial Hygienists

CMRG : Chemical Manufacturer's Recommended Guidelines

Malaysia OELs : Malaysia. Occupational Safety and Health (Use and Standards of Exposure of Chemicals Hazardous to Health) Regulations

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Safety Glasses with side shields

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity.

Gloves made from the following material(s) are recommended: Polymer laminate

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece air-purifying respirator suitable for organic vapors and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Liquid
Color	Off-White
Odor	Solvent
Odor threshold	No Data Available
pH	7.5 - 8.5
Melting point/Freezing point	No Data Available
Boiling point/Initial boiling point/Boiling range	100 °C
Flash Point	No flash point
Evaporation rate	No Data Available
Flammability (solid, gas)	Not Applicable
Flammable Limits(LEL)	No Data Available
Flammable Limits(UEL)	No Data Available
Vapor Pressure	2,399.8 Pa [@ 20 °C]
Vapor Density and/or Relative Vapor Density	No Data Available
Density	1.06 - 1.08 g/ml
Relative Density	1.06 - 1.08 [Ref Std: WATER=1]
Water solubility	Moderate
Solubility- non-water	No Data Available
Partition coefficient: n-octanol/ water	No Data Available
Autoignition temperature	No Data Available
Decomposition temperature	No Data Available
Viscosity/Kinematic Viscosity	30,000 - 38,000 mPa-s [@ 25 °C] [Details:#6 Spindle]
Volatile Organic Compounds	16 % weight [Test Method:calculated per CARB title 2]
Volatile Organic Compounds	172 g/l [Test Method:calculated SCAQMD rule 443.1]
Percent volatile	79.7 % weight
VOC Less H2O & Exempt Solvents	540 g/l [Test Method:calculated SCAQMD rule 443.1]

Nanoparticles

This material does not contain nanoparticles.

SECTION 10: Stability and reactivity

10.1. Reactivity

This material is considered to be non reactive under normal use conditions.

10.2. Chemical stability

Stable.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

None known.

10.5. Incompatible materials

None known.

10.6. Hazardous decomposition products

SubstanceCondition

None known.

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

May cause additional health effects (see below).

Skin Contact:

Dermal Defatting: Signs/symptoms may include localized redness, itching, drying and cracking of skin. May cause additional health effects (see below).

Eye Contact:

Dust created by cutting, grinding, sanding, or machining may cause eye irritation. Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.

Ingestion:

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

May cause additional health effects (see below).

Additional Health Effects:

Carcinogenicity:

Contains a chemical or chemicals which can cause cancer.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Inhalation-Vapor(4 hr)		No data available; calculated ATE >50 mg/l
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
HYDRODESULFURIZED Kerosine (Petroleum)	Dermal	Rabbit	LD50 > 2,000 mg/kg
HYDRODESULFURIZED Kerosine (Petroleum)	Inhalation-Vapor (4 hours)	Rat	LC50 > 5 mg/l
HYDRODESULFURIZED Kerosine (Petroleum)	Ingestion	Rat	LD50 > 5,000 mg/kg
Aluminum Oxide (non-fibrous)	Dermal		LD50 estimated to be > 5,000 mg/kg
Aluminum Oxide (non-fibrous)	Inhalation-Dust/Mist	Rat	LC50 > 2.3 mg/l

3M™ Perfect-It™ Rubbing Compound PN 06085, 06086, 06087, 39060, 6070

	(4 hours)		
Aluminum Oxide (non-fibrous)	Ingestion	Rat	LD50 > 5,000 mg/kg
Castor oil	Dermal		LD50 estimated to be > 5,000
Castor oil	Ingestion		LD50 estimated to be > 5,000
Ethylbenzene	Dermal	Rabbit	LD50 15,433 mg/kg
Ethylbenzene	Inhalation-Vapor (4 hours)	Rat	LC50 17.4 mg/l
Ethylbenzene	Ingestion	Rat	LD50 4,769 mg/kg
Naphthalene	Dermal	Human	LD50 estimated to be 2,000 - 5,000 mg/kg
Naphthalene	Inhalation-Vapor	Human	LC50 estimated to be 20 - 50 mg/l
Naphthalene	Ingestion	Human	LD50 estimated to be 300 - 2,000 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
HYDRODESULFURIZED Kerosine (PETROLEUM)	Rabbit	Minimal irritation
Aluminum Oxide (non-fibrous)	Rabbit	No significant irritation
Castor oil	Human	Minimal irritation
Ethylbenzene	Rabbit	Mild irritant
Naphthalene	Rabbit	Minimal irritation

Serious Eye Damage/Irritation

Name	Species	Value
HYDRODESULFURIZED Kerosine (PETROLEUM)	Rabbit	No significant irritation
Aluminum Oxide (non-fibrous)	Rabbit	No significant irritation
Castor oil	Rabbit	Mild irritant
Ethylbenzene	Rabbit	Moderate irritant
Naphthalene	Rabbit	No significant irritation

Sensitization:

Skin Sensitization

Name	Species	Value
HYDRODESULFURIZED Kerosine (PETROLEUM)	Guinea pig	Not classified
Castor oil	Human	Not classified
Ethylbenzene	Human	Not classified

Respiratory Sensitization

For the component/components, either no data are currently available or the data are not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value
HYDRODESULFURIZED Kerosine (PETROLEUM)	In Vitro	Some positive data exist, but the data are not sufficient for classification
HYDRODESULFURIZED Kerosine (PETROLEUM)	In vivo	Some positive data exist, but the data are not sufficient for classification
Aluminum Oxide (non-fibrous)	In Vitro	Not mutagenic
Castor oil	In Vitro	Not mutagenic
Castor oil	In vivo	Not mutagenic
Ethylbenzene	In vivo	Not mutagenic
Ethylbenzene	In Vitro	Some positive data exist, but the data are not sufficient for classification

Carcinogenicity

3M™ Perfect-It™ Rubbing Compound PN 06085, 06086, 06087, 39060, 6070

Name	Route	Species	Value
HYDRODESULFURIZED Kerosine (Petroleum)	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification
Aluminum Oxide (non-fibrous)	Inhalation	Rat	Not carcinogenic
Ethylbenzene	Inhalation	Multiple animal species	Carcinogenic
Naphthalene	Inhalation	Multiple animal species	Carcinogenic

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test Result	Exposure Duration
HYDRODESULFURIZED Kerosine (Petroleum)	Dermal	Not classified for female reproduction	Rat	NOAEL 494 mg/kg/day	prematuring & during gestation
HYDRODESULFURIZED Kerosine (Petroleum)	Dermal	Not classified for male reproduction	Rat	NOAEL 494 mg/kg/day	prematuring & during gestation
HYDRODESULFURIZED Kerosine (Petroleum)	Dermal	Not classified for development	Rat	NOAEL 494 mg/kg/day	prematuring & during gestation
HYDRODESULFURIZED Kerosine (Petroleum)	Inhalation	Not classified for development	Rat	NOAEL 400 ppm	during organogenesis
Ethylbenzene	Inhalation	Not classified for development	Rat	NOAEL 4.3 mg/l	prematuring & during gestation

Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
HYDRODESULFURIZED Kerosine (Petroleum)	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL not available	occupational exposure
HYDRODESULFURIZED Kerosine (Petroleum)	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Multiple animal species	NOAEL not available	not available
HYDRODESULFURIZED Kerosine (Petroleum)	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL not available	poisoning and/or abuse
HYDRODESULFURIZED Kerosine (Petroleum)	Ingestion	kidney and/or bladder	Not classified	Rat	NOAEL not available	not applicable
HYDRODESULFURIZED Kerosine (Petroleum)	Ingestion	liver	Not classified	Rat	LOAEL 18,912 mg/kg	not applicable
HYDRODESULFURIZED Kerosine (Petroleum)	Ingestion	heart hematopoietic system	Not classified	Human	NOAEL not available	poisoning and/or abuse
Ethylbenzene	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
Ethylbenzene	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human and animal	NOAEL Not available	
Ethylbenzene	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Professional judgment	NOAEL Not available	
Naphthalene	Ingestion	blood	Causes damage to organs	Human	NOAEL Not available	poisoning and/or abuse

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
HYDRODESULFURIZED KEROSENE (PETROLEUM)	Dermal	hematopoietic system	Not classified	Mouse	NOAEL 500 mg/kg/day	13 weeks
HYDRODESULFURIZED KEROSENE (PETROLEUM)	Dermal	liver immune system kidney and/or bladder	Not classified	Mouse	NOAEL 500 mg/kg/day	2 years
HYDRODESULFURIZED KEROSENE (PETROLEUM)	Dermal	nervous system	Not classified	Mouse	NOAEL 2,700 mg/kg/day	1 weeks
HYDRODESULFURIZED KEROSENE (PETROLEUM)	Dermal	heart gastrointestinal tract muscles respiratory system	Not classified	Mouse	NOAEL 500 mg/kg/day	2 years
HYDRODESULFURIZED KEROSENE (PETROLEUM)	Inhalation	kidney and/or bladder	Not classified	Rat	NOAEL not available	1 years
HYDRODESULFURIZED KEROSENE (PETROLEUM)	Inhalation	liver	Not classified	Rat	NOAEL 0.231 mg/l	14 weeks
HYDRODESULFURIZED KEROSENE (PETROLEUM)	Inhalation	heart	Not classified	Guinea pig	LOAEL 20.4 mg/l	not available
HYDRODESULFURIZED KEROSENE (PETROLEUM)	Inhalation	gastrointestinal tract hematopoietic system muscles respiratory system	Not classified	Multiple animal species	NOAEL 0.1 mg/l	13 weeks
Aluminum Oxide (non-fibrous)	Inhalation	pneumoconiosis	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	occupational exposure
Aluminum Oxide (non-fibrous)	Inhalation	pulmonary fibrosis	Not classified	Human	NOAEL Not available	occupational exposure
Castor oil	Ingestion	heart hematopoietic system liver	Not classified	Rat	NOAEL 4,800 mg/kg/day	13 weeks
Castor oil	Ingestion	kidney and/or bladder	Not classified	Mouse	NOAEL 13,000 mg/kg/day	13 weeks
Ethylbenzene	Inhalation	kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 1.1 mg/l	2 years
Ethylbenzene	Inhalation	liver	Some positive data exist, but the data are not sufficient for classification	Mouse	NOAEL 1.1 mg/l	103 weeks
Ethylbenzene	Inhalation	hematopoietic system	Not classified	Rat	NOAEL 3.4 mg/l	28 days
Ethylbenzene	Inhalation	auditory system	Not classified	Rat	NOAEL 2.4 mg/l	5 days
Ethylbenzene	Inhalation	endocrine system	Not classified	Mouse	NOAEL 3.3 mg/l	103 weeks
Ethylbenzene	Inhalation	gastrointestinal tract	Not classified	Rat	NOAEL 3.3 mg/l	2 years
Ethylbenzene	Inhalation	bone, teeth, nails, and/or hair muscles	Not classified	Multiple animal species	NOAEL 4.2 mg/l	90 days
Ethylbenzene	Inhalation	heart immune system respiratory system	Not classified	Multiple animal species	NOAEL 3.3 mg/l	2 years
Ethylbenzene	Ingestion	liver kidney and/or bladder	Not classified	Rat	NOAEL 680 mg/kg/day	6 months
Naphthalene	Dermal	blood	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL Not available	poisoning and/or abuse
Naphthalene	Dermal	eyes	Not classified	Human	NOAEL Not available	occupational exposure
Naphthalene	Inhalation	respiratory system	Causes damage to organs through prolonged or repeated exposure	Rat	LOAEL 0.01 mg/l	13 weeks

3M™ Perfect-It™ Rubbing Compound PN 06085, 06086, 06087, 39060, 6070

Naphthalene	Inhalation	blood	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL Not available	poisoning and/or abuse
Naphthalene	Inhalation	eyes	Not classified	Human	NOAEL Not available	occupational exposure
Naphthalene	Ingestion	blood	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL Not available	poisoning and/or abuse
Naphthalene	Ingestion	eyes	May cause damage to organs though prolonged or repeated exposure	Rabbit	LOAEL 500 mg/kg/day	15 days

Aspiration Hazard

Name	Value
HYDRODESULFURIZED Kerosine (PETROLEUM)	Aspiration hazard
Ethylbenzene	Aspiration hazard

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. Additional information leading to material classification in Section 2 is available upon request. In addition, environmental fate and effects data on ingredients may not be reflected in this section because an ingredient is present below the threshold for labeling, an ingredient is not expected to be available for exposure, or the data is considered not relevant to the material as a whole.

12.1. Toxicity

Acute aquatic hazard:

GHS Acute 3: Harmful to aquatic life.

Chronic aquatic hazard:

GHS Chronic 3: Harmful to aquatic life with long lasting effects

No product test data available

Material	Cas #	Organism	Type	Exposure	Test Endpoint	Test Result
HYDRODESULFURIZED Kerosine (PETROLEUM)	64742-81-0	Green Algae	Estimated	72 hours	Effect Level 50%	>1 mg/l
HYDRODESULFURIZED Kerosine (PETROLEUM)	64742-81-0	Rainbow Trout	Estimated	96 hours	Lethal Level 50%	>2 mg/l
HYDRODESULFURIZED Kerosine (PETROLEUM)	64742-81-0	Water flea	Experimental	48 hours	Effect Level 50%	1.4 mg/l
HYDRODESULFURIZED Kerosine (PETROLEUM)	64742-81-0	Green Algae	Estimated	72 hours	No obs Effect Level	1 mg/l

3M™ Perfect-It™ Rubbing Compound PN 06085, 06086, 06087, 39060, 6070

HYDRODESULFURIZED KEROSENE (PETROLEUM)	64742-81-0	Water flea	Experimental	21 days	No obs Effect Level	0.48 mg/l
Aluminum Oxide (non-fibrous)	1344-28-1		Experimental	96 hours	Lethal Concentration 50%	>100 mg/l
Aluminum Oxide (non-fibrous)	1344-28-1	Green algae	Experimental	72 hours	Effect Concentration 50%	>100 mg/l
Aluminum Oxide (non-fibrous)	1344-28-1	Water flea	Experimental	48 hours	Lethal Concentration 50%	>100 mg/l
Aluminum Oxide (non-fibrous)	1344-28-1	Green algae	Experimental	72 hours	No obs Effect Conc	>100 mg/l
Castor oil	8001-79-4	Zebra Fish	Estimated	96 hours	Lethal Concentration 50%	>100 mg/l
Ethylbenzene	100-41-4	Atlantic Silverside	Experimental	96 hours	Lethal Concentration 50%	5.1 mg/l
Ethylbenzene	100-41-4	Green Algae	Experimental	96 hours	Effect Concentration 50%	3.6 mg/l
Ethylbenzene	100-41-4	Mysid Shrimp	Experimental	96 hours	Lethal Concentration 50%	2.6 mg/l
Ethylbenzene	100-41-4	Rainbow Trout	Experimental	96 hours	Lethal Concentration 50%	4.2 mg/l
Ethylbenzene	100-41-4	Water flea	Experimental	48 hours	Effect Concentration 50%	1.8 mg/l
Ethylbenzene	100-41-4	Water flea	Experimental	7 days	No obs Effect Conc	0.96 mg/l
Naphthalene	91-20-3	Diatom	Experimental	72 hours	Effect Concentration 50%	0.4 mg/l
Naphthalene	91-20-3	Rainbow Trout	Experimental	96 hours	Lethal Concentration 50%	0.11 mg/l
Naphthalene	91-20-3	Water flea	Experimental	48 hours	Effect Concentration 50%	1.6 mg/l
Naphthalene	91-20-3	Fish other	Experimental	40 days	No obs Effect Conc	0.12 mg/l

12.2. Persistence and degradability

Material	CAS No.	Test Type	Duration	Study Type	Test Result	Protocol
HYDRODESULFURIZED KEROSENE	64742-81-0	Data not availbl-insufficient			N/A	

3M™ Perfect-It™ Rubbing Compound PN 06085, 06086, 06087, 39060, 6070

(PETROLEUM)						
Aluminum Oxide (non-fibrous)	1344-28-1	Data not available - insufficient			N/A	
Castor oil	8001-79-4	Estimated Biodegradation	28 days	Biological Oxygen Demand	64 % weight	OECD 301D - Closed Bottle Test
Ethylbenzene	100-41-4	Experimental Photolysis		Photolytic half-life (in air)	4.26 days (t _{1/2})	Other methods
Ethylbenzene	100-41-4	Experimental Biodegradation	28 days	Carbon dioxide evolution	70-80 % weight	Other methods
Naphthalene	91-20-3	Experimental Biodegradation	28 days	Biological Oxygen Demand	>74 % BOD/ThBOD	OECD 301C - MITI (I)

12.3. Bioaccumulative potential

Material	CAS No.	Test Type	Duration	Study Type	Test Result	Protocol
HYDRODESULFURIZED KEROSENE (PETROLEUM)	64742-81-0	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Aluminum Oxide (non-fibrous)	1344-28-1	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Castor oil	8001-79-4	Estimated Bioconcentration		Bioaccumulation Factor	7.4	Est: Bioconcentration factor
Ethylbenzene	100-41-4	Experimental BCF - Other	42 days	Bioaccumulation Factor	1	Other methods
Naphthalene	91-20-3	Experimental BCF-Carp	56 days	Bioaccumulation Factor	36.5-168	OECD 305E-Bioaccumulation - Fish

12.4. Mobility in soil

Please contact manufacturer for more details

12.5 Other adverse effects

No information available

SECTION 13: Disposal considerations

13.1. Disposal methods

According to the Environmental Quality (Scheduled Wastes) Regulations 2005, scheduled waste has to be sent to a prescribed premise for recycling, treatment or disposal. Please approach Kualiti Alam for proper schedule waste classification and disposal.

SECTION 14: Transport Information

Not hazardous for transportation.

Marine Transport (IMDG)

UN Number:None assigned.
Proper Shipping Name:None assigned.
Technical Name:None assigned.
Hazard Class/Division:None assigned.
Subsidiary Risk:None assigned.
Packing Group:None assigned.
Limited Quantity:None assigned.
Marine Pollutant: None assigned.
Marine Pollutant Technical Name: None assigned.
Other Dangerous Goods Descriptions:
None assigned.

Air Transport (IATA)

UN Number:None assigned.
Proper Shipping Name:None assigned.
Technical Name:None assigned.
Hazard Class/Division:None assigned.
Subsidiary Risk:None assigned.
Packing Group:None assigned.
Limited Quantity:None assigned.
Marine Pollutant: None assigned.
Marine Pollutant Technical Name: None assigned.
Other Dangerous Goods Descriptions:
None assigned.

Transportation classifications are provided as a customer service. As for shipping, YOU remain responsible for complying with all applicable laws and regulations, including proper transportation classification and packaging. 3M's transportation classifications are based on product formulation, packaging, 3M policies and 3M's understanding of applicable current regulations. 3M does not guarantee the accuracy of this classification information. This information applies only to transportation classification and not the packaging, labeling or marking requirements. The above information is only for reference. If you are shipping by air or ocean, YOU are advised to check & meet applicable regulatory requirements.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Global inventory status

Contact 3M for more information. The components of this material are in compliance with the provisions of the Korea Chemical Control Act. Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Australia National Industrial Chemical Notification and Assessment Scheme (NICNAS). Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Philippines RA 6969 requirements. Certain restrictions may apply. Contact the selling division for additional information. The components of this product are in compliance with the new substance notification requirements of CEPA. The components of this product are in compliance with the chemical notification requirements of TSCA. This product complies with Measures on Environmental Management of New Chemical Substances. All ingredients are listed on or exempt from on China IECSC inventory.

SECTION 16: Other information

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Data Sheet or use of the

product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications.

3M Malaysia SDSs are available at www.3M.com.my