Klotz Synthetic Lubricants, Inc.

# 1. Product and Supplier Information



Address

Klotz Synthetic Lubricants, Inc. 7424 Freedom Way Fort Wayne, IN 46818 USA Product Name: ATVUTV-550 5W/50 Engine Synthetic Lubricant

Manufacturer: Klotz Synthetic Lubricants

Phone Number: 260.490.0489

Emergency Contact: 800.424.9300 Chemtrec

Recommended Use: Restrictions of use:

4 Stroke engines Not for use in any other engine than

4-stroke engines.

# 2. Hazard(s) Identification

Osha Hazard Classification: 29 CFR 1910.1200(g)(4)



3. Composition/Information on Ingredients								
CAS#	SARA	Material or Component	Range	Exposure Limits ACGIH				
	313 dm		%	TWA	STEL			
NA	No NA	Synthetic Oil Base	100%	NE	NE			

### 4. First Aid

**Inhalation:** Move yourself and/or individual into fresh non stagnant air. Seek medical attention if breathing becomes harder. Vapors from exhaust may irritate breathing passages.

**Skin Contact:** Wash all areas of contact with hand soap and water. Always wash hands exposed to prevent ingestion. Extended or repeated contact might irritate the skin.

Eyes: Immediately flush eyes with plenty of water for at least 15 minutes while holding eyelids apart.

**Ingestion:** Seek immediate medical attention. Induce vomiting only as directed by physician. Drink water to dilute. Never give anything by mouth to an unconscious person.

Klotz Synthetic Lubricants, Inc.

## 5. Fire Fighting Measures

Flammability Summary(OSHA) No data on combinations. Component data given below.

Flammable

Flammable Properties: Product

Flash Point: 480°F (249°C)

Autoignition Temperature:

Upper Flammable/Explosive Limit, % in air:

No Data

No Data

Lower Flammable/Explosive Limit, % in air:

No Data

### Conditions of flammability:

Flammable in the presence of a source of ignition and the liquid product is above the flash point.

Keep away from high heat/ sparks/ open flame/ or hot surface.

## **Extinguishing Media:**

Foam, Dry chemical or carbon dioxide

#### **Fire Fighting Instructions:**

In case of fire, call emergency services. Then use normal fire fighting equipment including a NIOSH approved self-contained breathing apparatus. Use water to cool containers.

### 6. Accidental Release Measures

#### **Personal Protection for Emergency Situations:**

Eliminate any ignition sources until the area is determined to be free from explosion and fire hazards.

## **Spill Mitigation Procedures**

Air Release: NA

**Water Release:** This product is soluble in water. Contain all liquid for treatment and /or disposal as a hazardous waste. Notify all downstream users of possible contamination.

**Land Release:** Create a barrier to stop and prevent further spill on land. After spill is contained, then use material that is absorbent to soak up all product. All remaining, use an environmentally friendly cleaning soap to clean area.

**Additional Spill Information:** Stop all contamination as soon as possible and notify appropriate personnel. Use the dispose of spill residues per guidelines Section 13, Disposal Considerations.

## 7. Handling and Storage

**Handling:** Be careful when handling to not expose skin, eyes, or mouth to the product.

Storage: Keep in cool dry location with the container sealed with cap.

Shelf Life Limitations: If product is in the original container with cap sealed away from the oxygen,

this product as an indefinite shelf life.

Incompatible Materials for Storage: None

Klotz Synthetic Lubricants, Inc.

8. Exposure Controls and Personal Protection							
CAS#	Material or Component	Parameter	Value	Source			
8012-95-1	Oil Mist, mineral	TWA	5 mg/m	OSHA 1910.100			
				Table Z-1			

## **Protective Equipment for Routine Use of Product**

Skin: Wear impervious gloves to avoid skin contact when handling. Follow good hygiene practices

Eyes: Always wear protection over your eyes when handling product.

Protective Clothing Type: Impervious

Other: Safety shower and eye bath should at all times be available.

## 9. Physical Data

Boiling Point: 750°F (398.9°C) Specific Gravity: .866

Freezing Point: N/A % Volatile By Vol.:0% @ 100°F Melting Point: N/A Viscosity (cSt @ 100 C): 18.5 Vapor Pressure (mmHg): <0.1 @ 100°F Vapor Density (Air=1): Heavier

Solubility in Water: Very Slow Bulk Density: N/A

Evaporation Rate(Water=1): >1 Pour Point: -30°F (-34°C)

Odor: Sweet Appearance: Red

### 10. Stability and Reactivity

### **Chemical Stability:**

Stable under normal conditions

#### **Reactive Properties:**

Sensitivity to mechanical shock: None Hazardous Polymerization: Will not occur. Conditions to avoid: heat/sparks/flame

Chemical Incompatibility: None Incompatible material: None

Decomposition Temperature: None

Product may be unstable at: Temperatures higher than operating temperature.

## 11. Toxicological Information

Component Animal ToxicologyLubricantOral LD50 Value:>2000mg/kgDermal LD50 Value:No DataInhalation LC50 Value:>30000 mg/kgEye Irritation: This material is expected to be severely irritating

Klotz Synthetic Lubricants, Inc.

## 12. Ecological Information

#### Lubricant

**Ecotoxicity** 

Acute and Prolonged toxicity to Fish-Rainbow trout/ LC50 (96 h): > 100 mg/l

Toxicity to Microorganisms: N/A

Not a marine pollutant Environmental Fate:

Test method: OECD Guideline 301F Method of Analysis: BOD of the ThOD Degree of Elimination: >60 % (28 d) Evaluation: Readily Biodegradable

# 13. Disposal Considerations

## **Waste Disposal Summary:**

Product as supplied qualifies as "Unlisted Hazardous Waste D001" with the Characteristic of Ignitability

#### **Disposal Methods:**

Dispose of in accordance with local, state, and federal regulations for hazardous waste.

#### Components subject to land ban restrictions:

No Components subject to land ban restrictions

# **14.1 Transportation Information**

DOT Information: Non-Regulated TDG Information: Non-Dangerous

## 15. Regulatory Information

Miscellaneous Information: This material or all of its components are listed on the Inventory of Existing Chemical Substances under the Toxic Substance Control Act (TSCA) and the Canadian Domestic Substance List (DSL).

## 16. Other Information

Date of Preparation Reason for Issue Prepared By

Original date: 11/19/2015 Generation 1
Revised date: 05/08/2017 Color format
Revised date: 6/12/2019 Pictogram

Klotz Synthetic Lubricants, Inc.