MSDS ORDER NO): RELEA	ASE NO:	MSDS NO:				
BARNES DISTRIBUTION Synonyms: BD1096 BD1096-1 MATERIAL SAFETY DATA SHEET							
SECTION 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION							
PRODUCT NAME: BD1096 PTFE DRY LUBE							
IDENTIFICATION NUMBER: A-6178							
DATE PRINTED: 01/25/08							
PRODUCT USE/CLASS: PTFE DRY LUBRICANT							
MANUFACTURED FOR: BARNES DISTRIBUTION THE GALLERIA/TOWER AT ERIEVIEW 1301 EAST 9TH STREET STE #700 CLEVELAND, OH 44114							
PHONE: 1-866-438-6767 MON - FRI / 8:00 AM - 5:00 PM							
EMERGENO	CY TELEPHONE: 303	8-623-5716 ROC	KY MOUNTAIN POISON	CONTROL 24H			
MANUFACTURED BY: BARNES DISTRIBUTION THE GALLERIA/TOWER AT ERIEVIEW 1301 EAST 9TH STREET STE #700 CLEVELAND, OH 44114							
PHONE: 1-866-438-6767 MON - FRI / 8:00 AM - 5:00 PM							
EMERGENCY TELEPHONE: 303-623-5716 ROCKY MOUNTAIN POISON CONTROL 24H							
PREPARER: CUSTOMER SERVICE							
PHONE :							
PREPARE DATE: 01/25/08							
SECTION 2 - COMPOSITION/INFORMATION ON INGREDIENTS							
ITEM	CHEMICAL NAME		CAS NUMBER	WT/WT % LESS THAN			
01	N-HEXANE		110-54-3	60.0%			
02	2-propanone		67-64-1	25.0%			
03	PROPANE/ISOBUTA	NE/N-BUTANE	68476-86-8	20.0%			

MSDS ORDER NO:

RELEASE NO:

MSDS NO:

ITEM	ACG	IH	B A R N E S EXPOSURE LIN OSP	AITS	B U T I O N COMPANY	SKIN
	TLV-TWA	TLV-STEL	PEL-TWA	PEL-CEILING	TLV-TWA	
01	50 PPM	N.E.	50 PPM	500 PPM	N.E.	YES
02	750 PPM	1000 PPM	750 PPM	N.E.	N.E.	NO
03	1000 PPM	N.E.	800 PPM	N.E.	N.E.	YES

(SEE SECTION 16 FOR ABBREVIATION LEGEND)

-----SECTION 3 - HAZARDS IDENTIFICATION -----

EMERGENCY OVERVIEW: VAPORS IRRITATING TO EYES AND RESPIRATORY TRACT. VAPORS MAY CAUSE FLASH FIRE OR EXPLOSION.

EFFECTS OF OVEREXPOSURE - EYE CONTACT: LIQUID, AEROSOLS AND VAPORS OF THIS PRODUCT ARE IRRITATING AND CAN CAUSE PAIN, TEARING, REDDENING AND SWELLING ACCOMPANIED BY A STINGING SENSATION AND/OR A FEELING LIKE THAT OF FINE DUST IN THE EYES.

EFFECTS OF OVEREXPOSURE - SKIN CONTACT: PROLONGED OR REPEATED CONTACT CAN RESULT IN DEFATTING AND DRYING OF THE SKIN WHICH MAY RESULT IN SKIN IRRITATION AND DERMATITIS (RASH).

EFFECTS OF OVEREXPOSURE - INHALATION: HEADACHES, DIZZINESS, NAUSEA, DECREASED BLOOD PRESSURE, CHANGES IN HEART RATE AND CYANOSIS MAY RESULT FROM OVER-EXPOSURE TO VAPOR OR SKIN EXPOSURE. PROLONGED INHALATION MAY BE HARMFUL.

EFFECTS OF OVEREXPOSURE - INGESTION: THIS MATERIAL MAY BE HARMFUL OR FATAL IF SWALLOWED. IF A CORROSIVE PRODUCT, MAY CAUSE SEVERE AND PERMANENT DAMAGE TO MOUTH, THROAT AND STOMACH.

EFFECTS OF OVEREXPOSURE - CHRONIC HAZARDS: OVEREXPOSURE MAY CAUSE NERVOUS SYSTEM DAMAGE. OVEREXPOSURE MAY CAUSE LUNG DAMAGE. OVEREXPOSURE MAY CAUSE KIDNEY DAMAGE. MAY CAUSE LIVER DISORDER (E.G., EDEMA, PROTEINURIA) AND DAMAGE.

PRIMARY ROUTE(S) OF ENTRY: SKIN CONTACT SKIN ABSORPTION INHALATION INGESTION EYE CONTACT

-----SECTION 4 - FIRST AID MEASURES -----

FIRST AID - EYE CONTACT:

ORDER NO: MSDS NO: RELEASE NO: BARNES DISTRIBUTION IMMEDIATELY FLUSH EYES WITH PLENTY OF WATER. GET MEDICAL ATTENTION, IF IRRITATION PERSISTS. FIRST AID - SKIN CONTACT: WASH WITH SOAP AND WATER. GET MEDICAL ATTENTION IF IRRITATION DEVELOPS OR PERSISTS. FIRST AID - INHALATION: REMOVE TO FRESH AIR. IF NOT BREATHING, GIVE ARTIFICIAL RESPIRATION. IF BREATHING IS DIFFICULT, GIVE OXYGEN. GET IMMEDIATE MEDICAL ATTENTION. FIRST AID - INGESTION: GET MEDICAL ATTENTION IMMEDIATELY. IF SWALLOWED, DO NOT INDUCE VOMITING. GIVE VICTIM A GLASS OF WATER OR MILK. CALL A PHYSICIAN OR POISON CONTROL CENTER IMMEDIATELY. NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON. -----SECTION 5 - FIRE FIGHTING MEASURES -----FLASH POINT: -156 F (PENSKY-MARTENS C.C.) LOWER EXPLOSIVE LIMIT: 1.0% UPPER EXPLOSIVE LIMIT: 12.8% AUTOIGNITION TEMPERATURE: ND EXTINGUISHING MEDIA: ALCOHOL FOAM CO2 DRY CHEMICAL FOAM WATER FOG UNUSUAL FIRE AND EXPLOSION HAZARDS: VAPORS CAN TRAVEL TO A SOURCE OF IGNITION AND FLASH BACK. "EMPTY" CONTAINERS RETAIN PRODUCT RESIDUE (LIQUID AND/OR VAPOR) AND CAN BE DANGEROUS. DO NOT PRESSURIZE, CUT, WELD, BRAZE, SOLDER, DRILL, GRIND, OR EXPOSE SUCH CONTAINERS TO HEAT, FLAME, SPARKS, STATIC ELECTRICITY, OR OTHER SOURCES OF IGNITION; THEY MAY EXPLODE AND CAUSE INJURY OR DEATH. EMPTY DRUMS SHOULD BE COMPLETELY DRAINED, PROPERLY BUNGED AND PROMPTLY RETURNED TO A DRUM RECONDITIONER, OR PROPERLY DISPOSED OF. SPECIAL FIREFIGHTING PROCEDURES: CONTAINERS CAN BUILD UP PRESSURE IF EXPOSED TO HEAT (FIRE). AS IN ANY FIRE, WEAR SELF-CONTAINED BREATHING APPARATUS PRESSURE-DEMAND (MSHA/NIOSH APPROVED OR EOUIVALENT) AND FULL PROTECTIVE GEAR.

-----SECTION 6 - ACCIDENTAL RELEASE MEASURES -----

MSDS

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: ABSORB SPILL WITH INERT MATERIAL (E.G. DRY SAND OR EARTH), THEN PLACE IN A CHEMICAL WASTE CONTAINER.

MSDS ORDER NO:

RELEASE NO: MSDS NO:

BARNES DISTRIBUTION

-----SECTION 7 - HANDLING AND STORAGE -----

HANDLING: WASH THOROUGHLY AFTER HANDLING.

STORAGE: KEEP AWAY FROM HEAT, SPARKS AND FLAME. KEEP FROM FREEZING.

-----SECTION 8 - EXPOSURE CONTROLS/PERSONAL PROTECTION -----

ENGINEERING CONTROLS:

LOCAL EXHAUST VENTILATION MAY BE NECESSARY TO CONTROL ANY AIR CONTAMINANTS TO WITHIN THEIR TLVS DURING THE USE OF THIS PRODUCT.

RESPIRATORY PROTECTION:

A NIOSH/MSHA APPROVED AIR PURIFYING RESPIRATOR WITH AN ORGANIC VAPOR CARTRIDGE OR CANISTER MAY BE PERMISSIBLE UNDER CERTAIN CIRCUMSTANCES WHERE AIRBORNE CONCENTRATIONS ARE EXPECTED TO EXCEED EXPOSURE LIMITS. PROTECTION PROVIDED BY AIR PURIFYING RESPIRATORS IS LIMITED. USE A POSITIVE PRESSURE AIR SUPPLIED RESPIRATOR IF THERE IS ANY POTENTIAL FOR AN UNCONTROLLED RELEASE, EXPOSURE LEVELS ARE NOT KNOWN, OR ANY OTHER CIRCUMSTANCES WHERE AIR PURIFYING RESPIRATORS MAY NOT PROVIDE ADEQUATE PROTECTION.

SKIN PROTECTION:

WHERE CONTACT IS LIKELY, WEAR CHEMICAL RESISTANT GLOVES, A CHEMICAL SUIT, RUBBER BOOTS, AND CHEMICAL SAFETY GOGGLES PLUS A FACE SHIELD.

EYE PROTECTION:

WEAR SAFETY GLASSES WITH SIDE SHIELDS (OR GOGGLES) AND A FACE SHIELD.

OTHER PROTECTIVE EQUIPMENT: STANDARD INDUSTRIAL CLOTHING STANDARDS SHOULD BE FOLLOWED.

HYGIENIC PRACTICES:

WASH HANDS BEFORE EATING. REMOVE CONTAMINATED CLOTHING AND WASH BEFORE REUSE. USE ONLY IN A WELL VENTILATED AREA. FOLLOW ALL MSDS/LABEL PRECAUTIONS EVEN AFTER CONTAINER IS EMPTIED BECAUSE THEY MAY RETAIN PRODUCT RESIDUES. AVOID PROLONGED OR REPEATED CONTACT WITH SKIN. AVOID BREATHING VAPORS FROM HEATED MATERIAL. AVOID CONTACT WITH EYES, SKIN, AND CLOTHING.

-----SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES -----

BOILING RANGE: -43 - 159 F

VAPOR DENSITY: IS HEAVIER THAN AIR

ODOR: SOLVENT

ODOR THRESHOLD: ND

APPEARANCE: HAZY

MSDS ORDER NO: RELEASE NO: MSDS NO: BARNES DISTRIBUTION EVAPORATION RATE: IS FASTER THAN BUTYL ACETATE SOLUBILITY IN H2O: NEGLIGIBLE FREEZE POINT: 32 SPECIFIC GRAVITY: 0.6693 VAPOR PRESSURE: 80-90 AN :% 0.0 @ Hq PHYSICAL STATE: AEROSOL VISCOSITY: ND COEFFICIENT OF WATER/OIL DISTRIBUTION: COMPLETE (SEE SECTION 16 FOR ABBREVIATION LEGEND) -----SECTION 10 - STABILITY AND REACTIVITY -----CONDITIONS TO AVOID: ALL SOURCES OF IGNITION, WELDING ARCS, AND OPEN FLAMES. INCOMPATIBILITY: STRONG ACIDS, ALKALIS, OXIDIZERS, AND AMINES. HAZARDOUS DECOMPOSITION PRODUCTS: OXIDES OF CARBON, OXIDES OF NITROGEN, AND MAY PRODUCE FORMS OF CHLORIDE, CHLORINE, AND PHOSGENE. HAZARDOUS POLYMERIZATION: WILL NOT OCCUR UNDER NORMAL CONDITIONS. STABILITY: THIS PRODUCT IS STABLE UNDER NORMAL STORAGE CONDITIONS. -----SECTION 11 - TOXICOLOGICAL PROPERTIES -----PRODUCT LD50: 5800 MG/KG PRODUCT LC50: 50100 PPM COMPONENT TOXICOLOGICAL INFORMATION: CHEMICAL NAME LD50 LC50 N-HEXANE 28710 MG/KG/RAT 150000 MG/M3/MOUSE 2-propanone 5800 MG/KG/RAT 50100 MG/M3/8H/RAT PROPANE/ISOBUTANE/N-BUTANE NE 658000 MG/M3/4H RAT POLYTETRAFLUOROETHYLENE NE NE PAGE: 5

ORDER NO: RELEASE NO: MSDS NO: BARNES DISTRIBUTION VM&P NAPHTHA 5840 MG/KG/RAT 153000 MG/M3/MOUSE DOCK RESIN NE NE TOLUENE 636 MG/KG/RAT 49000 MG/M3/4H/RAT BENZENE 930 MG/KG N.E. -----SECTION 12 - ECOLOGICAL INFORMATION -----ECOLOGICAL INFORMATION: NO INFORMATION. -----SECTION 13 - DISPOSAL CONSIDERATIONS -----DISPOSAL METHOD: DISPOSE IN ACCORDANCE WITH ALL FEDERAL, STATE, AND LOCAL REGULATIONS. -----SECTION 14 - TRANSPORTATION INFORMATION -----DOT PROPER SHIPPING NAME: AEROSOL - CONSUMER COMMODITY DOT TECHNICAL NAME: ORM-D DOT HAZARD CLASS: 2.1 HAZARD SUBCLASS: NA DOT UN/NA NUMBER: UN1950 PACKING GROUP: NA RESP. GUIDE PAGE: 126 -----SECTION 15 - REGULATORY INFORMATION -----U.S. FEDERAL REGULATIONS: AS FOLLOWS OSHA: HAZARDOUS BY DEFINITION OF HAZARD COMMUNICATION STANDARD (29 CFR 1910.1200) CERCLA - SARA HAZARD CATEGORY: THIS PRODUCT HAS BEEN REVIEWED ACCORDING TO THE EPA 'HAZARD CATEGORIES' PROMULGATED UNDER SECTIONS 311 AND 312 OF THE SUPERFUND AMENDMENT AND REAUTHORIZATION ACT OF 1986 (SARA TITLE III) AND IS CONSIDERED, UNDER APPLICABLE DEFINITIONS, TO MEET THE FOLLOWING CATEGORIES: IMMEDIATE HEALTH HAZARD CHRONIC HEALTH HAZARD

FIRE HAZARD

MSDS

MSDS ORDER NO:	RELEASE NO: MSDS I	ло:				
BARNES DISTRIBUTION PRESSURIZED GAS HAZARD						
SARA SECTION 313: THIS PRODUCT CONTAINS THE FOLLOWING SUBSTANCES SUBJECT TO THE REPORTING REQUIREMENTS OF SECTION 313 OF TITLE III OF THE SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT OF 1986 AND 40 CFR PART 372:						
CHEMICAL NAME	CAS NUMBER	WT/WT % IS LESS THAN				
N-HEXANE	110-54-3	60.0%				
TOXIC SUBSTANCES CONTROL ACT: THIS PRODUCT CONTAINS THE FOLLOWING CHEMICAL SUBSTANCES SUBJECT TO THE REPORTING REQUIREMENTS OF TSCA 12(B) IF EXPORTED FROM THE UNITED STATES:						
CHEMICAL NAME	CAS NUMBER					
VM&P NAPHTHA	8032-32-4					
U.S. STATE REGULA	FIONS: AS FOLLOWS					
NEW JERSEY RIGHT-TO-KNOW: THE FOLLOWING MATERIALS ARE NON-HAZARDOUS, BUT ARE AMONG THE TOP FIVE COMPONENTS IN THIS PRODUCT:						
CHEMICAL NAME	CAS NUMBER					
POLYTETRAFLUOROET	HYLENE 9002-84-0					
PENNSYLVANIA RIGHT-TO-KNOW: THE FOLLOWING NON-HAZARDOUS INGREDIENTS ARE PRESENT IN THE PRODUCT AT GREATER THAN 3%:						
CHEMICAL NAME	CAS NUMBER					
NO NON-HAZARDOUS INGREDIENTS ARE PRESENT AT GREATER THAN 3%.						
CALIFORNIA PROPOSITION 65:						
WARNING: THE CHEMICAL(S) NOTED BELOW AND CONTAINED IN THIS PRODUCT, ARE KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER, BIRTH DEFECTS OR OTHER REPRODUCTIVE HARM:						
CHEMICAL NAME	CAS NUMBER	R				
TOLUENE	108-88-3					
BENZENE	71-43-2					
INTERNATIONAL REGULATIONS: AS FOLLOWS						
CANADIAN WHMIS:						
	PAGE:	7				

MSDS ORDER NO:

RELEASE NO: MSDS NO:

BARNES DISTRIBUTION THIS MSDS HAS BEEN PREPARED IN COMPLIANCE WITH CONTROLLED PRODUCT REGULATIONS EXCEPT FOR USE OF THE 16 HEADINGS.

CANADIAN WHMIS CLASS: NO INFORMATION AVAILABLE.

-----SECTION 16 - OTHER INFORMATION -----

HMIS RATINGS: HEALTH 1 FLAMMABILITY 4 REACTIVITY 0

PREVIOUS MSDS REVISION DATE: 09/28/05

REASON FOR REVISION: CUSTOMER REQUEST

VOLATILE ORGANIC COMPOUNDS (VOCS): 4.31 LBS/GAL 516 GRAMS/LTR

LEGEND: N.A. - NOT APPLICABLE N.E. - NOT ESTABLISHED N.D. - NOT DETERMINED

THIS MSDS IS NOT FOR REPRODUCTION OR DISTRIBUTION

THE INFORMATION CONTAINED ON THIS MSDS IS BEEN CHECKED AND SHOULD BE ACCURATE. HOWEVER, IT IS THE RESPONSIBILITY OF THE USER TO COMPLY WITH ALL FEDERAL, STATE, AND LOCAL LAWS AND REGULATIONS.

PRODUCT: A-6178

PAGE: 8 THE END