



OUR CORE BUSINESS PRODUCTS & INFORMATION BROCHURES & VIDEO GALLERY

CUSTOMER ORDER CENTER CAREERS CONTACT

HOME

SDS Search

Safety Data Sheet

Supply Co. - 64704711 KP82811-1X MPL-4

Document Nbr: 082621

Class C Parts IDs KP82811,KP82811-1

SAFETY DATA SHEET

ISSUING DATE: 17-APR-2015

REVISION DATE: 13-JUN-2015

VERSI ON: 1. 02

---- 1. I DENTI FI CATI ON OF THE SUBSTANCE/PREPARATI ON ----- AND OF THE COMPANY/UNDERTAKI NG

PRODUCT I DENTI FI ER:

PRODUCT NAME: 64704711 KP82811-1X MPL-4

RECOMMENDED USE OF THE CHEMICAL AND RESTRICTIONS ON USE:

PRODUCT CODE: F01504

PRODUCT TYPE: EXTREMELY FLAMMABLE AEROSOL

SYNONYMS: NONE

SUPPLIER'S DETAILS:

RECOMMENDED USE: MULTI - PURPOSE LUBRI CANT.
USES ADVISED AGAINST: NO INFORMATION AVAILABLE

MANUFACTURER:

AMERICAN JETWAY CORPORATION 34136 MYRTLE STREET WAYNE, MI 48184-0126

DI STRI BUTOR:

CLASS C SOLUTIONS GROUP
A BUSINESS OF MSC INDUSTRIAL SUPPLY CO.
75 MAXESS ROAD
MELVILLE, NY 11747-3151
1-866-438-6767

EMERGENCY TELEPHONE NUMBER:

CHEMICAL EMERGENCY PHONE NUMBER: CHEMIREC: 1-800-262-8200 ID 1195

COMPANY EMERGENCY PHONE NUMBER: 734-721-5930

----2. HAZARDS IDENTIFICATION -----

CLASSI FI CATI ON:

SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE): CATEGORY 3

ASPIRATION TOXICITY: CATEGORY 1 FLAMMABLE AEROSOLS: CATEGORY 1 GASES UNDER PRESSURE: COMPRESSED GAS

GHS LABEL ELEMENTS, INCLUDING PRECAUTIONARY STATEMENTS:

EMERGENCY OVERVIEW:

DANGER:

HAZARD STATEMENTS:

MAY CAUSE RESPIRATORY IRRITATION. MAY CAUSE DROWSINESS OR DIZZINESS
MAY BE FATAL IF SWALLOWED AND ENTERS AIRWAYS
EXTREMELY FLAMMABLE AEROSOL
CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED

EXCLAMATI ON MARK HEALTH HAZARD FLAME GAS CYLI NDER

APPEARANCE: CLEAR

PHYSICAL ESTATE AEROSOL

ODOR: SOLVENT

PRECAUTIONARY STATEMENTS - PREVENTION:
AVOID BREATHING DUST/FUME/GAS/MIST/VAPORS/SPRAY
USE ONLY OUTDOORS OR IN A WELL-VENTILATED AREA
KEEP AWAY FROM HEAT/SPARKS/OPEN FLAMES/HOT SURFACES. - NO SMOKING
DO NOT SPRAY ON AN OPEN FLAME OR OTHER IGNITION SOURCE
PRESSURIZED CONTAINER: DO NOT PIERCE OR BURN, EVEN AFTER USE

PRECAUTIONARY STATEMENTS - RESPONSE:

IF INHALED:

REMOVE PERSON TO FRESH AIR AND KEEP COMFORTABLE FOR BREATHING. CALL A POISON CENTER OR DOCTOR/PHYSICIAN IF YOU FEEL UNWELL

IF SWALLOWED:

I MMEDIATELY CALL A POISON CENTER OR DOCTOR/PHYSICIAN DO NOT INDUCE VOMITING

PRECAUTIONARY STATEMENTS - STORAGE:

STORE LOCKED UP

STORE IN A WELL-VENTILATED PLACE. KEEP CONTAINER TIGHTLY CLOSED

PROTECT FROM SUNLIGHT. DO NOT EXPOSE TO TEMPERATURES EXCEEDING 50 DEG. C/122 DEG. F

PRECAUTIONARY STATEMENTS - DISPOSAL:

DISPOSE OF CONTENTS/CONTAINER TO AN APPROVED WASTE DISPOSAL PLANT

HAZARDS NOT OTHERWISE CLASSIFIED (HNOC): NONE

OTHER INFORMATION:

TOXIC TO AQUATIC LIFE WITH LONG LASTING EFFECTS

O% OF THE MIXTURE CONSISTS OF INGREDIENT(S) OF UNKNOWN TOXICITY

----3. COMPOSITION/INFORMATION ON INGREDIENTS -----

CHEMI CAL NAME	CAS - NO	WEI GHT %
PETROLEUM DISTILLATES	64742 - 47 - 8	70 - 80
PROPANE/I SOBUTANE/N- BUTANE	68476 - 86 - 8	20-30
ETHYL ACETIC ESTER	141 - 78 - 6	1- 10
1 - METHYOXY - 2 - PROPANOL	107 - 98 - 2	1-10

*THE EXACT PERCENTAGE (CONCENTRATION) OF COMPOSITION HAS BEEN WITHHELD AS A TRADE SECRET.

----4. FIRST AID MEASURES -----

FIRST AID MEASURES FOR DIFFERENT EXPOSURE ROUTES:

GENERAL ADVICE:

AVOID CONTACT WITH EYES, SKIN, AND CLOTHING. AVOID BREATHING, VAPORS, MIST, OR GAS.

EYE CONTACT:

IMMEDIATELY FLUSH WITH PLENTY OF WATER. AFTER INITIAL FLUSHING, REMOVE ANY CONTACT LENSES AND CONTINUE FLUSHING FOR AT LEAST 15 MINUTES. SEEK IMMEDIATE MEDICAL ATTENTION/ADVICE.

SKIN CONTACT:

WASH OFF IMMEDIATELY WITH SOAP AND PLENTY OF WATER. REMOVE AND WASH CONTAMINATED CLOTHING BEFORE RE-USE. GET MEDICAL ATTENTION IMMEDIATELY IF SYMPTOMS OCCUR.

I NHALATI ON:

MOVE TO FRESH AIR. IF NOT BREATHING, GIVE ARTIFICIAL RESPIRATION. IF BREATHING HAS STOPPED, CONTACT EMERGENCY MEDICAL SERVICES IMMEDIATELY.

I NGESTI ON:

DO NOT INDUCE VOMITING. CALL A PHYSICIAN IMMEDIATELY. NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON. RISK OF PRODUCT ENTERING THE LUNGS ON VOMITING AFTER INGESTION.

MOST IMPORTANT SYMPTOMS/EFFECTS, ACUTE AND DELAYED:

MAIN SYMPTOMS:

MAY CAUSE RESPIRATORY IRRITATION. CAUSES SKIN AND EYE IRRITATION. MAY CAUSE

RESPIRATORY SYSTEM IRRITATION. HARMFUL IF SWALLOWED AND ENTERS AIRWAYS.

INDICATION OF IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENT NEEDED, IF NECESSARY:

NOTES TO PHYSICIAN: TREAT SYMPTOMATICALLY.

----5. FIRE-FIGHTING MEASURES -----

SUITABLE EXTINGUISHING MEDIA:

WATER FOG. DRY CHEMICAL. CARBON DIOXIDE (CO2). COOL CONTAINERS/TANKS WITH WATER SPRAY.

UNSUITABLE EXTINGUISHING MEDIA:

KEEP AWAY FROM SOURCES OF IGNITION - NO SMOKING. COOL CONTAINERS/TANKS WITH WATER SPRAY.

SPECIFIC HAZARDS ARISING FROM THE CHEMICAL:

EXTREMELY FLAMMABLE. KEEP PRODUCT AND EMPTY CONTAINER AWAY FROM HEAT AND SOURCES OF IGNITION. IN THE EVENT OF FIRE AND/OR EXPLOSION DO NOT BREATHE FUMES. IN THE EVENT OF FIRE, COOL TANKS WITH WATER SPRAY. RISK OF IGNITION.

EXPLOSION DATA:

SENSITIVITY TO MECHANICAL IMPACT: NONE. SENSITIVITY TO STATIC DISCHARGE: YES.

PROTECTIVE EQUIPMENT AND PRECAUTIONS FOR FIREFIGHTERS:

AS IN ANY FIRE, WEAR SELF-CONTAINED BREATHING APPARATUS PRESSURE-DEMAND, MSHA/NIOSH (APPROVED OR EQUIVALENT) AND FULL PROTECTIVE GEAR.

----- 6. ACCIDENTAL RELEASE MEASURES -----

PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES:

PERSONAL PRECAUTIONS:

AVOID CONTACT WITH EYES, SKIN, AND CLOTHING. AVOID BREATHING VAPORS OR MISTS.. USE WITH ADEQUATE VENTILATION. KEEP CONTAINER AWAY FROM HEAT, FLAMES, AND ALL OTHER SOURCES OF IGNITION.

ENVIRONMENTAL PRECAUTIONS:

ENVIRONMENTAL PRECAUTIONS:

BEWARE OF VAPORS ACCUMULATING TO FORM EXPLOSIVE CONCENTRATIONS. VAPORS CAN ACCUMULATE IN LOW AREAS. PREVENT FURTHER LEAKAGE OR SPILLAGE IF SAFE TO DO SO. DO NOT ALLOW MATERIAL TO CONTAMINATE GROUND WATER SYSTEM. PREVENT PRODUCT FROM ENTERING DRAINS. LOCAL AUTHORITIES SHOULD BE ADVISED IF SIGNIFICANT SPILLAGES CANNOT BE CONTAINED.

METHODS AND MATERIALS FOR CONTAINMENT AND CLEANING UP:

METHODS FOR CONTAINMENT:

COVER WITH DRY EARTH, DRY SAND, OR OTHER NON-COMBUSTIBLE MATERIAL FOLLOWED WITH PLASTIC SHEET TO MINIMIZE SPREADING OR CONTACT WITH RAIN.

METHODS FOR CLEANING UP:

PICK UP AND TRANSFER TO PROPERLY LABELED CONTAINERS. SOAK UP WITH INERT ABSORBENT MATERIAL. CLEAN CONTAMINATED SURFACE THOROUGHLY. AFTER CLEANING, FLUSH AWAY TRACES WITH WATER. TAKE PRECAUTIONARY MEASURES AGAINST STATIC DISCHARGES.

----7. HANDLING AND STORAGE -----

PRECAUTIONS FOR SAFE HANDLING:

ADVICE ON SAFE HANDLING:

AVOID CONTACT WITH EYES. AVOID BREATHING VAPORS OR MISTS. CONTENTS UNDER

PRESSURE. DO NOT PUNCTURE OR INCINERATE CANS. DO NOT STICK PIN OR ANY OTHER SHARP OBJECT INTO OPENING ON TOP OF CAN.

CONDITIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILITIES:

TECHNICAL MEASURES/STORAGE CONDITIONS:

KEEP CONTAINER TIGHTLY CLOSED IN A DRY AND WELL-VENTILATED PLACE. KEEP AWAY FROM OPEN FLAMES, HOT SURFACES AND SOURCES OF IGNITION. KEEP IN PROPERLY LABELED CONTAINERS. KEEP OUT OF THE REACH OF CHILDREN. STORE LOCKED UP.

INCOMPATIBLE PRODUCTS: STRONG ACIDS, ALKALIS, OR OXIDIZING AGENTS.

AEROSOL LEVEL: 3

----- 8. EXPOSURE CONTROLS/PERSONAL PROTECTION -----

CONTROL PARAMETERS:

EXPOSURE GUIDELINES:

CHEMI CAL NAME	ACGIH TLV	OSHA PEL	NI OSH I DLH
PROPANE/I SOBUTANE/ N - BUTANE 68476 - 86 - 8	74-98-6: TWA: 1000 PPM	74-98-6: TWA: 1000 PPM TWA: 1800 MG/M3	74-98-6: IDLH: 2100 PPM TWA: 1000 PPM TWA: 1800 MG/M3
	106-97-8: STEL: 1000 PPM 75-28-5:	1000 PPM	106 - 97 - 8: TWA: 800 PPM TWA: 1900 MG/M3
	STEL: 1000 PPM		
		106-97-8: (VACATED) TWA: 800 PPM	
		(VACATED) TWA: 1900 MG/M3	
ETHYL ACETIC ESTER 141-78-6	TWA: 400 PPM	TWA: 400 PPM TWA: 1400 MG/M3	I DLH: 2000 PPM TWA: 400 PPM TWA: 1400 MG/M3
		(VACATED) TWA: 400 PPM	1111 1100 1111 11
		(VACATED) TWA: 1400 MG/M3	
1 - METHYOXY - 2 - PROPANOL 107 - 98 - 2	STEL: 100 PPM TWA: 50 PPM	(VACATED) TWA: 100 PPM	TWA: 100 PPM TWA: 360 MG/M3 STEL: 150 PPM
		(VACATED) TWA: 360 MG/M3	
		(VACATED) STEL: 150 PPM	
		(VACATED) STEL: 540 MG/M3	

ACGIH: (AMERICAN CONFERENCE OF GOVERNMENTAL INDUSTRIAL HYGIENISTS)

OSHA: (OCCUPATIONAL SAFETY & HEALTH ADMINISTRATION)

NIOSH IDLH: IMMEDIATELY DANGEROUS TO LIFE OR HEALTH

OTHER EXPOSURE GUIDELINES:

VACATED LIMITS REVOKED BY THE COURT OF APPEALS DECISION IN AFL-CIO V. OSHA,

965 F. 2D 962 (11TH CIR., 1992).

EXPOSURE CONTROLS:

ENGINEERING MEASURES:

SHOWERS

EYEWASH STATIONS

VENTILATION SYSTEMS.

INDIVIDUAL PROTECTION MEASURES, SUCH AS PERSONAL PROTECTIVE EQUIPMENT:

EYE/FACE PROTECTION: SAFETY GLASSES WITH SIDE-SHIELDS.

SKIN AND BODY PROTECTION: CHEMICAL RESISTANT APRON. PROTECTIVE GLOVES.

RESPIRATORY PROTECTION:

IF EXPOSURE LIMITS ARE EXCEEDED OR IRRITATION IS EXPERIENCED, NIOSH/MSHA APPROVED RESPIRATORY PROTECTION SHOULD BE WORN. POSITIVE-PRESSURE SUPPLIED AIR RESPIRATORS MAY BE REQUIRED FOR HIGH AIRBORNE CONTAMINANT CONCENTRATIONS. RESPIRATORY PROTECTION MUST BE PROVIDED IN ACCORDANCE WITH CURRENT LOCAL REGULATIONS.

HYGIENE MEASURES:

HANDLE IN ACCORDANCE WITH GOOD INDUSTRIAL HYGIENE AND SAFETY PRACTICE.

----9. PHYSI CAL AND CHEMI CAL PROPERTIES -----

PHYSICAL AND CHEMICAL PROPERTIES:

PHYSI CAL STATE: AEROSOL

APPEARANCE: CLEAR

ODOR: SOLVENT

COLOR: AMBER

ODOR THRESHOLD: NO INFORMATION AVAILABLE

PROPERTY VALUES REMARKS - METHODS

PH

 $\begin{tabular}{ll} {\tt MELTING/FREEZING} & {\tt POINT} & {\tt NO} & {\tt INFORMATION} & {\tt AVAILABLE} \\ \end{tabular}$

 ${\tt BOILING\ POINT/BOILING\ RANGE} \qquad {\tt NO\ INFORMATION\ AVAILABLE}$

FLASH POINT - 97 DEG. C / - 142 DEG. F BASED ON PROPELLANT

EVAPORATION RATE NO INFORMATION AVAILABLE

FLAMMABILITY (SOLID, GAS) NO INFORMATION AVAILABLE

FLAMMABILITY LIMITS IN AIR:

UPPER FLAMMABILITY LIMIT NO INFORMATION AVAILABLE LOWER FLAMMABILITY LIMIT NO INFORMATION AVAILABLE

VAPOR PRESSURE NO INFORMATION AVAILABLE

VAPOR DENSITY NO INFORMATION AVAILABLE

SPECIFIC GRAVITY 0. 74

WATER SOLUBILITY PRACTICALLY INSOLUBLE

PARTITION COEFFICIENT

N - OCTANOL/WATER

NO INFORMATION AVAILABLE

Class C Solutions Group, a business of MSC Industrial Supply Co. - 64704711 KP82811-1X MPL-4

AUTOI GNI TI ON TEMPERATURE NO INFORMATI ON AVAILABLE NOT APPLI CABLE

DECOMPOSITION TEMPERATURE NO INFORMATION AVAILABLE

VI SCOSITY NO INFORMATION AVAILABLE

EXPLOSIVE PROPERTIES NO INFORMATION AVAILABLE

OTHER INFORMATION: VOC CONTENT (%): 96.54

MIR VALUE: 1.22

----- 10. STABILITY AND REACTIVITY -----

REACTIVITY: NO DATA AVAILABLE

CHEMICAL STABILITY: STABLE UNDER RECOMMENDED STORAGE CONDITIONS.

POSSIBILITY OF HAZARDOUS REACTIONS: NONE UNDER NORMAL PROCESSING.

CONDITIONS TO AVOID: EXTREMES OF TEMPERATURE AND DIRECT SUNLIGHT.

INCOMPATIBLE MATERIALS: STRONG ACIDS, ALKALIS, OR OXIDIZING AGENTS.

HAZARDOUS DECOMPOSITION PRODUCTS: NONE KNOWN BASED ON INFORMATION SUPPLIED.

----- 11. TOXI COLOGI CAL INFORMATION -----

INFORMATION ON LIKELY ROUTES OF EXPOSURE:

PRODUCT INFORMATION:

I NHALATI ON:

AVOID BREATHING VAPORS OR MISTS. VAPORS MAY IRRITATE THROAT AND RESPIRATORY SYSTEM. MAY CAUSE DROWNSINESS AND DIZZINESS BASED ON COMPONENTS. MAY CAUSE IRRITATION OF RESPIRATORY TRACT.

EYE CONTACT: AVOID CONTACT WITH EYES.

SKIN CONTACT: AVOID CONTACT WITH SKIN.

I NGESTI ON:

MAY BE HARMFUL OR FATAL IF SWALLOWED. ASPIRATION INTO THE LUNGS DURING SWALLOWING MAY CAUSE SERIOUS LUNG DAMAGE WHICH MAY BE FATAL.

COMPONENT INFORMATION:

CHEMI CAL NAME	LD50 ORAL	LD50 DERMAL	LC50 INHALATION
PETROLEUM DI STI LLATES	>5000 MG/KG	>2000 MG/KG	>5. 2 MG/L
64742 - 47 - 8	(RAT)	(RABBIT)	(RAT) 4 H
ETHYL ACETIC ESTER	=5620 MG/KG	>18000 MG/KG	
141-78-6	(RAT)	(RABBIT)	
1 - METHYOXY - 2 - PROPANOL	=5000 MG/KG	=13 G/KG	>6 MG/L
107 - 98 - 2	(RAT)	(RABBIT)	(RAT) 4 H

INFORMATION ON TOXICOLOGICAL EFFECTS:

${\bf SYMPTOMS:}$

HARMFUL IF INHALED. ASPIRATION INTO THE LUNGS DURING SWALLOWING MAY CAUSE SERIOUS LUNG DAMAGE WHICH MAY BE FATAL.

DELAYED AND IMMEDIATE EFFECTS AS WELL AS CHRONIC EFFECTS FROM SHORT AND LONG-TERM EXPOSURE:

SENSITIZATION: NONE KNOWN.

GERM CELL MUTAGENICITY: NONE KNOWN.

CARCINOGENICITY: THERE ARE NO KNOWN CARCINOGENIC CHEMICALS IN THIS PRODUCT.

REPRODUCTIVE TOXICITY: NO INFORMATION AVAILABLE.

SPECIFIC TARGET ORGAN SYSTEMIC TOXICITY (SINGLE EXPOSURE):

MAY CAUSE RESPIRATORY IRRITATION. MAY CAUSE DROWSINESS AND DIZZINESS.

SPECIFIC TARGET ORGAN SYSTEMIC TOXICITY (REPEATED EXPOSURE): NO INFORMATION AVAILABLE.

CHRONI C TOXI CITY:

INTENTIONAL MISUSE BY DELIBERATELY CONCENTRATING AND INHALING CONTENTS MAY BE HARMFUL OR FATAL. CHRONIC HYDROCARBON ABUSE HAS BEEN ASSOCIATED WITH IRREGULAR HEART RHYTHMS AND POTENTIAL CARDIAC ARREST. PROLONGED SKIN CONTACT MAY DEFAT THE SKIN AND PRODUCE DERMATITIS.

TARGET ORGAN EFFECTS:

CENTRAL NERVOUS SYSTEM, EYES, RESPIRATORY SYSTEM, SKIN.

ASPIRATION HAZARD: MAY BE FATAL IF SWALLOWED AND ENTERS AIRWAYS.

NUMERICAL MEASURES OF TOXICITY - PRODUCT INFORMATION:

UNKNOWN ACUTE TOXICITY:

O% OF THE MIXTURE CONSISTS OF INGREDIENT(S) OF UNKNOWN TOXICITY

THE FOLLOWING VALUES ARE CALCULATED BASED ON CHAPTER 3.1 OF THE GHS DOCUMENT: ATEMIX (INHALATION-VAPOR): 1064~MG/L

-----12. ECOLOGICAL INFORMATION -----

ECOTOXI CI TY:

CHEMICAL NAME TOXICITY TO ALGAE TOXICITY TO FISH

PETROLEUM DI STI LLATES

2. 2 MG/L LC50 LEPOMI S

64742 - 47 - 8

MACROCHI RUS 96H STATI C

2. 4 MG/L LC50 ONCORHYNCHUS MYKISS 96H STATIC

45 MG/L LC50 PIMEPHALES PROMELAS 96H FLOW-THROUGH

PROPANE/I SOBUTANE/N-BUTANE 68476-86-8

ETHYL ACETI C ESTER 220 - 250 MG/L LC50 141 - 78 - 6 PI MEPHALES PROMELAS 96H

FLOW- THROUGH

352 - 500 MG/L LC50 ONCORHYNCHUS MYKISS 96H

SEMI - STATI C

484 MG/L LC50 ONCORHYNCHUS MYKISS 96H FLOW-THROUGH

1 - METHYOXY - 2 - PROPANOL 20. 8 G/L LC50 PI MEPHALES 107 - 98 - 2 PROMELAS 96H STATIC

CHEMI CAL NAME TOXI CITY TO TOXI CITY TO DAPHNI A AND MI CROORGANI SMS OTHER AQUATI C INVERTEBRATES

PETROLEUM DI STI LLATES

PROPANE/I SOBUTANE/N-BUTANE

ETHYL ACETIC ESTER 560 MG/L EC50 DAPHNIA MAGNA 48H STATIC

1 - METHYOXY - 2 - PROPANOL 23300 MG/L EC50 DAPHNI A

MAGNA 48H

PERSISTENCE AND DEGRADABILITY: NO INFORMATION AVAILABLE.

BIOACCUMULATION: NO INFORMATION AVAILABLE.

CHEMI CAL NAME LOG POW

PROPANE/I SOBUTANE/N- BUTANE 2. 8

68476 - 86 - 8

ETHYL ACETIC ESTER 0.6

141 - 78 - 6

1 - METHYOXY - 2 - PROPANOL - 0. 437

107 - 98 - 2

OTHER ADVERSE EFFECTS: NO INFORMATION AVAILABLE

----- 13. DI SPOSAL CONSI DERATI ONS -----

WASTE TREATMENT:

WASTE DISPOSAL METHODS:

THIS MATERIAL, AS SUPPLIED, IS A HAZARDOUS WASTE ACCORDING TO FEDERAL REGULATIONS (40 CFR 261).

CONTAMINATED PACKAGING: DO NOT RE-USE EMPTY CONTAINERS.

-----14. TRANSPORT INFORMATION -----

DOT GROUND:

CONSUMER COMMODITY ORM-D OR LIMITED QUANTITY

IATA: UN1950, AEROSOLS, FLAMMABLE, 2.1, LTD. QTY.

IMDG: UN1950, AEROSOLS, FLAMMABLE, 2.1, LTD. QTY.

----- 15. REGULATORY INFORMATION -----

INTERNATIONAL INVENTORIES:

CHEMI CAL NAME	TSCA	DSL/NDSL	EI NECS/ ELI NCS	ENCS	I ECSC	KECL	PICCS	AI CS
PETROLEUM DI STI LLATES	X	X	X	X	X	X	X	X
PROPANE/ I SOBUTANE/ N-BUTANE	X	X	X	NOT LI STED	X	X	X	X
ETHYL ACETIC ESTER	X	X	X	X	X	X	X	X
1 - METHYOXY 2 - PROPANOL	X	X	X	X	X	X	X	X

LEGEND:

TSCA: UNITED STATES TOXIC SUBSTANCES CONTROL ACT SECTION 8(B) INVENTORY

DSL/NDSL: CANADIAN DOMESTIC SUBSTANCES LIST/NON-DOMESTIC SUBSTANCES LIST

ELNECS/ELLNCS:

EUROPEAN INVENTORY OF EXISTING COMMERCIAL CHEMICAL SUBSTANCES/EU LIST OF NOTIFIED CHEMICAL SUBSTANCES

ENCS: JAPAN EXISTING AND NEW CHEMICAL SUBSTANCES

CHINA: CHINA INVENTORY OF EXISTING CHEMICAL SUBSTANCES

KECL: KOREAN EXISTING AND EVALUATED CHEMICAL SUBSTANCES

PICCS: PHILIPPINES INVENTORY OF CHEMICALS AND CHEMICAL SUBSTANCES

AICS: AUSTRALIAN INVENTORY OF CHEMICAL SUBSTANCES

U.S. FEDERAL REGULATIONS:

SARA 313:

SECTION 313 OF TITLE III OF THE SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT OF 1986 (SARA). THIS PRODUCT DOES NOT CONTAIN ANY CHEMICALS WHICH ARE SUBJECT TO THE REPORTING REQUIREMENTS OF THE ACT AND TITLE 40 OF THE CODE OF FEDERAL REGULATIONS, PART 372.

SARA 311/312 HAZARD CATEGORIES:

ACUTE HEALTH HAZARD: YES CHRONI C HEALTH HAZARD: NO

FIRE HAZARD: YES

SUDDEN RELEASE OF PRESSURE HAZARD: YES

REACTI VE HAZARD: NO

CLEAN WATER ACT:

THIS PRODUCT CONTAINS THE FOLLOWING SUBSTANCES WHICH ARE REGULATED POLLUTANTS PURSUANT TO THE CLEAN WATER ACT (40 CFR 122.21 AND 40 CFR 122.42):

CERCLA:

THIS MATERIAL, AS SUPPLIED, CONTAINS ONE OR MORE SUBSTANCES REGULATED AS A HAZARDOUS SUBSTANCE UNDER THE COMPREHENSIVE ENVIRONMENTAL RESPONSE COMPENSATION AND LIABILITY ACT (CERCLA) (40 CFR 302):

CHEMI CAL NAME HAZARDOUS EXTREMELY HAZARDOUS RQ SUBSTANCES RQS SUBSTANCES RQS

ETHYL ACETIC ESTER 5000 LB RQ 5000 LB FINAL RQ 141-78-6 RQ 2270 KG FINAL RQ

U. S. STATE REGULATIONS:

CALIFORNIA PROPOSITION 65:

THIS PRODUCT DOES NOT CONTAIN ANY KNOWN PROPOSITION 65 CHEMICALS.

U. S. STATE RIGHT-TO-KNOW REGULATIONS:

CHEMI CAL NAME NEW JERSEY MASSACHUSETTS PENNSYLVANI A

ETHYL ACETI C ESTER X X X

141-78-6

1-METHYOXY-2-PROPANOL X X X X

107-98-2

EPA PESTICIDE REGISTRATION NUMBER: NOT APPLICABLE

CANADA:

THIS PRODUCT HAS BEEN CLASSIFIED IN ACCORDANCE WITH THE HAZARD CRITERIA OF THE CONTROLLED PRODUCTS REGULATIONS (CPR) AND THE MSDS CONTAINS ALL THE INFORMATION REQUIRED BY THE CPR.

- A COMPRESSED GAS
- B FLAMMABLE AND COMBUSTIBLE MATERIAL
- D2 MATERIALS CAUSING OTHER TOXIC EFFECTS

-----16. OTHER INFORMATION -----

NFPA:

HEALTH HAZARD 2 FLAMMABI LI TY 4 I NSTABI LI TY 0 PHYSICAL AND CHEMICAL HAZARDS

HMIS:

HEALTH HAZARD 2 FLAMMABI LI TY 4 PHYSI CAL HAZARD 1 PERSONAL PROTECTION B

PREPARED BY: AMERICAN JETWAY 34136 MYRTLE STREET WAYNE. MI 48184

TEL.: 734 - 721 - 5930

ISSUING DATE: 17-APR-2015

REVISION DATE: 13-JUN-2015

REVISION NOTE: NO INFORMATION AVAILABLE

DI SCLAI MER:

THE INFORMATION PROVIDED ON THIS SDS IS CORRECT TO THE BEST OF OUR KNOWLEDGE. INFORMATION AND BELIEF AT THE DATE OF ITS PUBLICATION. THE INFORMATION GIVEN IS DESIGNED ONLY AS A GUIDE FOR SAFE HANDLING, USE, PROCESSING, STORAGE, TRANSPORTATION, DISPOSAL AND RELEASE AND IS NOT TO BE CONSIDERED AS A WARRANTY OR QUALITY SPECIFICATION. THE INFORMATION RELATES ONLY TO THE SPECIFIC MATERIAL DESIGNATED AND MAY NOT BE VALID FOR SUCH MATERIAL USED IN COMBINATION WITH ANY OTHER MATERIAL OR IN ANY PROCESS, UNLESS SPECIFIED IN THE TEXT.

Follow us on:









HOME | OUR CORE BUSINESS | PRODUCTS & INFORMATION BROCHURES & VIDEO GALLERY | CUSTOMER ORDER CENTER | CAREERS | CONTACT

Copyright © 20162016 Class C Solutions Group, a business of MSC Industrial Supply Co. | Privacy | Terms & Conditions | Last Posting: May 06, 2016

Sign In