






SECTION 1 - IDENTIFICATION

<b>Manufacturer:</b> Black Swan Mfg. Co. 4540 W. Thomas St. Chicago, IL 60651-3318 Tel.: 800-252-5796 Fax: 773-227-3705 Web Site : <a href="http://www.blackswanmfg.com">www.blackswanmfg.com</a> E-mail : <a href="mailto:info@blackswanmfg.com">info@blackswanmfg.com</a>	For any Transportation or Medical Chemical Emergencies call:  <p style="text-align: center;"><b>INFOTRAC</b></p> <p style="text-align: center;">(800) 535-5053 <b>OR</b> (352) 323-3500</p> <p style="text-align: center;">24 hours per day - 7 days a week</p>
<b>Product Name: No-Hub Sealant</b>	<b>Recommended Use:</b> A sealant specifically designed as a coating for cast iron pipe to improve leak-free sealing of no-hub couplings.

SECTION 2 – HAZARD(S) IDENTIFICATION

<p><b>Labels</b></p>  <p>Health Hazard Flammable</p>	<p style="text-align: center;"><b>NFPA</b></p> <div style="display: flex; justify-content: space-around;"> <div data-bbox="389 699 535 798"> <p><b>HEALTH HAZARD</b>            4 – Deadly            3 – Extreme Danger            2 – Hazardous            1 – Slight Hazardous            0 – Normal Material</p> </div> <div data-bbox="535 745 665 913">  </div> <div data-bbox="665 699 795 829"> <p><b>FIRE HAZARD</b>            Flash Points            4 – Below 73°F            3 – Below 100°F            2 – Above 100°F, Not exceeding 200°F            1 – Above 200°F            0 – Will not burn</p> </div> </div> <div style="display: flex; justify-content: space-around; margin-top: 10px;"> <div data-bbox="389 840 535 955"> <p><b>SPECIFIC HAZARD</b>            Oxidizer OX            Acid ACID            Alkali ALK            Corrosive COR            Use NO WATER            Radioactive </p> </div> <div data-bbox="665 840 795 976"> <p><b>REACTIVITY</b>            4 – May detonate            3 – Shock and heat may detonate            2 – Violent chemical change            1 – Unstable if heated            0 – Stable</p> </div> </div>	<p style="text-align: center;"><b>GHS Classification</b></p> <table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 50%; vertical-align: top;"> <p style="text-align: center;"><b>Health</b></p> <p>Acute Toxicity: Not Established            Skin Irritation: Not Established            Eye Irritation: Not Established            Skin Sensitization: NO</p> </td> <td style="width: 50%; vertical-align: top;"> <p style="text-align: center;"><b>Environmental</b></p> <p>Acute Aquatic Toxicity: Not Established            Chronic Aquatic Toxicity: Not Established</p> </td> </tr> <tr> <td colspan="2" style="text-align: center;"> <p><b>Physical</b></p> <p>Flammability: Cat. 2</p> </td> </tr> </table>	<p style="text-align: center;"><b>Health</b></p> <p>Acute Toxicity: Not Established            Skin Irritation: Not Established            Eye Irritation: Not Established            Skin Sensitization: NO</p>	<p style="text-align: center;"><b>Environmental</b></p> <p>Acute Aquatic Toxicity: Not Established            Chronic Aquatic Toxicity: Not Established</p>	<p><b>Physical</b></p> <p>Flammability: Cat. 2</p>	
<p style="text-align: center;"><b>Health</b></p> <p>Acute Toxicity: Not Established            Skin Irritation: Not Established            Eye Irritation: Not Established            Skin Sensitization: NO</p>	<p style="text-align: center;"><b>Environmental</b></p> <p>Acute Aquatic Toxicity: Not Established            Chronic Aquatic Toxicity: Not Established</p>					
<p><b>Physical</b></p> <p>Flammability: Cat. 2</p>						
<p style="text-align: center;"><b>Hazardous Statements</b></p> <p>H225: Highly flammable liquid and vapor          H304: May be fatal if swallowed and enters airways          H312: Harmful in contact with skin          H319: Causes serious eye irritation          H332: Harmful if inhaled          H335: May cause respiratory irritation          H336: May cause drowsiness or dizziness</p>		<p style="text-align: center;"><b>Precautionary Statements</b></p> <p>P102: Keep out of reach of children          P103: Read label before use          P210: Keep away from heat/sparks/open flames/hot surfaces – No smoking          P233/P235: Keep container tightly closed and cooled          P243: Take precautionary measures against static discharge          P261: Avoid breathing dust/fume/gas/mist/vapors/spray          P262: Do not get in eyes, on skin, or on clothing          P264: Wash thoroughly after handling          P270: Do not eat, drink or smoke when using this product          P271: Use only outdoors or in a well-ventilated area          P280/P284: Wear protective gloves/protective clothing/eye protection/face protection. Wear a NIOSH approved respirator for organic solvents.</p>				

SECTION 3 – COMPOSITION / INFORMATION ON INGREDIENTS

Chemicals	CAS#	EINECS#	REACH Pre-registration Number	Approx %
ETHYL ALCOHOL	64-17-5	200-578-6	N/A	25-30%
METHYL ALCOHOL	67-56-1	200-659-6	N/A	1-2%
ETHYL ACETATE	141-78-6	205-500-4	N/A	<1%
ACETONE	67-64-1	200-662-2	N/A	35-45%
POLYVINYL BUTYRAL	7723-18-5	N/A	N/A	10-20%

\*Unlisted ingredients are not classified as hazardous according to OSHA 1910.1200.

SECTION 4 – FIRST-AID MEASURES

<p><b>Inhalation:</b> Move into fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen and call physician.  <b>Skin:</b> Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water.  <b>Eyes:</b> Flush with water for 15 minutes. If irritation persists, get medical attention.  <b>Ingestion:</b> Give 1 or 2 glasses of water. DO NOT INDUCE VOMITING. Contact physician immediately.</p>
--

## GHS SAFETY DATA SHEET

### SECTION 5 – FIRE-FIGHTING MEASURES

**Fire Hazard:** Vapors may travel considerable distance to sources of ignition and flash back.  
**Combustion Products:** None.  
**Extinguishing Media:** Foam, Carbon Dioxide, Dry Chemical.  
**Unsuitable Extinguishing Media:** None Known.  
**Protective Equipment:** Self-contained breathing apparatus {(SCBA), MSHA/NIOSH}. Full protective gear.  
**Special Fire Fighting Procedures:** Evacuate enclosed areas, stay upwind. Closed or confined quarters require self-contained breathing apparatus, positive pressure hose masks or airline masks. Use agents appropriate for surrounding fires.

### SECTION 6 – ACCIDENTAL RELEASE MEASURES

**Personal Precautions:** None.  
**Protective Equipment:** Wear suitable respiratory protective equipment.  
**Emergency Procedures:** None.  
**Environmental Precautions:** Avoid runoff into storm sewers, ditches and waterways.  
**Methods for Cleaning Up:** Absorb with suitable inert material. Remove all sources of ignition.

### SECTION 7 – HANDLING AND STORAGE

<u>Handling</u>	<u>Storage</u>
Use good personal hygiene practice. Avoid inhalation of vapors and personal contact with the product. Repeated and prolonged overexposure to solvents may cause brain and nervous system damage. Concentrating and inhaling the contents may be harmful or fatal.	Keep and store in a cool, dry place from sources of ignition. Ground during transfer. Keep container tightly closed when not in use. <b>Incompatible Materials:</b> Strong oxidizing agents, strong acids.

### SECTION 8 – EXPOSURE CONTROLS / PERSONAL PROTECTION

<u>Hazardous Chemicals</u>	<u>ACGIH-TLV</u>	<u>ACGIH-STEL</u>	<u>OSHA-PEL</u>
ETHYL ALCOHOL	1000 ppm	N/A	1000 ppm
METHYL ALCOHOL	200 ppm	N/A	200 ppm
ETHYL ACETATE	400 ppm	N/A	400 ppm
ACETONE	500 ppm	750 ppm	1000 ppm

**Engineering Controls:** A source of running water to flush or wash the eyes and skin in case of contact.  
**Ventilation:** Mechanical.  
**Personal Protective Equipment – Respiratory:** If use conditions generate vapors or mists, wear a NIOSH-approved respirator appropriate for those emission levels. Appropriate respirators may be a full face piece or a half mask air-purifying cartridge respirator equipped for organic vapors/mists, a self-contained breathing apparatus in the pressure demand mode, or a supplied-air respirator.  
**Personal Protective Equipment – Skin:** Impermeable gloves. Chemical resistant coveralls.  
**Personal Protective Equipment – Eyes:** Safety glasses with side shields or chemical goggles.

### SECTION 9 – PHYSICAL & CHEMICAL PROPERTIES

<b>Appearance:</b> Amber Viscous Liquid	<b>Flash Point:</b> 65°F (T.C.C.)	<b>Vapor Pressure:</b> Not Established
<b>Odor:</b> Characteristic Solvent	<b>Specific Gravity:</b> Approx. 0.70	<b>Flammability:</b> Not Established
<b>pH:</b> Not Established	<b>Solubility (H2O):</b> Insoluble	<b>Flammability Limits:</b> LEL – 0.9%
<b>Melting Point:</b> Not Established	<b>Evaporation Rate:</b> > 1.0	UEL – 7.0%
<b>Freezing Point:</b> Not Established	<b>Vapor Density:</b> > 1.0	
<b>Boiling Point:</b> 170°F	<b>VOC:</b> 250 g/l	

# GHS SAFETY DATA SHEET

## SECTION 10 – STABILITY AND REACTIVITY

**Stability:** Stable.

**Hazardous polymerization:** Will not occur.

**Conditions to avoid:** Sparks, open flames, hot surfaces and strong oxidizing agents.

**Incompatible materials:** Strong oxidizing agents, strong acids.

**Hazardous decomposition products:** Carbon Monoxide, Carbon Dioxide

## SECTION 11 – TOXICOLOGICAL INFORMATION

<u>Hazardous Chemicals</u>	<u>Toxicity</u>	
	<u>LD<sub>50</sub></u>	<u>LC<sub>50</sub></u>
ETHYL ALCOHOL	N/A	N/A
METHYL ALCOHOL	N/A	N/A
ETHYL ACETATE	N/A	N/A
ACETONE	N/A	N/A
POLYVINYL BUTYRAL	N/A	N/A

**Likely Routes of Exposure:** Inhalation, Skin Contact, Eye Contact and Ingestion.

**Symptoms and Effect - Inhalation:** It is a respiratory tract irritant and anesthetic and causes central nervous system depression (e.g. headache, drowsiness, dizziness, loss of coordination & fatigue). **Skin Contact:** May cause mild skin irritation. Prolonged or repeated contact may cause redness, burning, and drying and cracking of the skin. **Eye Contact:** May cause mild eye irritation. Direct contact with the liquid or exposure to vapors or mists may cause stinging, tearing and redness. **Ingestion:** Ingestion of excessive quantities may cause irritation of the digestive tract and signs of nervous system depression.

**Long-Term Effect:** None known.

**Pre-Existing Conditions:** Any pre-existing heart or skin condition or an impaired lung function.

## SECTION 12 – ECOLOGICAL INFORMATION

**Ecotoxicity:** None known.

**Persistence & Degradability:** None known.

**Bioaccumulative Potential:** None known.

**Mobility in soil:** In normal use, emission of Volatile Organic Compounds (VOC's) to the air takes place, typically at a rate of  $\leq 250$  g/l.

## SECTION 13 – DISPOSAL CONSIDERATION

Dispose of product or container in accordance with federal, state or local regulations.

## SECTION 14 – TRANSPORTATION INFORMATION

### Shipping Information

**Shipping Name:** Adhesives, Containing a Flammable Liquid

**Hazardous Class:** 3

**I.D. Number:** UN1133

**Packing Group:** II

**Label Required:** Flammable Liquid

**Marine Pollutant:** No

**Exception to the rule:** If the package that contains the hazardous material is in a small consumer size (Less than 1L), then the rules that apply to shipping hazardous materials do not apply. This is called an "Exception".

**This is classified as Consumer Commodity ORM-D.**

## SECTION 15 – REGULATORY INFORMATION

**Precautionary Label Information:** Flammable, and Health Hazard.

**Risk Phrases:** R10-Flammable. R36/37-Irritant to eyes and respiratory system.

**Safety Phrases:** S2-Keep out of reach of children. S9-Keep container in a well-ventilated place. S16-Keep away from sources of ignition-No smoking. S25-Avoid contact with eyes. S26-In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. S33-Take precautionary measures against static discharges.

## SECTION 16 – OTHER INFORMATION

Information on this form is furnished solely for the purpose of compliance with the Occupational Safety and Health Act and shall not be used for any other purpose. Black Swan Mfg. Co. urges the customers receiving this Material Safety Data Sheet to study it carefully to become aware of the hazards, if any, of the product involved. In the interest of safety, you should notify your employees, agents and contractors of the information on the sheets.

DATE: 01/01/2017