



SAFETY DATA SHEET

1. Identification

Product identifier RTV Silicone Sealant - White (pressurized)

Other means of identification

Product code 14056

Recommended use Sealant and adhesive

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Manufactured or sold by:

Company name CRC Industries, Inc.
Address 885 Louis Dr.
Warminster, PA 18974 US

Telephone

General Information 215-674-4300

Technical Assistance 800-521-3168

Customer Service 800-272-4620

24-Hour Emergency (CHEMTREC) 800-424-9300 (US)
703-527-3887 (International)

Website www.crcindustries.com

2. Hazard(s) identification

Physical hazards Gases under pressure Compressed gas

Health hazards Skin corrosion/irritation Category 2
Serious eye damage/eye irritation Category 2B
Carcinogenicity Category 2

Environmental hazards Hazardous to the aquatic environment, acute hazard Category 3
Hazardous to the aquatic environment, long-term hazard Category 3

OSHA defined hazards Not classified.

Label elements



Signal word Warning

Hazard statement Contains gas under pressure; may explode if heated. Causes skin irritation. Causes eye irritation. Suspected of causing cancer. Harmful to aquatic life. Harmful to aquatic life with long lasting effects.

Precautionary statement

Prevention Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use with adequate ventilation. Open doors and windows or use other means to ensure a fresh air supply during use and while product is drying. If you experience any symptoms listed on this label, increase ventilation or leave the area. Wash hands thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection. Avoid release to the environment.

Response If on skin: Wash with plenty of water. If skin irritation occurs: Get medical attention. Take off contaminated clothing and wash before reuse. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention. If exposed or concerned: Get medical attention.

Storage Store locked up. Protect from sunlight. Store in a well-ventilated place. Exposure to high temperature may cause can to burst.

Disposal	Dispose of contents/container in accordance with local/regional/national regulations.
Hazard(s) not otherwise classified (HNOC)	None known.

Supplemental information

91.92% of the mixture consists of component(s) of unknown acute hazards to the aquatic environment. 91.92% of the mixture consists of component(s) of unknown long-term hazards to the aquatic environment.

When heated to temperature above 300°F/150°C in the presence of air, product may form formaldehyde vapors. When exposed to water or humid air, product evolves acetic acid (HOAc).

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Polydimethylsiloxane, hydroxy-terminated		70131-67-8	>= 60
Amorphous silica		7631-86-9	5 - 10
Distillates (petroleum), Hydrotreated Middle		64742-46-7	5 - 10
Polydimethylsiloxane		63148-62-9	5 - 10
Ethyltriacetoxysilane		17689-77-9	1 - 5
Methyltriacetoxysilane		4253-34-3	1 - 5
Aluminium		7429-90-5	1 - 3
Nitrogen		7727-37-9	1 - 3
Titanium dioxide		13463-67-7	1 - 3
Carbon black		1333-86-4	< 1

Specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation	Move to fresh air. Get medical attention immediately.
Skin contact	Remove contaminated clothing immediately and wash skin with soap and water. If skin irritation occurs: Get medical advice/attention. Wash contaminated clothing before reuse.
Eye contact	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.
Ingestion	In the unlikely event of swallowing contact a physician or poison control center. Rinse mouth. Get medical attention.
Most important symptoms/effects, acute and delayed	Irritation of eyes and mucous membranes. Exposed individuals may experience eye tearing, redness, and discomfort. Skin irritation. May cause redness and pain.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.
General information	IF exposed or concerned: Get medical advice/attention. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

5. Fire-fighting measures

Suitable extinguishing media	Dry chemical, CO2, or water spray.
Unsuitable extinguishing media	None known.
Specific hazards arising from the chemical	Contents under pressure. During fire, gases hazardous to health may be formed. When heated to temperature above 300°F/150°C in the presence of air, product may form formaldehyde vapors. When exposed to water or humid air, product evolves acetic acid (HOAc).
Special protective equipment and precautions for firefighters	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. Wear self-contained breathing apparatus and protective clothing.
Fire-fighting equipment/instructions	In case of fire: Stop leak if safe to do so. Cool containers exposed to heat with water spray and remove container, if no risk is involved.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Use a positive-pressure air-supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air-purifying respirators may not provide adequate protection. Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Eliminate all ignition sources (no smoking, flares, sparks or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Stop the flow of material, if this is without risk. Collect spillage. Prevent entry into waterways, sewer, basements or confined areas. Shovel up and place in a container for salvage or disposal. Dispose of saturated absorbent or cleaning materials appropriately, since spontaneous heating may occur. Final cleaning may require use of steam, solvents or detergents.

Environmental precautions

Avoid release to the environment. Contact local authorities in case of spillage to drain/aquatic environment. Prevent further leakage or spillage if safe to do so. Do not contaminate water. Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. Use caution around energized equipment. The metal container will conduct electricity if it contacts a live source. This may result in injury to the user from electrical shock and/or flash fire. Avoid breathing vapor. Avoid contact with eyes, skin, and clothing. Use only in well-ventilated areas. Should be handled in closed systems, if possible. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Observe good industrial hygiene practices. Avoid release to the environment. Do not empty into drains. For product usage instructions, please see the product label.

Conditions for safe storage, including any incompatibilities

Level 1 Aerosol.

Contents under pressure. Do not expose to heat or store at temperatures above 120°F/49°C as can may burst. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. Store in a well-ventilated place. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value	Form
Aluminium (CAS 7429-90-5)	PEL	5 mg/m ³ 15 mg/m ³	Respirable dust. Total dust.
Carbon black (CAS 1333-86-4)	PEL	3.5 mg/m ³	
Distillates (petroleum), Hydrotreated Middle (CAS 64742-46-7)	PEL	5 mg/m ³	Mist.
Titanium dioxide (CAS 13463-67-7)	PEL	15 mg/m ³	Total dust.

US. OSHA Table Z-3 (29 CFR 1910.1000)

Components	Type	Value
Amorphous silica (CAS 7631-86-9)	TWA	0.8 mg/m ³ 20 mppcf

US. ACGIH Threshold Limit Values

Components	Type	Value	Form
Aluminium (CAS 7429-90-5)	TWA	1 mg/m ³	Respirable fraction.
Carbon black (CAS 1333-86-4)	TWA	3 mg/m ³	Inhalable fraction.

US. ACGIH Threshold Limit Values

Components	Type	Value	Form
Distillates (petroleum), Hydrotreated Middle (CAS 64742-46-7)	TWA	5 mg/m3	Inhalable fraction.
Titanium dioxide (CAS 13463-67-7)	TWA	10 mg/m3	

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value	Form
Aluminium (CAS 7429-90-5)	TWA	5 mg/m3	Welding fume or pyrophoric powder.
		5 mg/m3	Respirable.
		10 mg/m3	Total
Amorphous silica (CAS 7631-86-9)	TWA	6 mg/m3	
Carbon black (CAS 1333-86-4)	TWA	0.1 mg/m3	
Distillates (petroleum), Hydrotreated Middle (CAS 64742-46-7)	STEL	10 mg/m3	Mist.
	TWA	5 mg/m3	Mist.

Biological limit values	No biological exposure limits noted for the ingredient(s).
Exposure guidelines	Occupational Exposure Limits are not relevant to the current physical form of the product.
Appropriate engineering controls	Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash facilities and emergency shower must be available when handling this product.
Individual protection measures, such as personal protective equipment	
Eye/face protection	Wear safety glasses with side shields (or goggles).
Skin protection	
Hand protection	Wear protective gloves such as: Nitrile. Butyl rubber.
Other	Wear appropriate chemical resistant clothing.
Respiratory protection	In case of insufficient ventilation, wear suitable respiratory equipment. Air monitoring is needed to determine actual employee exposure levels.
Thermal hazards	Wear appropriate thermal protective clothing, when necessary.
General hygiene considerations	When using do not smoke. Keep away from food and drink. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties**Appearance**

Physical state	Solid.
Form	Paste.
Color	White.
Odor	Acetic acid.
Odor threshold	Not available.
pH	Not available.
Melting point/freezing point	Not available.
Initial boiling point and boiling range	680 °F (360 °C) estimated
Flash point	> 212 °F (> 100 °C) Tag Closed Cup
Evaporation rate	Not available.
Flammability (solid, gas)	Not available.
Upper/lower flammability or explosive limits	
Flammability limit - lower (%)	Not available.

Flammability limit - upper (%)	Not available.
Vapor pressure	76514.4 hPa estimated
Vapor density	Not available.
Relative density	1.01
Solubility (water)	Not available.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	500 °F (260 °C) estimated
Decomposition temperature	Not available.
Viscosity (kinematic)	Not available.
Percent volatile	< 3 %

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
Conditions to avoid	Heat, flames and sparks. Avoid temperatures exceeding the flash point. Contact with incompatible materials. When exposed to water or humid air, product evolves acetic acid (HOAc). When heated to temperature above 300°F/150°C in the presence of air, product may form formaldehyde vapors.
Incompatible materials	Strong oxidizing agents. Moist air. Water, moisture.
Hazardous decomposition products	Carbon oxides. Traces of incompletely burned carbon compounds. Silicone dioxide. Formaldehyde. Metal oxides. Nitrogen oxides (NOx). Sulfur oxides. Chlorine compounds.

11. Toxicological information

Information on likely routes of exposure

Ingestion	Expected to be a low ingestion hazard.
Inhalation	Inhalation of fumes may result in metal fume fever, a flu-like illness with symptoms of metallic taste, fever and chills, aches, chest tightness, and cough. Material is not likely to present an inhalation hazard at ambient conditions. However, if material is heated or high vapor concentrations are attained, central nervous system depression may occur, which is characterized by drowsiness, dizziness, confusion or loss of coordination.
Skin contact	Causes skin irritation.
Eye contact	Causes eye irritation.

Symptoms related to the physical, chemical and toxicological characteristics Irritation of eyes. Exposed individuals may experience eye tearing, redness, and discomfort. Skin irritation. May cause redness and pain.

Information on toxicological effects

Acute toxicity Not available.

Product	Species	Test Results
RTV Silicone Sealant - White (pressurized)		
Acute		
<i>Inhalation</i>		
LC50	Rabbit	371.2399 mg/l, 4 hours estimated

* Estimates for product may be based on additional component data not shown.

Skin corrosion/irritation	Causes skin irritation.
Serious eye damage/eye irritation	Causes eye irritation.
Respiratory sensitization	Not available.
Skin sensitization	This product is not expected to cause skin sensitization.
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.
Carcinogenicity	Suspected of causing cancer.

IARC Monographs. Overall Evaluation of Carcinogenicity

Amorphous silica (CAS 7631-86-9)
Carbon black (CAS 1333-86-4)

3 Not classifiable as to carcinogenicity to humans.
2B Possibly carcinogenic to humans.

Reproductive toxicity	This product is not expected to cause reproductive or developmental effects.
Specific target organ toxicity - single exposure	Not classified.
Specific target organ toxicity - repeated exposure	Not classified.
Aspiration hazard	Not likely, due to the form of the product.
Chronic effects	Prolonged exposure may cause chronic effects.

12. Ecological information

Ecotoxicity Harmful to aquatic life with long lasting effects. Accumulation in aquatic organisms is expected.

Product	Species	Test Results
RTV Silicone Sealant - White (pressurized)		
Aquatic		
Fish	LC50	Fish
		95.237 mg/l, 96 hours estimated
Components		
Species		
Test Results		
Aluminium (CAS 7429-90-5)		
Aquatic		
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss)
		0.16 mg/l, 96 hours
Polydimethylsiloxane (CAS 63148-62-9)		
Aquatic		
Fish	LC50	Channel catfish (Ictalurus punctatus)
		2.36 - 4.15 mg/l, 96 hours
Titanium dioxide (CAS 13463-67-7)		
Aquatic		
Crustacea	EC50	Water flea (Daphnia magna)
		> 1000 mg/l, 48 hours
Fish	LC50	Mummichog (Fundulus heteroclitus)
		> 1000 mg/l, 96 hours

* Estimates for product may be based on additional component data not shown.

Persistence and degradability Not available.

Bioaccumulative potential Not available.

Partition coefficient n-octanol / water (log Kow)

Nitrogen 0.67

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal of waste from residues / unused products This product, in its present state, when discarded or disposed of, is not a hazardous waste according to Federal regulations (40 CFR 261.4 (b)(4)). Under RCRA, it is the responsibility of the user of the product to determine, at the time of disposal, whether the product meets RCRA criteria for hazardous waste. Consult authorities before disposal. Contents under pressure. Do not puncture, incinerate or crush. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose in accordance with all applicable regulations.

Hazardous waste code Not regulated.

Contaminated packaging Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied.

14. Transport information

DOT

UN number UN1950
UN proper shipping name Aerosols, non-flammable, Limited Quantity

Transport hazard class(es)	
Class	2.2
Subsidiary risk	-
Label(s)	2.2
Packing group	Not applicable.
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Special provisions	Not available.
Packaging exceptions	306
Packaging non bulk	None
Packaging bulk	None

IATA

UN number	UN1950
UN proper shipping name	Aerosols, non-flammable, Limited Quantity
Transport hazard class(es)	
Class	2.2
Subsidiary risk	-
Packing group	Not applicable.
Environmental hazards	No.
ERG Code	2L
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Other information	
Passenger and cargo aircraft	Allowed.
Cargo aircraft only	Allowed.

IMDG

UN number	UN1950
UN proper shipping name	AEROSOLS, LIMITED QUANTITY
Transport hazard class(es)	
Class	2
Subsidiary risk	-
Packing group	Not applicable.
Environmental hazards	
Marine pollutant	No.
EmS	Not available.
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.

15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.
All components are on the U.S. EPA TSCA Inventory List.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

SARA 304 Emergency release notification

Not regulated.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

US EPCRA (SARA Title III) Section 313 - Toxic Chemical: Listed substance

Not listed.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

CERCLA Hazardous Substances: Reportable quantity

Not listed.

Spills or releases resulting in the loss of any ingredient at or above its RQ require immediate notification to the National Response Center (800-424-8802) and to your Local Emergency Planning Committee.

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act (SDWA) Not regulated.

Food and Drug Administration (FDA) Not regulated.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Section 311/312 Hazard categories
Immediate Hazard - Yes
Delayed Hazard - Yes
Fire Hazard - No
Pressure Hazard - Yes
Reactivity Hazard - No

SARA 302 Extremely hazardous substance No

US state regulations

US. New Jersey Worker and Community Right-to-Know Act

Aluminium (CAS 7429-90-5)
Carbon black (CAS 1333-86-4)
Nitrogen (CAS 7727-37-9)
Titanium dioxide (CAS 13463-67-7)

US. Massachusetts RTK - Substance List

Aluminium (CAS 7429-90-5)
Amorphous silica (CAS 7631-86-9)
Nitrogen (CAS 7727-37-9)
Titanium dioxide (CAS 13463-67-7)

US. Pennsylvania Worker and Community Right-to-Know Law

Aluminium (CAS 7429-90-5)
Amorphous silica (CAS 7631-86-9)
Carbon black (CAS 1333-86-4)
Distillates (petroleum), Hydrotreated Middle (CAS 64742-46-7)
Nitrogen (CAS 7727-37-9)
Titanium dioxide (CAS 13463-67-7)

US. Rhode Island RTK

None.

US. California Proposition 65

WARNING: This product contains a chemical known to the State of California to cause cancer.

US - California Proposition 65 - CRT: Listed date/Carcinogenic substance

Carbon black (CAS 1333-86-4) Listed: February 21, 2003

Volatile organic compounds (VOC) regulations

EPA

VOC content (40 CFR 51.100(s)) < 3 %

Consumer products (40 CFR 59, Subpt. C) Not regulated

State

Consumer products This product is regulated as a Sealant and Caulking Compound. This product is compliant for use in all 50 states.

VOC content (CA) < 3 %

VOC content (OTC) < 3 %

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No

Country(s) or region	Inventory name	On inventory (yes/no)*
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date	05-20-2014
Prepared by	Allison Cho
Version #	01
Further information	Not available.
HMIS® ratings	Health: 1* Flammability: 1 Physical hazard: 0 Personal protection: B
NFPA ratings	Health: 1 Flammability: 1 Instability: 0
Disclaimer	The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. This information is accurate to the best of CRC Industries' knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label. For further clarification of any information contained on this (M)SDS consult your supervisor, a health & safety professional, or CRC Industries.