

UPC- 044579410334 (MELON) ←

Chemisico
 Division of United Industries
 P. O. Box 142642
 St. Louis, MO 63114-0642

Hazardous Material Identification System - (HMIS)	
HEALTH - 0	REACTIVITY - 0
FLAMMABILITY - 2	PERSONAL -

Material Safety Data Sheet

Complies with OSHA's Hazard Communication Standard, 29 CFR 1910.1200

I Trade Name: DG Guarantee Potpourri Air Fresheners (Floral Spring/Vanilla Scent/Cinnamon Apple)																			
Product Type: Aerosol Air Fresheners																			
Product Item Number: 41020/41021/41022		Formula Code Number:																	
EPA Registration Number	Manufacturer	Emergency Telephone Numbers																	
NA	Chemisico Division of United Industries Corporation 8494 Chapin Industrial Drive St. Louis, MO 63114	For Chemical Emergency: 1-800-633-2873 For Information: 1-800-678-9258 Prepared by: Charlie Duckworth Date Prepared: October 22, 2004																	
II Hazards Ingredient/Identity Information		III Physical and Chemical Characteristics																	
<table border="0"> <thead> <tr> <th>Chemical</th> <th>%</th> <th>OSHA PEL</th> <th>ACGIH TLV</th> </tr> </thead> <tbody> <tr> <td>Isopropyl alcohol ppm CAS #67-63-0</td> <td>1.00</td> <td>400 ppm</td> <td>500</td> </tr> <tr> <td>Mineral Spirits ppm CAS 8052-41-3</td> <td>2.30</td> <td>100 ppm</td> <td>100</td> </tr> <tr> <td>Hydrocarbon Propellant blend CAS #75-28-5/106-97-8/74-98-6</td> <td>22.00</td> <td>NE</td> <td>NE</td> </tr> </tbody> </table>	Chemical	%	OSHA PEL	ACGIH TLV	Isopropyl alcohol ppm CAS #67-63-0	1.00	400 ppm	500	Mineral Spirits ppm CAS 8052-41-3	2.30	100 ppm	100	Hydrocarbon Propellant blend CAS #75-28-5/106-97-8/74-98-6	22.00	NE	NE	Appearance & Odor: Light mist spray with fragrance Boiling Point: NA Melting Point: NA Vapor Pressure: 110 PSIG at 54°C/130°F Specific Gravity: 0.993 (H ₂ O=1) Vapor Density: Greater than 1 (Air = 1) Solubility in Water: Greater than 90% Evaporation Rate: Less than 1 (butyl acetate = 1)		
Chemical	%	OSHA PEL	ACGIH TLV																
Isopropyl alcohol ppm CAS #67-63-0	1.00	400 ppm	500																
Mineral Spirits ppm CAS 8052-41-3	2.30	100 ppm	100																
Hydrocarbon Propellant blend CAS #75-28-5/106-97-8/74-98-6	22.00	NE	NE																
IV Fire and Explosive Hazards Data		V Reactivity Data																	
Flash Point: >200 F (TCC) (liquid portion) Flame Extension: 0-inches (Level 1 Aerosol) Flammable Limits: NA Autoignition Temperature: NA Fire Extinguishing Media: Water fog, Carbon dioxide, Dry chemical Decomposition Temperature: NA Special Fire-Fighting Procedures: Keep cans cool. Use equipment or shielding to protect personnel against bursting, rupturing or venting cans. Unusual Fire & Explosion Hazards: At elevated temperatures (over 54° C/130° F), cans may vent, rupture or burst. Also see Section V.		Stability: Stable Polymerization: Will not occur Conditions to Avoid: Temperatures over 130° F Incompatible Materials: NA Hazardous Decomposition or Byproducts: Carbon dioxide, carbon monoxide																	
VI Health Hazard Data		VII Precautions for Safe Handling and Use																	
Special Notes: Have the product container with you when calling a Poison Control Center or doctor, or going for treatment. Health conditions Aggravated by Exposure: None known Ingredients listed by NTP, OSHA, or IARC as Carcinogens or Potential Carcinogens: None		Steps to be Taken in Case Material is Released or Spilled: Avoid breathing vapors. Avoid contact with liquid. Remove ignition sources. Soak up spills with absorbent material. Waste Disposal: Do not puncture or incinerate containers. If empty: Place in trash or offer for recycling if available. If partly filled: Call local solid waste agency or 1-800-CLEANUP for disposal instructions. Handling & Storage Precautions: Do not store where temperatures can exceed 54° C/130° F.																	
VIII Control Measures		IX Transportation Data																	
Read and follow label directions. They are your best guide to using this product effectively, and give necessary safety precautions to protect your health.		DOT: Consumer Commodity, Hazard Class ORM-D (Limited Quantity Exception) IMDG: Aerosols (Maximum 1 Liter), Hazard Class 2, UN-1950, Packing Group III IATA: Aerosols, Flammable (Each Not Exceeding 1 Liter Capacity), Packing Group III (Each Not Exceeding 1 Liter Capacity), Hazard Class 2.1, UN-1950, Packing Group III Hazard Class 2.1, UN-1950, Packing Group III																	

The information and statements herein are believed to be reliable but are not to be construed as warranty or representation for which we assume legal responsibility. Users should undertake sufficient verification and testing to determine the suitability for their own particular purpose of any information or products referred to herein. NO WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE IS MADE.