

S A F E T Y D A T A S H E E T

ELGEN DUCT SEALER

Page 1

SECTION I - PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: ELGEN DUCT SEALER
MANUFACTURERS' ADDRESS: Elgen Manufacturing Company INC.
10 Railroad Ave, Closter NJ 07624
EMERGENCY PHONE: INFOTRAC: (800) 535-5053
BUSINESS HOURS: 6AM - 6PM
REVISION DATE: 04/01/2016
INFORMATION PHONE: (800)503-9805
REVISION #: 3-15
PREPARED BY: IT Department. Supersedes all previous
DOT HAZARD CLASS: Not Hazardous - UN Number: N/A

SECTION II - HAZARDOUS INGREDIENTS / SARA III INFORMATION

HMIS Ratings: Health: 1 Flammability: 0 Reactivity: 0 Personal Protective Equipment: B

REPORTABLE COMPONENTS

CAS NUMBER

Weight %

None

SECTION III – COMPOSITION/INFORMATION ON INGREDIENTS

PROPRIETARY COMPONENT	CAS NUMBER	CONCENTRATION
Trade Secret	Proprietary Blend	<40%

SECTION IV – FIRST AID MEASURES

INHALATION: No first aid is normally needed, however, seek medical attention.

SKIN: Remove contaminated clothing and shoes. Wash thoroughly with water and soap. If irritation occurs, consult a physician.

EYES: Flush with a gentle stream of water for at least 15 minutes. If irritation occurs, consult a physician

INGESTION: no known cases – seek medical attention

SECTION V - FIRE-FIGHTING MEASURES

FLASH POINT None

FIRE AND EXPLOSION HAZARD Closed containers exposed to extreme heat may rupture due to pressure build up

EXTINGUISHING MEDIA Use water, dry chemicals or CO₂

FIRE FIGHTING INSTRUCTIONS Water may be used to cool exposed containers.

SECTION VI – ACCIDENTAL RELEASE MEASURES

SPILL CLEANUP: : Scrape or shovel material into suitable containers. Wipe up remaining material with damp rags. Prevent spilled material from entering sewers, storm drains or any authorized treatment, drainage system and/or natural waterways.

ACCIDENTAL RELEASE MEASURES: Try to prevent the material from entering drains or water courses.

SECTION VII – HANDLING AND STORAGE

HANDLING: Protect material from freezing.

STORAGE: Keep in a dry, cool place, protect material from freezing.

S A F E T Y D A T A S H E E T

ELGEN DUCT SEALER

Page 2

SECTION VIII – EXPOSURE CONTROLS/PERSONAL PROTECTION

- ENGINEERING CONTROLS :** Use only in area provided with appropriate exhaust ventilation.
- EYE PROTECTION :** General mechanical ventilation may be sufficient to keep product vapor concentrations within specified time-weight TLV ranges. If general ventilation proves inadequate to maintain vapor concentrations, supplemental local exhaust may be required.
- SKIN PROTECTION :** Protection gloves
- RESPIRATORY PROTECTION :** For emergency or when working in confined areas use self-contained breathing apparatus or supplied air respiratory protection. In other circumstances involving potential overexposure, use NIOSH/MSHA-approved organic vapor respirator. Respiratory protection must be in accordance with 29CFR 1910.134.

SECTION IX - PHYSICAL / CHEMICAL PROPERTIES

FORM	Paste	SPECIFIC GRAVITY	(H2O=1) 1.49
COLOR	Grey/White	BOILING POINT	212°F
ODOR	Slight, characteristic	VAPOR PRESSURE (MM HG)	760mm@100°C
VAPOR DENSITY	(AIR=1) <1	PERCENT VOLATILE BY WEIGHT	30.7%
METHOD	ASTM D 792	VOLATILE ORGANIC COMPOUNDS (VOC)	0.0 g/L
WATER SOLUBILITY	Soluble		

SECTION X – STABILITY AND REACTIVITY DATA

- CONDITIONS TO AVOID :** N/A
- INCOMPATIBILITY :** Salts and strong acids may cause reaction.
- DECOMPOSITION :** N/A
- POLYMERIZATION :** Polymerization will not occur.
- STABILITY :** Stable

SECTION XI – TOXICOLOGICAL INFORMATION

- SKIN :** May cause irritation upon prolonged or repeated contact.
- EYES :** May be irritating to eyes.
- INHALATION :** N/A

SECTION XII – ECOLOGICAL INFORMATION

- ECOTOXICITY:** No ecotoxicity data was found for the product
- ENVIRONMENTAL FATE:** No environmental information found for this product

SECTION XIII – DISPOSAL CONSIDERATIONS

Consult with the US EPA Guidelines listed in 40 CFR Part 261.3 for the classifications of hazardous waste prior to disposal. Furthermore, consult with your state and local waste requirements or guidelines, if applicable, to ensure compliance. Arrange disposal in accordance to the EPA and/or state and local guidelines.

S A F E T Y D A T A S H E E T

ELGEN DUCT SEALER

Page 3

SECTION XIV – TRANSPORT INFORMATION

DOT HAZARD CLASS	Not Hazardous
UN NUMBER	N/A
PACKING GROUP	N/A
SHIPPING NAME	N/A

SECTION XV –REGULATORY INFORMATION

This product is considered non-hazardous under the OSHA Hazard Communication Standard 29 CFR 1910.1200.

EMERGENCY PLANNING AND COMMUNITY RIGHT-TO-KNOW (SARA TITLE III):

Section 311/312 Categorizations (40 CFR 370): Immediate (Acute) Health Hazard.

Section 313 Information (40 CFR 372) – Toxic Chemicals List: This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR 372:

Toxic Substances Control Act (TSCA): All components of this product are on the TSCA Inventory or are exempt from TSCA Inventory requirements.

CALIFORNIA PROPOSITION 65 (Safe Drinking Water and Toxic Enforcement Act of 1986): This product may contain trace amounts of chemicals known to the State of

California to cause cancer and birth defects or other reproductive harm.

SECTION XVI –OTHER INFORMATION

CREATION DATE	06/10/2009
REVISION DATE	04/01/2016
REVISION NOTE	SDS - 16 Section
AUTHOR	IT Department

All the information above is believed to be accurate and represents the best information currently available to us. However, we make no warranty of merchantability or any other warranty, express or implied, with respect to such information, and we assume no liability resulting from its use. Users should make their own investigations to determine the suitability of the information for their particular purposes. In no event shall Elgen Manufacturing be liable for any claims, losses, or damages of any third party or for lost profits or any special, indirect, incidental, consequential or exemplary damages, howsoever arising, even if Elgen Manufacturing has been advised of the possibility of such damages.