



# SAFETY DATA SHEET

Revision Date 10-Apr-2015

Version 1

## 1. IDENTIFICATION

### Product identifier

**Product Name** Gumout Jet Spray Carb and Choke Cleaner

### Other means of identification

**Product Code** 600951  
**Document** SKU: 800002230, 800002231, 800002241  
**Synonyms** None

### Recommended use of the chemical and restrictions on use

**Recommended Use** Carburetor Cleaner Consumer Use  
**Uses advised against** All other applications

### Details of the supplier of the safety data sheet

<u>Supplier Address</u>	<u>Manufacturer Address</u>	<u>Distributor</u>
ITW Global Brands 6925 Portwest Dr., Suite 100 Houston, TX 77024		
<b>Company Phone Number</b>	1-855-888-1988	
<b>24 Hour Emergency Phone Number</b>	(CHEMTREC) 1-800-424-9300 or 1-703-527-3887 (U.S.) (RMPDC) 1-877-504-9352 (U.S.)	
<b>E-mail address</b>	SDS@itwgb.com	

## 2. HAZARDS IDENTIFICATION

### Classification

#### **OSHA Regulatory Status**

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

**NOTE: This product is a consumer product and is labeled in accordance with the US Consumer Product Safety Commission regulations which take precedence over OSHA Hazard Communication labeling. The actual container label will not include the label elements below. The labeling below applies to industrial/professional products.**

Serious eye damage/eye irritation	Category 2
Reproductive toxicity	Category 2
Specific target organ toxicity (single exposure)	Category 3
Specific target organ toxicity (repeated exposure)	Category 2
Flammable aerosols	Category 1
Gases under pressure	Compressed gas

### Label elements

#### **Emergency Overview**

#### **Danger**

Causes serious eye irritation  
Suspected of damaging fertility or the unborn child  
May cause drowsiness or dizziness  
May cause damage to organs through prolonged or repeated exposure  
Extremely flammable aerosol  
Contains gas under pressure; may explode if heated

**Appearance** Colorless**Physical state** Liquid Flammable Aerosol**Odor** Alcohol**Precautionary Statements - Prevention**

Obtain special instructions before use  
 Do not handle until all safety precautions have been read and understood  
 Use personal protective equipment as required  
 Wash face, hands and any exposed skin thoroughly after handling  
 Wear eye/face protection  
 Do not breathe dust/fume/gas/mist/vapors/spray  
 Use only outdoors or in a well-ventilated area  
 Do not puncture or incinerate container  
 Contents under pressure and can explode when exposed to heat or open flame  
 Keep away from heat/sparks/open flames/hot surfaces. - No smoking

**Precautionary Statements - Response**

IF exposed or concerned: Get medical advice/attention  
 IF SWALLOWED: Rinse mouth. DO NOT induce vomiting

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
 If eye irritation persists: Get medical advice/attention  
 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

**Precautionary Statements - Storage**

Store locked up  
 Store in a well-ventilated place. Keep container tightly closed  
 Do not expose to temperatures exceeding 122 °F (50 °C)  
 Keep away from heat, sparks, flames and other ignition sources  
 Keep out of reach of children

**Precautionary Statements - Disposal**

Dispose of contents/container to an approved waste disposal plant

**Hazards not otherwise classified (HNOC)**

Not applicable

**Other Information**

- Causes mild skin irritation
- May be harmful if inhaled or swallowed
- Harmful to aquatic life with long lasting effects

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

**substance(s)**

Chemical Name	CAS No	Weight-%	Trade Secret
ACETONE	67-64-1	60 - 100	*
TOLUENE	108-88-3	5 - 10	*
CARBON DIOXIDE	124-38-9	5 - 10	*

\*The exact percentage (concentration) of composition has been withheld as a trade secret.

### 4. FIRST AID MEASURES

**Description of first aid measures**

<b>General advice</b>	Get medical advice/attention if you feel unwell.
<b>Eye contact</b>	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
<b>Skin contact</b>	IF ON SKIN: Wash skin with soap and water. If skin irritation persists, call a physician. Wash contaminated clothing before reuse.
<b>Inhalation</b>	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If symptoms persist, call a physician.
<b>Ingestion</b>	IF SWALLOWED: Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Call a physician.
<b>Self-protection of the first aider</b>	Use personal protective equipment as required. Avoid contact with skin, eyes or clothing.

**Most important symptoms and effects, both acute and delayed**

**Symptoms** See section 2 for more information.

**Indication of any immediate medical attention and special treatment needed**

**Note to physicians** Treat symptomatically.

**5. FIRE-FIGHTING MEASURES****Suitable extinguishing media**

Dry chemical, CO<sub>2</sub>, sand, earth, water spray or regular foam

**Unsuitable extinguishing media**

None.

**Specific hazards arising from the chemical**

Extremely flammable. Contents under pressure and can explode when exposed to heat or flames. Vapors may cause flash fire.

**Explosion data**

**Sensitivity to Mechanical Impact** None.

**Sensitivity to Static Discharge** May be ignited by heat, sparks or flames.

**Protective equipment and precautions for firefighters**

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

**6. ACCIDENTAL RELEASE MEASURES****Personal precautions, protective equipment and emergency procedures**

**Personal precautions** Ensure adequate ventilation, especially in confined areas. Avoid contact with skin, eyes and inhalation of vapors. Use personal protective equipment as required. Remove all sources of ignition.

**Environmental precautions**

**Environmental precautions** Do not flush into surface water or sanitary sewer system. See Section 12 for additional ecological information.

**Methods and material for containment and cleaning up**

<b>Methods for containment</b>	Prevent further leakage or spillage if safe to do so.
<b>Methods for cleaning up</b>	Ensure adequate ventilation. Soak up with inert absorbent material. Sweep up and shovel into suitable containers for disposal.
<b>Prevention of secondary hazards</b>	Clean contaminated objects and areas thoroughly observing environmental regulations.

## 7. HANDLING AND STORAGE

### Precautions for safe handling

**Advice on safe handling** Handle in accordance with good industrial hygiene and safety practice. Avoid breathing vapors or mists. Avoid contact with skin, eyes or clothing. Wash thoroughly after handling. Wash contaminated clothing before reuse. Use personal protective equipment as required.

### Conditions for safe storage, including any incompatibilities

**Storage Conditions** Keep containers tightly closed in a cool, well-ventilated place. Keep away from sunlight, ignition sources and other sources of heat. Do not expose to temperatures exceeding 50 °C/122 °F. Keep out of the reach of children.

**Incompatible materials** Strong oxidizing agents

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Control parameters

#### Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
ACETONE 67-64-1	STEL: 750 ppm TWA: 500 ppm	TWA: 1000 ppm TWA: 2400 mg/m <sup>3</sup> (vacated) TWA: 750 ppm (vacated) TWA: 1800 mg/m <sup>3</sup> (vacated) STEL: 2400 mg/m <sup>3</sup> The acetone STEL does not apply to the cellulose acetate fiber industry. It is in effect for all other sectors (vacated) STEL: 1000 ppm	IDLH: 2500 ppm TWA: 250 ppm TWA: 590 mg/m <sup>3</sup>
TOLUENE 108-88-3	TWA: 20 ppm	TWA: 200 ppm (vacated) TWA: 100 ppm (vacated) TWA: 375 mg/m <sup>3</sup> (vacated) STEL: 150 ppm (vacated) STEL: 560 mg/m <sup>3</sup> Ceiling: 300 ppm	IDLH: 500 ppm TWA: 100 ppm TWA: 375 mg/m <sup>3</sup> STEL: 150 ppm STEL: 560 mg/m <sup>3</sup>
CARBON DIOXIDE 124-38-9	STEL: 30000 ppm TWA: 5000 ppm	TWA: 5000 ppm TWA: 9000 mg/m <sup>3</sup> (vacated) TWA: 10000 ppm (vacated) TWA: 18000 mg/m <sup>3</sup> (vacated) STEL: 30000 ppm (vacated) STEL: 54000 mg/m <sup>3</sup>	IDLH: 40000 ppm TWA: 5000 ppm TWA: 9000 mg/m <sup>3</sup> STEL: 30000 ppm STEL: 54000 mg/m <sup>3</sup>

NIOSH IDLH *Immediately Dangerous to Life or Health*

**Other Information** Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992).

### Appropriate engineering controls

**Engineering Controls** Showers  
Eyewash stations  
Ventilation systems

### Individual protection measures, such as personal protective equipment

**Eye/face protection** Wear safety glasses with side shields (or goggles).

<b>Skin and body protection</b>	Wear protective gloves and protective clothing.
<b>Respiratory protection</b>	Use NIOSH-approved air-purifying respirator with organic vapor cartridge or canister, as appropriate.
<b>General Hygiene Considerations</b>	Handle in accordance with good industrial hygiene and safety practice. Regular cleaning of equipment, work area and clothing is recommended.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

### Information on basic physical and chemical properties

<b>Physical state</b>	Liquid; Flammable Aerosol
<b>Appearance</b>	Colorless
<b>Odor</b>	Alcohol
<b>Odor threshold</b>	No information available

<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>
pH	No information available	
Melting point / freezing point	No information available	
Boiling point / boiling range	56 °C / 133 °F	
Flash point	-20 °C / -4 °F	Tag Closed Cup
Evaporation rate	No information available	
Flammability (solid, gas)	No information available	
Flammability Limit in Air		
Upper flammability limit:	2.6	
Lower flammability limit:	12.8	
Vapor pressure	185	
Vapor density	No information available	
Relative density	0.798	
Water solubility	Miscible in water	
Solubility in other solvents	No information available	
Partition coefficient	No information available	
Autoignition temperature	465 °C / 869 °F	
Decomposition temperature	No information available	
Kinematic viscosity	No information available	
Dynamic viscosity	No information available	
Explosive properties	No information available	
Oxidizing properties	No information available	

### Other Information

<b>Softening point</b>	No information available
<b>Molecular weight</b>	No information available
<b>VOC Content (%)</b>	9.8%
<b>Density</b>	0.797 g/cm <sup>3</sup>
<b>Bulk density</b>	No information available

## 10. STABILITY AND REACTIVITY

### Reactivity

Stable under normal use

### Chemical stability

Stable under recommended storage conditions

### Possibility of Hazardous Reactions

None under normal processing.

### Conditions to avoid

Keep away from all heat sources, open flames and other sources of ignition.

**Incompatible materials**

Strong oxidizing agents

**Hazardous Decomposition Products**

Carbon oxides

## 11. TOXICOLOGICAL INFORMATION

**Information on likely routes of exposure**

<b>Inhalation</b>	May cause irritation of respiratory tract. May cause central nervous system depression with nausea, headache, dizziness, vomiting, and incoordination. Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal. Harmful by inhalation.
<b>Eye contact</b>	Contact with eyes may cause irritation. May cause redness and tearing of the eyes.
<b>Skin contact</b>	May cause skin irritation and/or dermatitis.
<b>Ingestion</b>	Ingestion may cause irritation to mucous membranes. Potential for aspiration if swallowed. Aspiration may cause pulmonary edema and pneumonitis. May be fatal if swallowed.

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
ACETONE 67-64-1	= 5800 mg/kg ( Rat )	-	= 50100 mg/m <sup>3</sup> ( Rat ) 8 h
TOLUENE 108-88-3	= 2600 mg/kg ( Rat )	= 12000 mg/kg ( Rabbit )	= 12.5 mg/L ( Rat ) 4 h

**Information on toxicological effects**

**Symptoms** No information available.

**Delayed and immediate effects as well as chronic effects from short and long-term exposure**

**Sensitization** No information available.  
**Germ cell mutagenicity** No information available.  
**Carcinogenicity** The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
TOLUENE 108-88-3	-	Group 3	-	-

*IARC (International Agency for Research on Cancer)*

*Not classifiable as a human carcinogen*

**Chronic toxicity** May cause adverse liver effects.

**Target Organ Effects** Central nervous system, Central Vascular System (CVS), Eyes, kidney, Liver, Respiratory system, Skin.

The following values are calculated based on chapter 3.1 of the GHS document .

<b>ATEmix (oral)</b>	5526 mg/kg
<b>ATEmix (dermal)</b>	122449 mg/kg
<b>ATEmix (inhalation-dust/mist)</b>	62 mg/l

## 12. ECOLOGICAL INFORMATION

**Ecotoxicity**

Chemical Name	Algae/aquatic plants	Fish	Crustacea
ACETONE 67-64-1	-	4.74 - 6.33: 96 h Oncorhynchus mykiss mL/L LC50 6210 - 8120: 96 h Pimephales promelas mg/L LC50 static 8300: 96 h Lepomis macrochirus mg/L LC50	10294 - 17704: 48 h Daphnia magna mg/L EC50 Static 12600 - 12700: 48 h Daphnia magna mg/L EC50

TOLUENE 108-88-3	433: 96 h Pseudokirchneriella subcapitata mg/L EC50 12.5: 72 h Pseudokirchneriella subcapitata mg/L EC50 static	15.22 - 19.05: 96 h Pimephales promelas mg/L LC50 flow-through 12.6: 96 h Pimephales promelas mg/L LC50 static 5.89 - 7.81: 96 h Oncorhynchus mykiss mg/L LC50 flow-through 14.1 - 17.16: 96 h Oncorhynchus mykiss mg/L LC50 static 5.8: 96 h Oncorhynchus mykiss mg/L LC50 semi-static 11.0 - 15.0: 96 h Lepomis macrochirus mg/L LC50 static 54: 96 h Oryzias latipes mg/L LC50 static 28.2: 96 h Poecilia reticulata mg/L LC50 semi-static 50.87 - 70.34: 96 h Poecilia reticulata mg/L LC50 static	5.46 - 9.83: 48 h Daphnia magna mg/L EC50 Static 11.5: 48 h Daphnia magna mg/L EC50
---------------------	---	--	---

**Persistence and degradability**

No information available.

**Bioaccumulation**

No information available.

**Mobility**

Disperses in water.

Chemical Name	Partition coefficient
ACETONE 67-64-1	-0.24
TOLUENE 108-88-3	2.65

**Other adverse effects**

No information available

**13. DISPOSAL CONSIDERATIONS****Waste treatment methods****Disposal of wastes**

Recover or recycle if possible. Disposal should be in accordance with applicable regional, national and local laws and regulations.

**Contaminated packaging**

Do not reuse container.

**US EPA Waste Number**

U002 U220

Chemical Name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
ACETONE 67-64-1	-	Included in waste stream: F039	-	U002
TOLUENE 108-88-3	U220	Included in waste streams: F005, F024, F025, F039, K015, K036, K037, K149, K151	-	U220

Chemical Name	RCRA - Halogenated Organic Compounds	RCRA - P Series Wastes	RCRA - F Series Wastes	RCRA - K Series Wastes
TOLUENE 108-88-3	-	-	Toxic waste waste number F025 Waste description: Condensed light ends, spent filters and filter aids, and spent desiccant wastes from the production of certain chlorinated aliphatic hydrocarbons, by free radical catalyzed processes. These chlorinated aliphatic	-

			hydrocarbons are those having carbon chain lengths ranging from one to and including five, with varying amounts and positions of chlorine substitution.	
--	--	--	---	--

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California Hazardous Waste Status
ACETONE 67-64-1	Ignitable
TOLUENE 108-88-3	Toxic Ignitable

#### 14. TRANSPORT INFORMATION

##### DOT

**UN/ID no** UN 1950  
**Proper shipping name:** Aerosols, Consumer Commodity, Limited Quantity (LQ)  
**Hazard Class** 2.1

##### IATA

**UN/ID no** UN 1950  
**Proper shipping name:** Aerosols, Consumer commodity, Limited Quantity (LQ)  
**Hazard Class** 2.1

##### IMDG

**UN/ID no** UN 1950  
**Proper shipping name:** Aerosols, Consumer Commodity, Limited Quantity (LQ)  
**Hazard Class** 2.1

#### 15. REGULATORY INFORMATION

##### International Inventories

**TSCA** Complies  
**DSL/NDSL** Complies  
**EINECS/ELINCS** Complies  
**ENCS** Not determined  
**IECSC** Not determined  
**KECL** Not determined  
**PICCS** Not determined  
**AICS** Not determined

##### Legend:

**TSCA** - United States Toxic Substances Control Act Section 8(b) Inventory  
**DSL/NDSL** - Canadian Domestic Substances List/Non-Domestic Substances List  
**EINECS/ELINCS** - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances  
**ENCS** - Japan Existing and New Chemical Substances  
**IECSC** - China Inventory of Existing Chemical Substances  
**KECL** - Korean Existing and Evaluated Chemical Substances  
**PICCS** - Philippines Inventory of Chemicals and Chemical Substances  
**AICS** - Australian Inventory of Chemical Substances

##### US Federal Regulations

##### SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical Name	SARA 313 - Threshold Values %
TOLUENE - 108-88-3	1.0



**SARA 311/312 Hazard Categories**

Acute health hazard	No
Chronic Health Hazard	No
Fire hazard	No
Sudden release of pressure hazard	No
Reactive Hazard	No

**CWA (Clean Water Act)**

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
TOLUENE 108-88-3	1000 lb	X	X	X

**CERCLA**

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical Name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
ACETONE 67-64-1	5000 lb	-	RQ 5000 lb final RQ RQ 2270 kg final RQ
TOLUENE 108-88-3	1 lb	-	RQ 1 lb final RQ RQ 0.454 kg final RQ

**US State Regulations****California Proposition 65**

This product contains the following Proposition 65 chemicals

Chemical Name	California Proposition 65
TOLUENE - 108-88-3	Developmental Female Reproductive

**U.S. State Right-to-Know Regulations**

Chemical Name	New Jersey	Massachusetts	Pennsylvania
ACETONE 67-64-1	X	X	X
TOLUENE 108-88-3	X	X	X
CARBON DIOXIDE 124-38-9	X	X	X

**U.S. EPA Label Information**

EPA Pesticide Registration Number Not applicable

**WHMIS Hazard Class**

Non-controlled

<b>NFPA</b>	Health hazards 2	Flammability 3	Instability 0	-
<b>HMIS</b>	Health hazards 2	Flammability 3	Physical hazards 1	Personal protection B

NFPA (National Fire Protection Association)  
HMIS (Hazardous Material Information System)

Revision Date 10-Apr-2015

Revision Note 4

**Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**End of Safety Data Sheet**