

# Safety Data Sheet

## MasterSeal 590 also Waterplug

Revision date : 2014/07/31  
Version: 3.0

Page: 1/10  
(51722052/SDS\_GEN\_US/EN)

### 1. Identification

**Product identifier used on the label**

**MasterSeal 590 also Waterplug**

**Recommended use of the chemical and restriction on use**

Recommended use\*: for industrial and professional users

\* The "Recommended use" identified for this product is provided solely to comply with a US Federal requirement and is not part of the seller's published specification. The terms of this Safety Data Sheet (SDS) do not create or infer any warranty, express or implied, including by incorporation into or reference in the seller's sales agreement.

**Details of the supplier of the safety data sheet**

Company:  
BASF CORPORATION  
100 Park Avenue  
Florham Park, NJ 07932, USA

Telephone: +1 973 245-6000

**Emergency telephone number**

CHEMTREC: 1-800-424-9300  
BASF HOTLINE: 1-800-832-HELP (4357)

**Other means of identification**

---

### 2. Hazards Identification

**According to Regulation 2012 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200**

**Classification of the product**

Skin Corr./Irrit.	2	Skin corrosion/irritation
Eye Dam./Irrit.	1	Serious eye damage/eye irritation
Carc.	1A	Carcinogenicity
STOT SE	3 (irritating to respiratory system)	Specific target organ toxicity — single exposure
STOT RE	1	Specific target organ toxicity — repeated exposure

**Label elements**

# Safety Data Sheet

## MasterSeal 590 also Waterplug

Revision date : 2014/07/31  
Version: 3.0

Page: 2/10  
(51722052/SDS\_GEN\_US/EN)

Pictogram:



Signal Word:  
Danger

Hazard Statement:

H318	Causes serious eye damage.
H315	Causes skin irritation.
H335	May cause respiratory irritation.
H350	May cause cancer.
H372	Causes damage to organs (Lung) through prolonged or repeated exposure.

Precautionary Statements (Prevention):

P280	Wear protective gloves/protective clothing/eye protection/face protection.
P271	Use only outdoors or in a well-ventilated area.
P260	Do not breathe dust/gas/mist/vapours.
P202	Do not handle until all safety precautions have been read and understood.
P270	Do not eat, drink or smoke when using this product.
P264	Wash with plenty of water and soap thoroughly after handling.

Precautionary Statements (Response):

P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a POISON CENTER or doctor/physician.
P304 + P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P303 + P352	IF ON SKIN (on hair): Wash with plenty of soap and water.
P332 + P313	If skin irritation occurs: Get medical advice/attention.
P362 + P364	Take off contaminated clothing and wash before reuse.

Precautionary Statements (Storage):

P403 + P233	Store in a well-ventilated place. Keep container tightly closed.
P405	Store locked up.

Precautionary Statements (Disposal):

P501	Dispose of contents/container to hazardous or special waste collection point.
------	---

### Hazards not otherwise classified

If applicable information is provided in this section on other hazards which do not result in classification but which may contribute to the overall hazards of the substance or mixture.

**According to Regulation 1994 OSHA Hazard Communication Standard: 29 CFR Part 1910.1200**

### Emergency overview

WARNING:  
MAY BE HARMFUL IF INHALED.  
RISK OF SERIOUS DAMAGE TO EYES.  
Can cause moderate irritation due to abrasive action.

# Safety Data Sheet

## MasterSeal 590 also Waterplug

Revision date : 2014/07/31  
Version: 3.0

Page: 3/10  
(51722052/SDS\_GEN\_US/EN)

In combination with water, repeated or prolonged dermal exposure can cause moderate to severe alkali burns.

CONTAINS MATERIAL WHICH CAN CAUSE CANCER.

Keep container tightly closed.

Avoid inhalation of dusts.

Avoid ingestion.

Avoid contact with the skin, eyes and clothing.

Wash thoroughly after handling.

### 3. Composition / Information on Ingredients

#### According to Regulation 2012 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200

<u>CAS Number</u>	<u>Content (W/W)</u>	<u>Chemical name</u>
65997-15-1	>= 25.0 - < 50.0 %	Cement, portland, chemicals
14808-60-7	>= 15.0 - < 25.0 %	crystalline silica
1305-62-0	>= 3.0 - < 10.0 %	Calcium dihydroxide

#### According to Regulation 1994 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200

<u>CAS Number</u>	<u>Content (W/W)</u>	<u>Chemical name</u>
65997-15-1	>= 30.0 - <= 60.0 %	Cement, portland, chemicals
14808-60-7	>= 15.0 - <= 40.0 %	crystalline silica
471-34-1	>= 1.0 - <= 5.0 %	Calcium carbonate
1305-62-0	>= 1.0 - <= 5.0 %	Calcium dihydroxide
13397-24-5	>= 1.0 - <= 5.0 %	Gypsum (Ca(SO <sub>4</sub> ).2H <sub>2</sub> O)
1317-65-3	>= 0.5 - <= 1.5 %	Limestone

### 4. First-Aid Measures

#### Description of first aid measures

##### General advice:

First aid personnel should pay attention to their own safety. Remove contaminated clothing.

##### If inhaled:

After inhalation of dust. Keep patient calm, remove to fresh air. If difficulties occur: Obtain medical attention.

##### If on skin:

After contact with skin, wash immediately with plenty of water and soap. Under no circumstances should organic solvent be used. If irritation develops, seek medical attention.

##### If in eyes:

Wash affected eyes for at least 15 minutes under running water with eyelids held open, consult an eye specialist.

##### If swallowed:

Rinse mouth immediately and then drink plenty of water, seek medical attention. Do not induce vomiting unless told to by a poison control center or doctor.

#### Most important symptoms and effects, both acute and delayed

# Safety Data Sheet

## MasterSeal 590 also Waterplug

Revision date : 2014/07/31  
Version: 3.0

Page: 4/10  
(51722052/SDS\_GEN\_US/EN)

Symptoms: The most important known symptoms and effects are described in the labelling (see section 2) and/or in section 11.

### Indication of any immediate medical attention and special treatment needed

---

## 5. Fire-Fighting Measures

### Extinguishing media

Suitable extinguishing media:  
foam, water spray, dry powder, carbon dioxide

Unsuitable extinguishing media for safety reasons:  
water jet

Additional information:

Product itself is non-combustible. Only the packaging materials can catch fire. The extinguishing agents normally used are sufficient.

### Special hazards arising from the substance or mixture

Hazards during fire-fighting:

carbon monoxide, carbon dioxide, harmful vapours

Evolution of fumes/fog. The substances/groups of substances mentioned can be released in case of fire. Product is not combustible or explosive.

### Advice for fire-fighters

Protective equipment for fire-fighting:

Wear self-contained breathing apparatus and chemical-protective clothing.

### Further information:

Product itself is non-combustible; fire extinguishing method of surrounding areas must be considered. The degree of risk is governed by the burning substance and the fire conditions. Dispose of fire debris and contaminated extinguishing water in accordance with official regulations.

---

## 6. Accidental release measures

### Personal precautions, protective equipment and emergency procedures

Avoid dust formation. Avoid contact with skin and eyes. Use personal protective clothing. Handle in accordance with good building materials hygiene and safety practice.

### Environmental precautions

Do not discharge into drains/surface waters/groundwater.

### Methods and material for containment and cleaning up

For small amounts: Pick up with suitable appliance and dispose of.

For large amounts: Pick up with suitable appliance and dispose of. Pack in tightly closed containers for disposal.

For residues: Rinse with plenty of water.

Avoid raising dust.

---

# Safety Data Sheet

## MasterSeal 590 also Waterplug

Revision date : 2014/07/31  
Version: 3.0

Page: 5/10  
(51722052/SDS\_GEN\_US/EN)

### 7. Handling and Storage

#### Precautions for safe handling

Avoid dust formation. The Cement contained in this product reacts alkaline when in contact with water or humidity. This may cause severe irritation of skin or mucous membranes. The humidity of the skin or mucous membranes is enough for this reaction. Prolonged direct contact to the dry product should be avoided therefore. Avoid inhalation of dusts. Avoid skin contact. Pour downwind and allow as little free fall as possible while emptying bags into equipment. Breathing must be protected when large quantities are decanted without local exhaust ventilation.

Protection against fire and explosion:  
No special precautions necessary.

#### Conditions for safe storage, including any incompatibilities

Segregate from metals. Segregate from acids. Segregate from lyes. Segregate from oxidants. Segregate from foods and animal feeds.

Suitable materials for containers: tin (tinplate)

Further information on storage conditions: Containers should be stored tightly sealed in a dry place.

### 8. Exposure Controls/Personal Protection

#### Advice on system design:

Provide local exhaust ventilation to maintain recommended P.E.L.

#### Personal protective equipment

##### Respiratory protection:

Breathing protection if dusts are formed.

##### Hand protection:

Chemical resistant protective gloves, Manufacturer's directions for use should be observed because of great diversity of types.

##### Eye protection:

Tightly fitting safety goggles (chemical goggles).

##### Body protection:

Body protection must be chosen based on level of activity and exposure.

#### General safety and hygiene measures:

Avoid contact with the skin, eyes and clothing. Avoid inhalation of dusts. In order to prevent contamination while handling, closed working clothes and working gloves should be used. Handle in accordance with good building materials hygiene and safety practice. When using, do not eat, drink or smoke. Hands and/or face should be washed before breaks and at the end of the shift. At the end of the shift the skin should be cleaned and skin-care agents applied. Gloves must be inspected regularly and prior to each use. Replace if necessary (e.g. pinhole leaks). Contaminated equipment or clothing should be cleaned after each use or disposed of.

### 9. Physical and Chemical Properties

Form: powder  
Odour: odourless  
Odour threshold:

No applicable information available.

# Safety Data Sheet

## MasterSeal 590 also Waterplug

Revision date : 2014/07/31  
Version: 3.0

Page: 6/10  
(51722052/SDS\_GEN\_US/EN)

Colour:	grey	
pH value:	approx. 12 - 13	(approx. 20 °C) (as aqueous suspension)
Melting point:		The product has not been tested.
Sublimation point:		No applicable information available.
Flammability:	not flammable	
Vapour pressure:		The product has not been tested.
Bulk density:	approx. 1,800 - 2,400 kg/m <sup>3</sup>	
Vapour density:		The product is a non-volatile solid.
Partitioning coefficient n-octanol/water (log Pow):		not applicable
Viscosity, dynamic:		not applicable, the product is a solid
Solubility in water:		( 20 °C) dispersible
Miscibility with water:		miscible
Evaporation rate:		The product is a non-volatile solid.

## 10. Stability and Reactivity

### Reactivity

No hazardous reactions if stored and handled as prescribed/indicated.

### Chemical stability

The product is stable if stored and handled as prescribed/indicated.

### Possibility of hazardous reactions

The product is stable if stored and handled as prescribed/indicated.  
Strong bases are formed on the addition of water.

### Conditions to avoid

Avoid dust formation. Avoid humidity.

### Incompatible materials

strong acids  
strong bases, strong acids

### Hazardous decomposition products

Decomposition products:

No hazardous decomposition products if stored and handled as prescribed/indicated.

## 11. Toxicological information

### Primary routes of exposure

Routes of entry for solids and liquids are ingestion and inhalation, but may include eye or skin contact. Routes of entry for gases include inhalation and eye contact. Skin contact may be a route of entry for liquefied gases.

### Acute Toxicity/Effects

#### Acute toxicity

Assessment of acute toxicity: Product may present a nuisance dust hazard. Inhalation of dust may cause respiratory tract irritation, coughing and breathing difficulties.

#### Assessment other acute effects

# Safety Data Sheet

## MasterSeal 590 also Waterplug

Revision date : 2014/07/31  
Version: 3.0

Page: 7/10  
(51722052/SDS\_GEN\_US/EN)

Assessment of STOT single:  
Causes temporary irritation of the respiratory tract.

The product has not been tested. The statement has been derived from the properties of the individual components.

### Irritation / corrosion

Assessment of irritating effects: Skin contact causes irritation. May cause severe damage to the eyes. The product has not been tested. The statement has been derived from the properties of the individual components.

### Skin

Result: Irritant.

*Information on: Cement, portland, chemicals*

*Species: rabbit*

*Result: Irritant.*

### Eye

Result: Risk of serious damage to eyes.

*Information on: Cement, portland, chemicals*

*Species: rabbit*

*Result: Severely irritating.*

### Sensitization

Assessment of sensitization: There is no evidence of a skin-sensitizing potential. The product has not been tested. The statement has been derived from the properties of the individual components. Chromate in this product has been reduced. Sensitization due to chromate within stated shelf-life is unlikely.

## **Chronic Toxicity/Effects**

### Repeated dose toxicity

Assessment of repeated dose toxicity: After repeated exposure the prominent effect is local irritation. The product has not been tested. The statement has been derived from the properties of the individual components.

Inhalation of dust may cause respiratory tract irritation, coughing and breathing difficulties.

### Genetic toxicity

Assessment of mutagenicity: The chemical structure does not suggest a specific alert for such an effect. Based on available Data, the classification criteria are not met.

### Carcinogenicity

Assessment of carcinogenicity: Contains a known carcinogen. This product contains crystalline silica (quartz).

*Information on: crystalline silica*

*Assessment of carcinogenicity: In long-term studies in rats and mice in which the substance was given by feed, a carcinogenic effect was not observed. In long-term animal studies in which the substance was given by inhalation in high doses, a carcinogenic effect was observed. The substance and its compounds in the form of respirable dusts/aerosols classified by the German MAK commission as a category 1 carcinogen (substances that cause cancer to humans). A carcinogenic effect cannot safely be ruled out. The inhalation uptake of the alveolar fraction of the fine dust may cause damage to the lungs. The International Agency for Research on Cancer (IARC) has classified this substance as a Group 1 (known) human carcinogen.*

# Safety Data Sheet

## MasterSeal 590 also Waterplug

Revision date : 2014/07/31  
Version: 3.0

Page: 8/10  
(51722052/SDS\_GEN\_US/EN)

*The International Agency for Research on Cancer (IARC) has classified this substance as a Group 1 (known) human carcinogen.  
NTP listed carcinogen*

-----

### Reproductive toxicity

Assessment of reproduction toxicity: The chemical structure does not suggest a specific alert for such an effect. Based on available Data, the classification criteria are not met.

### Teratogenicity

Assessment of teratogenicity: The chemical structure does not suggest a specific alert for such an effect. Based on available Data, the classification criteria are not met.

### Experiences in humans

*Information on: crystalline silica  
May cause silicosis.*

-----

### Other Information

Based on our experience and the information available, no adverse health effects are expected if handled as recommended with suitable precautions for designated uses. The product has not been tested. The statements on toxicology have been derived from the properties of the individual components.

## **Symptoms of Exposure**

The most important known symptoms and effects are described in the labelling (see section 2) and/or in section 11.

---

## **12. Ecological Information**

### **Toxicity**

#### Aquatic toxicity

Assessment of aquatic toxicity:

There is a high probability that the product is not acutely harmful to aquatic organisms.

The product gives rise to pH shifts. Based on available Data, the classification criteria are not met.

### **Persistence and degradability**

#### Assessment biodegradation and elimination (H<sub>2</sub>O)

Inorganic product which cannot be eliminated from water by biological purification processes. The product is slightly soluble in water. It can be largely eliminated from the water by abiotic processes, e.g. mechanical separation.

Experience shows this product to be inert and non-degradable.

#### Elimination information

not applicable

### **Bioaccumulative potential**

#### Assessment bioaccumulation potential



# Safety Data Sheet

## MasterSeal 590 also Waterplug

Revision date : 2014/07/31  
Version: 3.0

Page: 9/10  
(51722052/SDS\_GEN\_US/EN)

The product will not be readily bioavailable due to its consistency and insolubility in water.

### Mobility in soil

#### Assessment transport between environmental compartments

The substance will not evaporate into the atmosphere from the water surface.

Following exposure to soil, adsorption to solid soil particles is probable, therefore contamination of groundwater is not expected.

### Additional information

Other ecotoxicological advice:

Do not discharge product into the environment without control. The product has not been tested. The statements on ecotoxicology have been derived from the properties of the individual components.

---

## 13. Disposal considerations

### Waste disposal of substance:

Dispose of in accordance with local authority regulations. Do not discharge into drains/surface waters/groundwater.

### Container disposal:

Completely emptied packagings can be given for recycling.

---

## 14. Transport Information

### Land transport

USDOT

Not classified as a dangerous good under transport regulations

### Sea transport

IMDG

Not classified as a dangerous good under transport regulations

### Air transport

IATA/ICAO

Not classified as a dangerous good under transport regulations

---

## 15. Regulatory Information

### Federal Regulations

#### Registration status:

Chemical TSCA, US released / listed

EPCRA 311/312 (Hazard categories):

Acute; Chronic

CERCLA RQ  
100 LBS

CAS Number  
50-00-0

Chemical name  
Formaldehyde

# Safety Data Sheet

## MasterSeal 590 also Waterplug

Revision date : 2014/07/31  
Version: 3.0

Page: 10/10  
(51722052/SDS\_GEN\_US/EN)

### State regulations

<u>State RTK</u>	<u>CAS Number</u>	<u>Chemical name</u>
MA, NJ, PA	65997-15-1	Cement, portland, chemicals
MA, NJ, PA	14808-60-7	crystalline silica
MA, NJ, PA	471-34-1	Calcium carbonate
MA, NJ, PA	1305-62-0	Calcium dihydroxide
NJ, PA	13397-24-5	Gypsum (Ca(SO4).2H2O)
MA, NJ, PA	1317-65-3	Limestone

### **CA Prop. 65:**

THIS PRODUCT CONTAINS A CHEMICAL(S) KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER AND BIRTH DEFECTS OR OTHER REPRODUCTIVE HARM.

### **NFPA Hazard codes:**

Health : 2      Fire: 0      Reactivity: 0      Special:

### **HMIS III rating**

Health: 2<sup>+</sup>      Flammability: 0      Physical hazard: 1

---

## 16. Other Information

### **SDS Prepared by:**

BASF NA Product Regulations  
SDS Prepared on: 2014/07/31

We support worldwide Responsible Care® initiatives. We value the health and safety of our employees, customers, suppliers and neighbors, and the protection of the environment. Our commitment to Responsible Care is integral to conducting our business and operating our facilities in a safe and environmentally responsible fashion, supporting our customers and suppliers in ensuring the safe and environmentally sound handling of our products, and minimizing the impact of our operations on society and the environment during production, storage, transport, use and disposal of our products.

---

IMPORTANT: WHILE THE DESCRIPTIONS, DESIGNS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE , IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU MAKE TESTS TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, YOU EXPRESSLY UNDERSTAND AND AGREE THAT THE DESCRIPTIONS, DESIGNS, DATA, AND INFORMATION FURNISHED BY OUR COMPANY HEREUNDER ARE GIVEN GRATIS AND WE ASSUME NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DESIGNS, DATA AND INFORMATION GIVEN OR RESULTS OBTAINED, ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK.  
END OF DATA SHEET