



PROFESSIONAL INVERTED MARKING & STRIPING AEROSOLS

STRIPING PAINT

| | | |
|--------------------|---|---------------------------|
| DESCRIPTION | A lead-free aerosol striping paint designed for use in an inverted position. Features weather and abrasion resistance for durability. | |
| USES | When used with the Rust-Oleum Striping Machine, these coatings are ideal for striping parking lots, aisles and athletic fields. They feature fast dry and adhesion to concrete, blacktop, gravel and grass. | |
| APPEARANCE | Flat finish | |
| PRODUCTS | 2526 Blue 2593 White | 2548 Yellow 2578 Black |
| PACKAGING | 20-ounce containers, 6 containers/carton | |

PHYSICAL PROPERTIES (Calculated values are shown and may vary slightly from the actual manufactured material)

| | |
|----------------------------------|---|
| RESIN TYPE | Vinyl Toluene Modified Alkyd |
| VOLATILE ORGANIC COMPOUNDS (VOC) | <66% (Complies with VOC Regulations in California) |
| FILL WEIGHT | 18 oz (510 g) |
| PRACTICAL COVERAGE | 2 inch stripe - 400 feet 2 inch stripe - 250 feet (2593) 4 inch stripe - 200 feet 4 inch stripe - 125 feet (2593) (coverage is dependent on surface porosity) |
| DRY TIME @70°F (21°C) and 50% RH | |
| TACK FREE | 10 minutes |
| RECOAT | Anytime |
| DRY HEAT RESISTANCE | 200°F (93°C) |
| SHELF LIFE | 5 years |

SAFETY (For additional information, see MSDS)

| | |
|-------------|-------------------|
| FLASH POINT | -156° F (-144° C) |
| LEAD-FREE | |

MARKING PAINT

| | |
|----------------------------|---|
| DESCRIPTION | An aerosol coating specifically packaged for use in an inverted position as a marking paint. |
| USES | Use for marking construction and excavation sites, underground utilities and for traffic safety. They can also be used with 2393 Marking Wand to make large jobs less tedious. They feature fast dry and adhesion to concrete, blacktop, gravel, soil and grass. |
| APPEARANCE | Flat to semi-gloss finish (dependent on surface porosity) |
| PRODUCTS | 2524 Caution Blue 2544 High Visibility Yellow 2545 Caution Yellow 2554 Fluorescent Orange 2558 Fluorescent Red-Orange 2564 Safety Red 2592 White 2596 Clear |
| PACKAGING | 20-ounce containers, 6 containers/carton |
| SURFACE PREPARATION | Remove all dirt and contaminants by sweeping the concrete or blacktop before application of the coating. Grease, oil and chemical contaminants are best removed by washing the surface with 3599 Industrial Pure Strength® Cleaner/Degreaser, commercial detergent or other suitable cleaner. Rinse thoroughly with fresh water and allow to fully dry. Use in properly ventilated area. Spraying can produce a fog that will travel. Protect surrounding area, clothing and skin from overspray. |

PHYSICAL PROPERTIES (Calculated values are shown and may vary slightly from the actual manufactured material)

| | |
|-----------------------------------|---|
| RESIN TYPE | Vinyl Toluidine Modified Alkyd |
| VOLATILE ORGANIC COMPOUNDS (VOC) | <65% (Complies with VOC Regulations in California.) |
| FILL WEIGHT | 15 ounces/can (426 g) |
| PRACTICAL COVERAGE | 300 – 350 linear feet (91 – 106 m) at 1.5 in wide (3.8 cm) (dependent on surface porosity) |
| DRY TIME @70°F (21° C) and 50% RH | |
| TACK FREE | 10 - 20 minutes |
| DRY HEAT RESISTANCE | 200°F (93°C) |
| SHELF LIFE | 5 years |

SAFETY (For additional information, see MSDS)

| | |
|-------------|-------------------|
| FLASH POINT | -156° F (-144° C) |
| LEAD-FREE | |