



SAFETY DATA SHEET
TruSil 100 Silicone Sealant (Clear)
 Silicone Rubber Compound



SECTION 1 - PRODUCT AND COMPANY IDENTIFICATION

1.1 Product identifier

Product Name: TruSil 100 Silicone Sealant (Clear)
Product Codes(s): TS-100 C
Synonyms: Silicone Sealant
REACH Registration Number: No data available

1.2 Relevant identified uses of the substance or mixture and uses advised against

General Use: General purpose sealant and adhesive
Uses advised against: None known

1.3 Details of the supplier and of the safety data sheet

Manufacturer/Distributor
 Everkem Diversified Products
 5180 Indiana Avenue
 Winston-Salem, NC 27106 USA
 +1-800-638-3160

1.4 Emergency telephone number: +1-800-638-3160


SECTION 2 - HAZARDS IDENTIFICATION

2.1 Classification of substance or mixture

Product definition: Mixture
Classification (Regulation (EC) No 1272/2008)
 Skin Irritant - Category 2 [H315]
 Eye Irritant - Category 2B [H320]

2.2 Label Elements

Labeling (Regulation (EC) No 1272/2008)

Hazard Symbol(s): 
 GHS07
Signal Word: Warning
Hazard Statement(s): H315 - Causes skin irritation
 H320 - Causes eye irritation
Precautionary Statements:
[Prevention] P264 - Wash hands and exposed skin areas after handling.
 P280 - Wear protective gloves, protective clothing and eye protection.
[Response] P302 + P352 - IF ON SKIN: Wash with plenty of soap and water.
 P321 - Specific treatment: Seek medical attention. Refer to Section 4 of this SDS.
 P332 + P313 - If skin irritation occurs: Get medical attention.
 P362 - Take off contaminated clothing and wash before reuse.
 P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present. Continue rinsing.
 P337 + P313 - If eye irritation persists: Get medical attention.

SECTION 3 - COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substances

Not applicable

3.2 Mixtures

Chemical characterization (preparation)

% by Weight	Ingredient	CAS Number	EC Number	Index Number	EC Classification
7.0 - 13.0	Silicon Dioxide, Amorphous	7631-86-9	265-148-2	-----	-----
1.0 - 7.0	Distillates (Petroleum), Hydrotreated Middle	64742-46-7	265-148-2	649-221-00-X	Xn, R65
1.0 - 5.0	Ethyltriacetoxysilane	17689-77-9	241-677-4	-----	-----
1.0 - 5.0	Methyltriacetoxysilane	4253-34-3	244-221-9	-----	-----
0.1 - 1.0	Octamethylcyclotetrasiloxane	556-67-2	209-136-7	014-018-00-1	Repr. Cat. 3, R62; R53

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to the health or the environment and hence require reporting in this section.

SECTION 4 - FIRST AID MEASURES

4.1 Description of first aid measures

Inhalation: If product vapor causes respiratory irritation or distress, move the exposed person to fresh air immediately. If breathing is difficult or irregular, administer oxygen; if respiratory arrest occurs, start artificial respiration by trained personnel. Loosen tight clothing such as a collar, a collar, tie, belt or waistband. If symptoms persist, seek medical attention.

Eyes: Immediately flush eyes with large amounts of water for 15 minutes, occasionally lifting upper and lower lids. Remove contact lenses, if present and easy to do, after first 2 minutes and continue rinsing. Obtain immediate medical attention, preferably from an ophthalmologist.

Skin: Remove contaminated clothing. Quickly and gently remove excess product with a dry cloth or paper towel. Flush skin with lukewarm water for 15 minutes. Wash affected area with soap and water. Clean contaminated clothing and shoes before reuse. If irritation persists, seek medical advice.

Ingestion: Rinse mouth with water if victim is conscious. Remove dentures, if present. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs naturally, have victim lean forward to reduce the risk of aspiration of material into the lungs. Never give anything by mouth to an unconscious person. Get medical attention immediately.

4.2 Most important symptoms and effects, both acute and delayed

Potential health symptoms and effects

Eyes: Causes moderate to severe eye irritation. Symptoms include redness, itching, swelling, tearing and pain.

Skin: Causes skin irritation. Symptoms may include localized redness and itching.

Inhalation: Vapor may cause irritation of the respiratory tract. Symptoms may include irritation of the nose and throat.

Chronic: Persons with pre-existing skin disorders or respiratory impairment may be more susceptible to the effects of this material. Silicon Dioxide is a suspected animal carcinogen. Octamethylcyclotetrasiloxane has caused reproductive effects in laboratory animals.

4.3 Indication of any immediate medical attention and special treatment needed

Advice to Doctor and Hospital Personnel

Treat symptomatically and supportively.

SECTION 5 - FIRE FIGHTING MEASURES

5.1 Extinguishable media

Suitable methods of extinction: Use water fog or water spray, dry chemical, carbon dioxide and foam.

Unsuitable methods of extinction: None known

5.2 Special hazards arising from the substance or mixture

Closed containers may explode due to the buildup of pressure when exposed to extreme heat. During emergency conditions overexposure to decomposition products may cause a health hazard. Symptoms may not be immediately apparent or may be delayed. Obtain medical attention.

This product contains methylpolysiloxanes, which can generate formaldehyde at temperatures greater than 150 °C (300 °F). Formaldehyde is a skin and respiratory sensitizer, eye and throat irritant, acute toxicant and potential cancer hazard. Material releases Acetic Acid when wet.

Explosion hazards: Material does not present an explosion hazard.

5.3 Advice for firefighters

Full protective equipment including self-contained breathing apparatus should be used. Water may be used to cool closed containers to prevent pressure buildup and possible autoignition or explosion when exposed to extreme heat. If possible, firefighters should control runoff water to prevent environmental contamination. Fire residues and contaminated extinguishing water must be disposed of in accordance with local regulations.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

Evacuate non-essential personnel. Remove all sources of ignition. Ventilate the area. Wear appropriate protective clothing and equipment designated in Section 8. Spilled material creates a slip hazard.

6.2 Environmental precautions

Avoid dispersal of spilled material and prevent contact with soil and entry into drains, sewers or waterways.

6.3 Methods and materials for containment and cleaning up

Approach spill from upwind direction. Cover drains and contain spill. Cover spill with non-combustible absorbent. Wipe or scrape up and contain for salvage or disposal. Clean area as appropriate since spilled material, even in small quantities, may present a slip hazard. Final cleaning may require use of steam, solvents or detergents. Dispose of saturated absorbent or cleaning materials appropriately, since spontaneous heating may occur. Local, state and federal laws and regulations may apply to releases and disposal of this material, as well as those materials and items used in the cleanup of releases. Place material to be discarded into an approved container for proper disposal. Observe possible material restrictions (refer to Sections 7.2 and 10.5).

6.4 Reference to other sections

For indications about waste treatment, see Section 13.

SECTION 7 - HANDLING AND STORAGE

7.1 Precautions for safe handling

Observe label precautions.. Wear all appropriate protective equipment specified in Section 8. Keep containers closed when not in use.

Use with adequate ventilation. Product evolves Acetic Acid when exposed to water or humid air. Provide ventilation during use to control Acetic Acid within exposure guidelines or use respiratory protection. Avoid contact with eyes and skin. Avoid breathing vapor.

Advice on protection against fire and explosion

Product does not present a fire or explosion hazard.

7.2 Conditions for safe storage, including any incompatibilities

Keep containers tightly closed in cool, dry, well-ventilated storage areas. Transfer only to approved containers having correct labeling. Protect containers against physical damage. Keep containers tightly closed. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not reuse empty containers as they may retain product residues. Use appropriate containment to avoid environmental contamination. Ventilate closed areas. Do not take internally. Keep out of reach of children.

7.3 Specific end uses

Apart from the uses mentioned in Section 1.2, no other specific uses are stipulated.

SECTION 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

8.1 Control parameters

CAS Number	Ingredient	OSHA PEL	ACGIH TLV	NIOSH
7631-86-9	Silicon Dioxide, Amorphous	80 mg/m3 TWA (final rule)	-----	10 ppm, 6 mg/m3 TWA
17689-77-9	Ethyltriacetoxysilane	See Acetic Acid comment.*	-----	-----
4253-34-3	Methyltriacetoxysilane	See Acetic Acid comment*	-----	-----
556-86-9	Octamethylcyclotetrasiloxane**	-----	-----	-----

*Acetic Acid (CAS #64-19-7) is formed upon contact with water or humid air. Provide adequate ventilation to control exposures within guidelines of OSHA PEL: TWA 10 ppm and ACGI TLV: TWA 10 ppm, STEL 15 ppm.

**Manufacturer's PEL: TWA 10 ppm

8.2 Exposure controls

Engineering Measures: Technical measures and appropriate working operations should be given priority over the use of personal protective equipment. Use adequate ventilation. Local exhaust is preferable. Refer to section 7.1.

Individual protection measures: Wear protective clothing to prevent repeated or prolonged contact with product. Protective clothing needs to be selected specifically for the workplace, depending on concentrations and quantities of hazardous substances handled. The chemical resistance of the protective equipment should be enquired at the representative supplier.

Hygiene measures: Facilities storing or using this material should be equipped with an eyewash station and safety shower. Change contaminated clothing. Preventive skin protection is recommended. Wash hands thoroughly after use, before eating, drinking or using the lavatory.

Eye/face protection: Wear protective goggles or safety glasses with unperforated side shields during use. Refer to 29 CFR 1910.133, ANSI Z87.1 or European Standard EN 166. It is recommended that contact lenses be removed before using this sealant. Do not handle lenses until all sealant has been cleaned from the fingertips, nails and cuticles. Residual sealant may remain on fingers for several days and transfer to lenses, causing severe eye irritation.

Hand Protection: Wear Nitrile rubber or Neoprene gloves or those recommended by glove supplier for protection against materials in Section 3. Gloves should be impermeable to chemicals and oil. Breakthrough time of selected gloves must be greater than the intended use period.

Other protective equipment: Long sleeve shirts and trousers without cuffs; boots if the situation calls for them.

Respiratory Protection: None needed under ambient conditions with adequate local exhaust. Always use an approved respirator when vapors are generated. Where risk assessment shows air-purifying respirators are appropriate use a full-faced respirator with multi-purpose combination (US) or type ABEK (EN 14387) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full -faced supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

Environmental exposure controls: Do not empty into drains.

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

Appearance	Clear, colorless paste
Odor	Acetic Acid odor
Odor Threshold	2 ppm (Acetic Acid)
Molecular Weight	Not applicable
Chemical Formula	Not applicable
pH	No data available
Freezing/Melting Point, Range	No data available
Initial Boiling Point	No data available
Evaporation Rate	No data available
Flammability (solid, gas)	Not applicable
Flash Point	>100 °C (>212 °F), closed cup
Autoignition Temperature	No data available
Decomposition Temperature	No data available
Lower Explosive Limit (LEL)	No data available
Upper Explosive Limit (UEL)	No data available
Vapor Pressure	No data available
Vapor Density	No data available
Specific Gravity	1.007
Viscosity	No data available
Solubility in Water	Negligible
Partition Coefficient: n-octanol/water	Not determined
Volatiles by Volume @ 70° F	Not determined

9.2 Other data

No data available

SECTION 10 - STABILITY AND REACTIVITY

10.1 Reactivity

No special reactivity has been reported.
Hazardous polymerization does not occur.

10.2 Chemical stability

Stable under recommended storage conditions.

10.3 Possibility of hazardous reactions

None known

10.4 Conditions to avoid

Temperature extremes, incompatible materials, moisture

10.5 Incompatible materials

Oxidizing agents, water, moisture

10.6 Hazardous decomposition products

Thermal decomposition products include carbon oxides, acetic acid, silicon dioxide, formaldehyde.

SECTION 11 - TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

Acute Oral Toxicity

Expected to have low acute oral toxicity

Acute inhalation toxicity

Expected to have low acute inhalation toxicity

Acute dermal toxicity

Expected to have low acute dermal toxicity

Skin irritation

Causes skin irritation

Eye irritation

Causes moderate to severe eye irritation

Sensitization

No data available

Genotoxicity in vitro

No data available

Mutagenicity

No data available

Specific organ toxicity - single exposure

No data available

Specific organ toxicity - repeated exposure

No data available

Aspiration hazard

No data available

11.2 Further information

Silicon Dioxide (CAS #7631-86-9): IARC Group 3 Carcinogen - Not classifiable as to its carcinogenicity to humans. Not listed as a carcinogen by ACGIH, NTP or OSHA.

Reproductive effects have been reported in test animals exposed to Octamethylcyclotetrasiloxane (CAS #556-67-2).

No data is available regarding the mutagenicity or teratogenicity of this product nor is there available data that indicates that it causes adverse developmental or fertility effects in humans.

Handle in accordance with good industrial hygiene and safety practice.

SECTION 12 - ECOLOGICAL INFORMATION

12.1 Toxicity

Complete ecotoxicity data for this product is not yet available.

12.2 Persistence and degradability

Organic materials in this product is expected to biodegrade over time.

12.3 Bioaccumulation potential

Not expected to bioaccumulate

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

No data available

12.6 Other adverse effects

Additional ecological information

Do not allow material to run into surface waters, wastewater or soil.

An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.

SECTION 13 - DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods

The generation of waste should be avoided or minimized whenever possible. Although this product is classified as non-hazardous under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261 this material and its container should be disposed of in a safe way as empty containers may contain product residue. Leave chemicals in original containers. No mixing with other waste. Handle unclean containers like the product itself. Incinerate in an approved facility. Do not incinerate closed container. Dispose of in accordance with the Directive 2008/98/EC as well as other national, federal, state/provincial and local laws and regulations.

Hazardous waste: The classification of this product may meet the criteria for a hazardous waste.

SECTION 14 - TRANSPORT INFORMATION

Note: Transportation information provided is for reference only. Customer is urged to consult 49 CFR 100 - 177, IMDG, IATA, EC, United Nations TDG and WHMIS (Canada) TDG information manuals for detailed regulations and exceptions covering specific container sizes, packaging materials and methods of shipping.

NOT REGULATED FOR TRANSPORT

SECTION 15 - REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for substance or mixture

U. S. Federal Regulations

OSHA Hazard Communication Standard: This material is classified as hazardous in accordance with OSHA 29 CFR 1910-1200.

TSCA Status: All components of this product are listed or exempt from listing on the Toxic Substance Control Act (TSCA) Inventory.

Superfund Amendments and Reauthorization Act (SARA)

SARA Section 311/312 Hazard Categories: Acute Health Hazard

SARA 313 Information: This material is not subject to the reporting requirements of Section 313 of the Emergency Planning and Community Right-to Know Act of 1986.

SARA 302/304 Extremely Hazardous Substance

No components of the product are subject to the reporting requirements of these sections of Title III of SARA.

SARA 302/304 Emergency Planning & Notification:

No components of the product are subject to the reporting requirements of these sections of Title III of SARA.

Comprehensive Response Compensation and Liability Act (CERCLA): This product contains no CERCLA reportable substances.

Clean Air Act (CAA)

This product does not contain any substances listed as Hazardous Air Pollutants (HAPs) designated in CAA Section 112 (b).

This product does not contain any Class 1 Ozone depleters.

This product does not contain any Class 2 Ozone depleters.

Clean Water Act (CWA)

None of the chemicals in this product are listed as Hazardous Substances under the CWA.

None of the chemicals in this product are listed as Priority Pollutants under the CWA.

None of the chemicals in this product are listed as Toxic Pollutants under the CWA.

Distillates (Petroleum) Hydrotreated Middle (CAS #64742-46-7) is classified as an oil under Section 311 of the CWA and the Oil Pollution Act (OPA) of 1990.

U.S. State Regulations

California Prop 65, Safe Drinking Water and Toxic Enforcement Act of 1986:

Petroleum-based chemicals in this product may contain trace amounts of materials known to the State of California to cause cancer or reproductive harm.

Other U.S. State Inventories:

Silicon Dioxide (CAS #7631-86-9) is listed on the following State Hazardous Substance Inventories, Right-to-Know lists and/or Air Quality/Air Pollutants lists: CA, MA, MN, NJ, PA.

Canada

WHMIS Hazard Symbol and Classification:



D1B - Toxic material causing immediate and toxic effects

D2A - Very toxic material causing other toxic effects

D2B - Eye irritation - Skin irritation - Toxic material causing other toxic effects

Canadian Controlled Products Regulations (CPR): This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations, and the MSDS contains all the information required by the Controlled Products Regulations.

Canadian Ingredient Disclosure List (IDL): Silicon Dioxide (CAS #7631-86-9) is listed on the IDL.

Canadian National Pollutant Release Inventory (NPRI): None of the chemicals in this material are listed on the NPRI.

European Economic Community

Labeling (67/548/EEC or 1999/45/EC): None allocated

Risk Phrases: R34/38 - Irritating to the eyes and skin.

Safety Phrases: S2 - Keep out of reach of children.

S24/25 - Avoid contact with skin and eyes.

S41 - Use only in well ventilated areas.

WGK, Germany (Water danger/protection): 2

15.2 Chemical safety assessment

For this product a chemical safety assessment was not carried out.

SECTION 16 - OTHER INFORMATION

Hazardous Material Information System (HMIS)

Health	* 1
Flammability	1
Physical Hazard	0
Personal Protection	C


HMIS & NFPA Hazard Rating Legend

* = Chronic Health Hazard 2 = MODERATE
0 = INSIGNIFICANT 3 = HIGH
1 = SLIGHT 4 = EXTREME



National Fire Protection Association (NFPA)

Flammability



Full Text of Risk (R) – Phrases Referenced in Section 3.

R62 - Risk of impaired fertility.

R65 - Harmful: May cause lung damage if swallowed.

R53 - May cause long-term adverse effects in the aquatic environment.

The information herein is given in good faith and is believed to be accurate and correct; however, no warranty, expressed or implied, is made. EverKem Diversified Products assumes no responsibility for personal injury or property damage that may arise from the use of this material since the conditions of handling and use are beyond our control. It is the responsibility of the user to comply with all Federal, State and local laws and regulations regarding use of this product. Vendees or users assume all risks associated with the use of this material.

Revision 1: Updated to GHS SDS format, 23 August 2014

Preparation Date: 22 February 2011