

Prepared according to Global Harmonized System (GHS) standards

SECTION 1

CHEMICAL PRODUCT IDENTIFICATION

Fastenal Company 2001 Theurer Boulevard Winona, MN 55987 Tel: 763-417-1238 - Non-Emergency Questions

Product Trade Name:

Talon Compressor & Air Tool Lubricant

Mixture
N/A
0409873, 0409875, 0409877, 0409876, 0409874, 0409872
Lubricant
Not Determined.
6/3/2015
9/15/2015
1-800-424-9300 (CHEMTREC)
12159

SECTION 2

HAZARD IDENTIFICATION

Appearance: Odor:	Clear, Light Yellow Petroleum
Classification:	Hazardous to the aquatic environment (acute hazard) category 3
Target Organs:	Not applicable.
Pictogram(s):	
	None required.
Signal Word:	None required.
Hazard Statement:	H412 - Harmful to aquatic life with long lasting effects
Other Hazards:	Not determined.
Prevention:	P273 - Avoid release to the environment
Response:	None required.
Storage Procedures:	None required.
Disposal:	P501 - Dispose of contents and container in accordance with federal, state, and local
Other:	See section 11 for complete health hazard information.

SECTION 3

COMPOSITION OF INGREDIENTS

Component	CAS Number	Percentage (by weight)
Zinc alkyldithiophosphate	Proprietary	0.1-1.0%
Butylated phenol	128-39-2	0.1-1.0%
Aryl phosphite	101-02-0	<0.1%

The balance of components do not contribute to the overall classification of the fluid, according to the GHS Standard.




SECTION 4	FIRST AID MEASURES
Eye Contact:	If irritation occurs, cautiously rinse eyes with lukewarm, gently flowing water for 5 minutes, while holding the eyelids open. If eye irritation persists: Get medical advice/attention.
Skin Contact:	Call a doctor if you feel unwell.
Inhalation:	Get medical advice or attention if you feel unwell or are concerned.
Ingestion:	If you feel unwell or concerned: Get medical advice/attention. Rinse mouth. Do NOT induce vomiting. If vomiting occurs naturally, lie on your side, in the recovery position.
Other:	No additional information
SECTION 5	FIRE FIGHTING MEASURES
Flash Point:	Not determined.
Flammable limits:	Not determined.
Extinguishing media: Special firefighting procedures	Use dry chemical, alcohol foam, all purpose AFFF or carbon dioxide to extinguish fire. DO NOT direct a solid stream of water or foam into hot, burning pools of liquid since this may cause frothing and increase fire intensity. Frothing can be violent and possibly endanger any firefighter standing too close to the burning liquid. Use water spray to cool fire exposed containers and structures until fire is out if it can be done with minimal risk. Avoid spreading burning material with water used for cooling purposes. Wear full firefighting turn-out gear (full Bunker gear), and respiratory protection (SCBA).
Unusual fire & explosion hazards:	Dense smoke may be generated while burning. Toxic fumes, gases or vapors may evolve on burning. High temperatures may create heavy flammable vapors that may settle along ground level and low spots to create an invisible fire hazard.
Byproducts of combustion:	Fires involving this product may release oxides of carbon, phosphorus, nitrogen and sulfur; reactive hydrocarbons and irritating vapors.
Autoignition temperature:	Not determined.
Explosion data:	Not determined. Care should always be exercised in dust/mist areas.
Other:	Dispose of fire debris and contaminated extinguishing water in accordance with official regulations.

		_
СТ		
	 •	15

ACCIDENTAL RELEASE MEASURES

Spill control procedures (land):	Immediately turn off or isolate any source of ignition (pilot lights, electrical equipment, flames, heaters, etc.). Evacuate area and ventilate. Personnel wearing proper protective equipment should contain spill immediately with inert materials (sand, earth, chemical spill pads of cotton) by forming dikes. Dikes should be placed to contain spill in a manner that will prevent material from entering sewers and waterways. Large spill, once contained, may be picked up using explosion proof, non-sparking vacuum pumps, shovels, or buckets, and disposed of in suitable containers for disposal. Clean up residue with an appropriate solvent. If a large spill occurs notify appropriate authorities. In case of road spill or accident contact Chem-Trec (800-424-9300).
Spill control procedures (water):	Try to contain large spills with floating booms to prevent spill from spreading. Remove from surface by skimming or with suitable adsorbents. If a large spill occurs notify appropriate authorities (normally the National Response Center or Coast Guard at 800-424-8802).
Waste disposal method:	Do not empty into drains. All disposals must comply with federal, state, and local regulations. The material, if spilled or discarded may be a regulated waste. Refer to state and local regulations. Department of Transportation (DOT) regulations may apply for transporting this material when spilled. See Section 14.
Other:	CAUTION - If spilled material is cleaned up using a regulated solvent, the resulting waste mixture will be regulated.





SECTION 7	HANDLING AND STORAGE
Handling procedures:	Keep containers closed when not in use. Do not transfer to unmarked containers. Empty containers retain product residue which may exhibit hazards of material, therefore do not pressurize, cut, glaze, weld, or use for any other purposes. Return drums to reclamation centers for proper cleaning and reuse. Handling temperatures should not exceed 60°C (140°F) to min imize danger of burns. Open containers carefully in a well ventilated area or use appropriate respiratory protection. Wash thoroughly after handling.
Storage procedures:	Store containers away from heat, sparks, open flame, or oxidizing materials. Extended storage at excessive temperatures may produce odorous and toxic fumes from product decomposition.
Additional information:	No additional information.

SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure limits/standards for materials that can be formed when handling this product:

Contains highly refined petroleum oil		DSHA TWA *5 mg/m³ (PEL)	OSHA STEL *10 mg/m ³	ACGIH TWA *5 mg/m ³ (TLV)
	* Exposure limits not defined		re for, "oil mist".	(120)
	TWA – Time Weighted Avera any 8-hour work shift of a 40- STEL – Short Term Exposure average exposure which shal unless another time limit is sp	hour work week E Limit is the em Il not be exceed becified.	which shall not b ployee's 15-minut ed at any time dur	e exceeded. e time weighted ring a work day
	All base oils, including additiv	ve carriers, conta	ain <3.0% DMSO	extractable material.
Personal protection:	Applicable mainly to person product, service/maintenance			
Respiratory protection:	None required if ventilation meeting OSHA 1910.134 a misting may occur, wear a dust/mist air purifying respirat	nd ANSI Z88.2 n MSHA/NIOSH	2 requirements r	nust be followed. Where
Eye protection:	Eye protection is strongly r vented/splash proof goggles			
Hand protection:	Impervious, chemically resist sensitization and absorption.	tant gloves such	h as neoprene or	nitrile rubber to avoid skin
Other protection:	Use of an apron and overboon nitrile rubber is recommended material use insulated protect contaminated leather articles	ed based on lev tive equipment.	vel of activity and Launder soiled c	exposure. If handling hot lothes. Properly dispose of
Local control measures:	Use adequate ventilation wh methods such as fume hood areas. If vapor or mist is ge accordance with good engine below the specified exposur areas where this material is u	ls or area fans enerated when t eering practice r re. Eyewash st	may be used to r he material handl must be provided ations and show	educe localized vapor/mist led, adequate ventilation in to maintain concentrations
Other:	Consumption of food and o present. Always wash hand smoking.			-



SECTION 9

PHYSICAL AND CHEMICAL PROPERTIES

	-
Appearance:	Clear, Light Yellow
Odor:	Petroleum
Odor threshold:	Not determined.
pH:	Not applicable.
Melting/Freezing point:	Not determined.
Initial boiling point:	Not determined.
Boiling range:	Not determined.
Flash point:	207℃
Evaporation rate:	Not determined.
Flammability:	Not determined.
Upper flammable limit:	Not determined.
Lower flammable limit:	Not determined.
Vapor pressure:	Not determined.
Vapor density:	Not determined.
Relative density:	0.870 @ 15.6℃
Solubility:	Negligible in water, miscible in most petroleum solvents.
Partition Coefficient:	Not determined.
Auto-ignition temperature:	Not determined.
Decomposition temperature:	Not determined.
Viscosity:	31 cSt @ 40°C
Other	Not applicable.

SECTION 10

STABILITY AND REACTIVITY

Reactivity	
Chemical stability:	Material is chemically stable at room temperatures and pressure.
Hazardous polymerization:	Will not occur.
Conditions to avoid:	Avoid high temperatures and product contamination.
Incompatibility with other materials:	Avoid contact with acids and strong oxidizing materials.
Decomposition products:	Smoke, carbon monoxide, carbon dioxide, and other aldehydes of incomplete combustion. Oxides of carbon, nitrogen, and sulfur; reactive hydrocarbons and irritating vapors.
Other:	Not applicable.

Other:

SECTION 11

TOXICOLOGICAL INFORMATION

Acute toxicity (LD50) *See note at the bottom of the section 0----

>5000 mg/kg
>5000 mg/kg
>20.0 mg/l
Non-irritant
Non-irritant
Not expected to have a sensitizing effect.
Not expected to have a sensitizing effect.
Not applicable



Chronic Toxicity	
Mutagenicity:	Not suspected of causing genetic defects
Carcinogenicity:	Not suspected of causing cancer.
Reproductive toxicity:	Not expected to have adverse effects on reproduction.
STOT-single exposure:	Not expected to have adverse effects.
STOT-repeated exposure:	Not expected to have long term adverse effects.
Other:	*All data in this section is based off calculations from Part 3 of the Globally Harmonized System of Classification and Labelling of Chemicals (GHS) utilizing information from the constituent components.

SECTION 12

ECOLOGICAL INFORMATION

Environmental toxicity	
Fish:	> 100 mg/l.
Invertebrates:	> 100 mg/l.
Aquatic plants:	> 100 mg/l.
Microorganism:	> 100 mg/l.
Persistence/Degradability:	This product is not expected to be readily biodegradable.
Bioaccumulation:	Not determined.
Mobility in soil:	Not determined.
Other:	All classifications are based on calculations in Part 4 of the Globally Harmonized System of Classification and Labelling of Chemicals (GHS) utilizing information from the constituent components.

SECTION 13 DISPOSAL CONSIDERATIONS

Waste disposal:

Other

This product unadulterated by other materials can be classified as a non-hazardous waste. Depending on use, used product may be regulated. Dispose of in a licensed facility. Do not discharge product in to sewer system. Dispose of containers by crushing or puncturing, so as to prevent unauthorized use of used containers. Waste management should be in full compliance with federal, state, and local laws. The transportation, storage, treatment and disposal of RCRA waste material must be

conducted in compliance with 40 CFR 262, 263, 264, 268 and 270. Chemical additions, processing or otherwise altering this material may make the waste management information presented in this SDS incomplete, inaccurate or otherwise inappropriate.

SECTION 14

TRANSPORT INFORMATION

Land Transport (DOT): Proper Shipping Name: Land Transport (TDG): Proper Shipping Name: Sea Transport (IMDG): Proper Shipping Name: Air Transport (IATA): Proper Shipping Name: Other: Not Regulated. Not Applicable. Not Regulated. Not Applicable. Not Regulated. Not Applicable. Not Regulated. Not Applicable. Not Applicable.



SECTION 15

REGULATORY INFORMATION

Federal Regulation			
Clean water act/oil:	Under Section 311 of the Clean Water Act (40 CFR 110) and the Oil Pollution Control Act of 1990, this material is considered an oil. Any spill or discharges that produce a visible sheen or film on surface of water, or in waterways, ditches, or sewers leading to surface water must be reported. Contact the National Response Center at 800-424-8802.		
TSCA:	All components of this material are listed in the U.S. TSCA In	nventory.	
Other TSCA:	Not applicable.		
SARA title III:	Section 302/304 extremely hazardous substances:		
	None.		
	Section 311, 312 hazard categorization:		
	Acute (immediate health effects):	NO	
	Chronic (delayed health effects):	NO	
	Fire (hazard):	NO	
	Reactivity (hazard):	NO	
	Pressure (sudden release hazard):	NO	
	Section 313 toxic chemicals:		
	No components present are at or greater than the de m concentration requirements for reporting.	ninimis (minimum reportable)	
CERCLA:	For stationary/moving sources – reportable quantity (due to): Not hazardous due to the petroleum exclusion.		
State Regulations			
Right-to-know	Not determined.		
California Proposition 65	This product is known to cause cancer and/or birth defects, or According to the Safety Drinking Water and Toxic Enforcement	•	
Other:	A release of this product, as supplied, is exempt from report Environmental Response Compensation and Liability Act (C may be reportable to the Nation Response Center under the 1321(b)(3) and (5) - see head of Section 15. Failure to re- civil and criminal penalties.	CERCLA). However, releases e Clean Water Act, 33 U.S.C. port may result in substantial	
	Recommend contacting the local authorities in the event of	any type of spill to determine	

local reporting requirements and also to aid in the cleanup.

OTHER INFORMATION			
NFPA 704	NPCA-HMIS	KEY	
1	1	0 = Minimal	
1	1	1 = Slight	
0	0	2 = Moderate	
None	N/A	3 = Serious	
N/A	В	4 = Severe	
	1 1 0 None	1 1 1 1 0 0 None N/A	

Version: II

INFORMATION PROVIDED IN THIS SDS IS CONSIDERED ACCURATE AND RELIABLE BASED ON INFORMATION ISSUED FROM INTERNAL AND OUTSIDE SOURCES TO THE BEST OF THE AUTHORS' KNOWLEDGE. HOWEVER, THE AUTHOR'S MAKE NO REPRESENTATIONS, GUARANTEES OR WARRANTIES, EXPRESSED OR IMPLIED, OF MERCHANTABILITY OR FITNESS FOR THE PARTICULAR PURPOSE, REGARDING THE ACCURACY OF SUCH INFORMATION OR THE RESULT TO BE OBTAINED FROM THE USE THEREOF, OR AS TO THE SUFFICIENCY OF THE INFORMATION HEREIN PRESENTED. THE AUTHORS ASSUME NO RESPONSIBILITY FOR INJURY TO RECIPIENT OR TO THIRD PERSONS OR FOR ANY DAMAGE TO ANY PROPERTY AND RECIPIENT ASSUMES ALL SUCH RISKS.

Section 15 update 9/15/2015